Printing date 06/07/2024 Reviewed on 06/07/2024

1 Identification

· Product identifier

· Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

· Article number: LEI014

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department: Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



k

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 3

H311 Toxic in contact with skin.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed. H315 Causes skin irritation.

Skin Irritation 2 Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 1)

· Hazard-determining components of labeling:

Cyclohexanone 99.8% Methyl Ethyl Ketone

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v /
Methyl Ethyl Ketone 60% v/v

(Contd. of page 2)

· vPvB: Not applicable.

*

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 78-93-3	Methyl Ethyl Ketone	55.998%
CAS: 108-94-1	Cyclohexanone 99.8%	44.002%

*

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- $\cdot \textbf{\textit{After swallowing:}} \ Immediately \ call \ a \ doctor.$
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 78-93-3	Methyl Ethyl Ketone	200 ppm
CAS: 108-94-1	Cyclohexanone 99.8%	60 ppm
· PAC-2:		
CAS: 78-93-3	Methyl Ethyl Ketone	2700* ppm
CAS: 108-94-1	Cyclohexanone 99.8%	830 ppm
· PAC-3:		
CAS: 78-93-3	Methyl Ethyl Ketone	4000* ppm
CAS: 108-94-1	Cyclohexanone 99.8%	5000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 78-93-3 Methyl Ethyl Ketone

PEL Long-term value: 590 mg/m³, 200 ppm

(Contd. on page 5)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 4)

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm TLV Short-term value: NIC-150 (300) ppm

Long-term value: NIC-75 (200) ppm

BEI, NIC-Skin

CAS: 108-94-1 Cyclohexanone 99.8%

PEL Long-term value: 200 mg/m³, 50 ppm REL Long-term value: 100 mg/m³, 25 ppm

Skin

TLV Short-term value: 50 ppm Long-term value: 20 ppm

Skin, BEI, A3

· Ingredients with biological limit values:

CAS: 78-93-3 Methyl Ethyl Ketone

BEI 2 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methyl ethyl ketone (nonspecific)

CAS: 108-94-1 Cyclohexanone 99.8%

BEI 80 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek

LD50: 1.2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)

8 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Clear · Odor: Distinct · Odor threshold: Not determined.

Not determined. · pH-value:

· Change in condition

Melting point/Melting range: Undetermined.

79-80.5 °C (174.2-176.9 °F) Boiling point/Boiling range:

-4 °C (24.8 °F) · Flash point:

· Flammability (solid, gaseous): Highly flammable.

420 °C (788 °F) · Auto igniting:

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

Not determined.

· Explosion limits:

· Decomposition temperature:

Lower: 1.3 Vol % Upper: 11.5 Vol %

· Vapor pressure at 20 °C (68 °F): 105 hPa (78.8 mm Hg)

· Density at 20 °C (68 °F): 0.86936 g/cm³ (7.25481 lbs/gal)

· Relative density Not determined. · Vapor density Not determined. · Evaporation rate

Not determined.

(Contd. on page 7)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

		Contd. of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/v	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	869.4 g/l / 7.26 lb/gal	
Solids content:	44.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)				
Oral	LD50	1,136 mg/kg		
Dermal	LD50	682 mg/kg		
Inhalative	LC50/4h	25 mg/l		

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic Harmful

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

CAS: 108-94-1 Cyclohexanone 99.8%

3

(Contd. on page 8)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, IMDG, IATA	UN1993	
· UN proper shipping name · DOT	Flammable liquids, n.o.s. (Methyl Ethyl Ketone	
· IMDG, IATA	, Cyclohexanone) FLAMMABLE LIQUID, N.O.S. (Methyl Ethyl Ketone	

(Contd. on page 9)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 8) · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids · Label · IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, IMDG, IATA II· Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E· Stowage Category В · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL ETHYL **KETONE** , CYCLOHEXANONE), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 10)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 9) · Sara · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): None of the ingredients is listed. · TSCA (Toxic Substances Control Act): Methyl Ethyl Ketone **ACTIVE** Cyclohexanone 99.8% *ACTIVE* · Hazardous Air Pollutants None of the ingredients is listed. · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 78-93-3 Methyl Ethyl Ketone Ι · TLV (Threshold Limit Value) CAS: 108-94-1 Cyclohexanone 99.8% *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health)

- None of the ingredients is listed.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).



· Hazard pictograms





GHS02

· Signal word Danger

· Hazard-determining components of labeling:

Cyclohexanone 99.8% Methyl Ethyl Ketone

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin.

Causes skin irritation.

(Contd. on page 11)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 10)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

06/07/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 12)

Printing date 06/07/2024 Reviewed on 06/07/2024

Trade name: Cyclohexanone 40% v/v / Methyl Ethyl Ketone 60% v/v

(Contd. of page 11)

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 4: Acute toxicity – Category 4

Acute Toxicity - Dermal 3: Acute toxicity - Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

HS