Printing date 07/24/2024

Reviewed on 07/24/2024

Identification		
Product identifier		
Trade name: <u>Potassium Hydroxia</u> in IPA, NIST Traced		
Article number: AM033		
Details of the supplier of the safet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	ty data sheet	AQUA SOLUTIONS
Information department: Technical Coordinator Sherman Nelson shermann@aquas Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	solutions.org	
Hazard(s) identification		
GHS02 Flame		
GHS02 Flame Flammable Liquids 2 GHS07	H225 Highly flat	mmable liquid and vapor.
Flammable Liquids 2		
Flammable Liquids 2 GHS07 Eye Irritation 2A		rious eye irritation.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements	H319 Causes set Single Exposure 3 H336 May cause	rious eye irritation.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - Sa Label elements GHS label elements The product in Hazard pictograms Flammable Liquids 2 Hazard pictograms	H319 Causes set Single Exposure 3 H336 May cause	rious eye irritation. e drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Isopropanol Hazard statements Highly flammable liquid and vapor Causes serious eye irritation. May cause drowsiness or dizziness	H319 Causes set Single Exposure 3 H336 May cause is classified and labeled according of labeling: pr.	rious eye irritation. e drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product in Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Isopropanol Hazard statements Highly flammable liquid and vapor Causes serious eye irritation. May cause drowsiness or dizziness Precautionary statements	H319 Causes set Single Exposure 3 H336 May cause is classified and labeled according of labeling: or. s. flames/hot surfaces No smoking.	rious eye irritation. e drowsiness or dizziness. to the Globally Harmonized System (GHS,

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 1) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. *Continue rinsing.* Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH ² Health = 2FIRE ³ *Fire* = 3 **REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
CAS: 67-63-0 Isopropanol	99.873%
• Table of Nonhazardous Ingredients	
CAS: 1310-58-3 Potassium Hydroxide	0.089%
CAS: 12230-71-6 Barium Hydroxide	0.038%

4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

US

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 2)

- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

	o ns, protective equipment and emergency procedures nuipment. Keep unprotected persons away.	
	ecautions: Do not allow to enter sewers/ surface or ground water.	
	erial for containment and cleaning up:	
	-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	ated material as waste according to section 13.	
Ensure adequate v		
· Reference to other		
	nformation on safe handling.	
	nformation on personal protection equipment.	
	disposal information.	
	Criteria for Chemicals	
• PAC-1:		
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 1310-58-3	Potassium Hydroxide	0.18 mg/m ³
CAS: 12230-71-6	Barium Hydroxide	3.4 mg/m ³
· PAC-2:		
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 1310-58-3	Potassium Hydroxide	$2 mg/m^3$
CAS: 12230-71-6	Barium Hydroxide	420 mg/m ³
· PAC-3:		·
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 1310-58-3	Potassium Hydroxide	54 mg/m ³
	Barium Hydroxide	$2,500 \text{ mg/m}^3$

(Contd. on page 4)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 3)

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Comp	ponents with limit values that require monitoring at the workplace:
CAS:	67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm
	Long-term value: 200 ppm
	BEI, A4
· Ingre	dients with biological limit values:
CAS:	67-63-0 Isopropanol
	40 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift at end of workweek
	LD50: Acetone (background, nonspecific)
· Addit	ional information: The lists that were valid during the creation were used as basis.
· Expo	sure controls
· Perso	nal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing.
	hands before breaks and at the end of work.
	contact with the eyes.
	contact with the eyes and skin.
	hing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use ratory protective device that is independent of circulating air.
respi	(Contd. on page 5)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear to slightly hazy
Odor:	IPA
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-89.5 °C (-129.1 °F)
Boiling point/Boiling range:	82 °C (179.6 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	2 Vol %

US

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

	(Co	ntd. of page
Upper:	12 Vol %	
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)	
• Density at 20 °C (68 °F):	0.78562 g/cm ³ (6.556 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	<i>99.9</i> %	
VOC content:	99.87 %	
	784.6 g/l / 6.55 lb/gal	
Solids content:	0.1 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- CAS: 67-63-0 Isopropanol

(Contd. on page 7)

3

US -

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Isopropanol	
)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Isopropanol	
)	
Transport hazard class(es)		
DOT		
PLAMMABLE LIQUD		
3		
Class	3 Flammable liquids	

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

	(Contd. of pag
Label	3
IMDG, IATA	
Class	2 Elammahla lianida
Label	3 Flammable liquids 3
	5
Packing group	П
DOT, IMDG, IATA	11
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL
), <i>3</i> , <i>11</i>

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

• Section 355 (extremely hazardous substances):			
None of the ingredients is listed.			
· Section 313 (Specific toxic chemical listings):			
CAS: 67-63-0	Isopropanol		
CAS: 12230-71-6	Barium Hydroxide		
· TSCA (Toxic Substances Control Act):			
Isopropanol ACTIVE			
Potassium Hydroxide ACTIVE			
	(Contd. on page 9)		

Printing date 07/24/2024

Reviewed on 07/24/2024

D, CBD(inh), NL(oral)

A4

A4

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 8)

• *Hazardous Air Pollutants* None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 12230-71-6 Barium Hydroxide

· TLV (Threshold Limit Value)

CAS: 67-63-0 Isopropanol

CAS: 12230-71-6 Barium Hydroxide

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Isopropanol · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 10)

US

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: Potassium Hydroxide 0.01 N in IPA, NIST Traceable

(Contd. of page 9) If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision:

• Date of preparation / last revision Revision 1.2 07/24/2024: Reviewed SDS for accuracy. MH/STN Creation Date for SDS 12-03-2014 STN 07/24/2024 / 1.0

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit **BEI:** Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.

· US ·