

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

1 Identification

- **Product identifier**
- **Trade name:** Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17
- **Article number:** SPX773
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**
Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 1)

- **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 2)

· Dangerous components:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	99.744%
CAS: 5137-55-3	methyltrioctylammonium chloride	0.254%
· Table of Nonhazardous Ingredients		
CAS: 7758-95-4	Lead Chloride	0.002%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
 Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	0.67 mg/m ³
CAS: 7758-95-4	Lead Chloride	0.2 mg/m ³
· PAC-2:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	7.4 mg/m ³
CAS: 7758-95-4	Lead Chloride	160 mg/m ³
· PAC-3:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	44 mg/m ³
CAS: 7758-95-4	Lead Chloride	940 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
 At this time, the remaining constituent has no known exposure limits.

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	
PEL	Long-term value: 410 mg/m ³ , 100 ppm

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 4)

REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3

· **Ingredients with biological limit values:**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

BEI	1 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: MIBK
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Clear water white
Odor:	Distinct
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	-83.5 °C (-118.3 °F)
Boiling point/Boiling range:	114 °C (237.2 °F)

· **Flash point:** 14 °C (57.2 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 460 °C (860 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.7 Vol %
Upper:	9 Vol %

· **Vapor pressure at 20 °C (68 °F):** 8 hPa (6 mm Hg)

· **Density at 20 °C (68 °F):** 0.82072 g/cm³ (6.84891 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water at 20 °C (68 °F): 19 g/l

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic at 20 °C (68 °F):	0.59 mPas
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	99.7 %
VOC content:	99.74 %
	818.6 g/l / 6.83 lb/gal

Solids content: 0.0 %

· **Other information** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	87,859 mg/kg (rat)
Inhalative	LC50/4h	11 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 The product shows the following dangers according to internally approved calculation methods for preparations:
 Harmful
 Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B
CAS: 7758-95-4	Lead Chloride	2A

· **NTP (National Toxicology Program)**

CAS: 7758-95-4	Lead Chloride	R
----------------	---------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17



(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1197
- **UN proper shipping name**
- **DOT** Extracts, flavoring, liquid
- **IMDG** EXTRACTS, LIQUID
- **IATA** Extracts, liquid
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, IMDG, IATA** II
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Warning: Flammable liquids
- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E,S-D
- **Stowage Category** B

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 8)

- | | |
|--|---|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1197 EXTRACTS, LIQUID, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
 No further relevant information available.
- Sara**

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 108-10-1 | Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 | Lead Chloride

· TSCA (Toxic Substances Control Act):

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	ACTIVE
---	--------

methyltrioctylammonium chloride	ACTIVE
---------------------------------	--------

Lead Chloride	ACTIVE
---------------	--------

· Hazardous Air Pollutants

CAS: 108-10-1 | Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 | Lead Chloride

· Proposition 65

· Chemicals known to cause cancer:

CAS: 108-10-1 | Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 | Lead Chloride

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-10-1 | Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 9)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	I
CAS: 7758-95-4	Lead Chloride	B2

· **TLV (Threshold Limit Value)**

CAS: 7758-95-4	Lead Chloride	A3
----------------	---------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2024

Reviewed on 06/10/2024

Trade name: Lead Standard Solution 0.05 g Pb/gal
Prepared to ASTM D3237-17

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

Date of Preparation / Last Revision:

· **Date of preparation / last revision**

Revision 1.2, 06/10/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

06/10/2024 / 1.0

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**