Printing date 06/10/2024 Reviewed on 06/10/2024

#### 1 Identification

· Product identifier

• Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

· Article number: SPX771

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department: Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



\*

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS05 Corrosion

Eye Damage 1

H318 Causes serious eye damage.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

GHS08

(Contd. on page 2)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 1)

#### · Signal word Danger

#### · Hazard-determining components of labeling:

*Methyl Isobutyl Ketone (4-Methyl-2-pentanone)* 

methyltrioctylammonium chloride

#### · Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye damage.

Suspected of causing cancer.

May cause drowsiness or dizziness.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

*Immediately call a poison center/doctor.* 

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 3

Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = \*3

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 2)

\*

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

|   | · Dangerous components: |   |         |
|---|-------------------------|---|---------|
| CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) |                         | Methyl Isobutyl Ketone (4-Methyl-2-pentanone) | 96.901% |
|   | CAS: 5137-55-3          | methyltrioctylammonium chloride               | 3.063%  |
| · Table of Nonhazardous Ingredients                         |                         |   |         |
|   | CAS: 7758-95-4          | Lead Chloride                                 | 0.035%  |

\*

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 3)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · PAC-1:  |   |                        |
|---|---|------------------------|
| CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) |   | 75 ppm                 |
| CAS: 5137-55-3  | methyltrioctylammonium chloride               | 0.67 mg/m <sup>3</sup> |
| CAS: 7758-95-4  | Lead Chloride                                 | 0.2 mg/m <sup>3</sup>  |
| · PAC-2:  |   |                        |
| CAS: 108-10-1   | Methyl Isobutyl Ketone (4-Methyl-2-pentanone) | 500 ppm                |
| CAS: 5137-55-3  | methyltrioctylammonium chloride               | 7.4 mg/m <sup>3</sup>  |
| CAS: 7758-95-4  | Lead Chloride                                 | $160 \text{ mg/m}^3$   |
| · PAC-3:  |   |                        |
| CAS: 108-10-1   | Methyl Isobutyl Ketone (4-Methyl-2-pentanone) | 3000* ppm              |
| CAS: 5137-55-3  | methyltrioctylammonium chloride               | 44 mg/m³               |
| CAS: 7758-95-4  | Lead Chloride                                 | 940 mg/m³              |

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 4)

#### CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

PEL Long-term value: 410 mg/m³, 100 ppm REL Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 75 ppm Long-term value: 20 ppm BEI. A3

#### · Ingredients with biological limit values:

#### CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

BEI 1 mg/L

LD50 Intraperitoneal: urine

Time: end of shift LD50: MIBK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

*Store protective clothing separately.* 

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

· Body protection: Protective work clothing

(Contd. of page 5)

| Information on basic physical and c                      | hemical properties  |
|--|---|
| General Information                                      |   |
| Appearance:  |   |
| Form:<br>Color:  | Fluid   |
| Cotor: Odor:   | According to product specification Characteristic   |
| Odor threshold:  | Not determined.   |
| pH-value:  | Not determined.   |
| Change in condition                                      |   |
| Melting point/Melting range:                             | -83.5 °C (-118.3 °F)  |
| Boiling point/Boiling range:                             | 114 °C (237.2 °F)   |
| Flash point:   | 14 °C (57.2 °F)   |
| Flammability (solid, gaseous):                           | Highly flammable.   |
| Auto igniting:   | 460 °C (860 °F)   |
| Decomposition temperature:                               | Not determined.   |
| Ignition temperature:                                    | Product is not selfigniting.  |
| Danger of explosion:                                     | Product is not explosive. However, formation of explosive air/vapo mixtures are possible. |
| Explosion limits:  |   |
| Lower:   | 1.7 Vol %   |
| Upper:   | 9 Vol %   |
| Vapor pressure at 20 °C (68 °F):                         | 8 hPa (6 mm Hg)   |
| Density at 20 °C (68 °F):                                | $1.00116 \ g/cm^3 (8.35468 \ lbs/gal)$  |
| Relative density   | Not determined.   |
| Vapor density  | Not determined.   |
| Evaporation rate   | Not determined.   |
| Solubility in / Miscibility with Water at 20 °C (68 °F): | 19 g/l  |
| Partition coefficient (n-octanol/wate                    | r): Not determined.   |
| Viscosity:   |   |
| Dynamic:   | Not determined.   |
| Kinematic:   | Not determined.   |
| Solvent content:   |   |
| Organic solvents:  | 96.9 %  |
| VOC content:   | 96.90 %   |
|  | 970.1 g/l / 8.10 lb/gal   |
| Solids content:  | 0.0 %   |

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 6)

· Other information

No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50  | · LD/LC50 values that are relevant for classification: |                   |  |
|------------|--|-------------------|--|
| ATE (Acu   | te Toxicity  | Estimate)         |  |
| Oral       | LD50   | 7,279 mg/kg (rat) |  |
| Inhalative | LC50/4h  | 11.4 mg/l (ATE)   |  |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- $\cdot$  on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

| Carcinogenic categories                                 |   |    |  |
|---|---|----|--|
| · IARC (International Agency for Research on Cancer)    |   |    |  |
| CAS: 108-10-1   | Methyl Isobutyl Ketone (4-Methyl-2-pentanone) | 2B |  |
| CAS: 7758-95-4  | Lead Chloride                                 | 2A |  |
| · NTP (National T                                       | · NTP (National Toxicology Program)           |    |  |
| CAS: 7758-95-4  | Lead Chloride                                 | R  |  |
| · OSHA-Ca (Occupational Safety & Health Administration) |   |    |  |
| None of the ingredients is listed.                      |   |    |  |

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| 7 4 5 |         |           |         |
|-------|---------|-----------|---------|
| 74    | ransno  | rt inta   | rmation |
|       | Turispo | i i iiijo | THURST  |

| · UN-Number<br>· DOT, IMDG, IATA   | UN1992  |
|------------------------------------|---|
| · UN proper shipping name<br>· DOT | Flammable liquids, toxic, n.o.s. (methyltrioctylammonium chloride)                  |
| · IMDG                             | FLAMMABLE LIQUID, TOXIC, N.O.S. (methyltrioctylammonium chloride), MARINE POLLUTANT |
| · IATA                             | FLAMMABLE LIQUID, TOXIC, N.O.S. (methyltrioctylammonium                             |

chloride)

- · Transport hazard class(es)
- $\cdot DOT$



· Class
· Label
3 Flammable liquids
3, 6.1

· IMDG







· Class 3 Flammable liquids

(Contd. on page 9)

Reviewed on 06/10/2024 Printing date 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

|   | (Contd. of page                                  |
|---|--|
| Label   | 3/6.1  |
| IATA  |  |
|   |  |
| Class   | 3 Flammable liquids                              |
| Label   | 3 (6.1)  |
| Packing group   |  |
| DOT, IMDG, IATA   | II   |
| Environmental hazards:  |  |
| Marine pollutant:   | Symbol (fish and tree)                           |
| Special precautions for user  | Warning: Flammable liquids                       |
| Hazard identification number (Kemler code)                              |  |
| EMS Number:   | F-E,S-D  |
| Stowage Category  | B CIVIC CI.                                      |
| Stowage Code  | SW2 Clear of living quarters.                    |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable.                                  |
| Transport/Additional information:                                       |  |
| DOT   |  |
| Quantity limitations  | On passenger aircraft/rail: 1 L                  |
| -   | On cargo aircraft only: 60 L                     |
| IMDG  |  |
| Limited quantities (LQ)   | 1L   |
| Excepted quantities (EQ)  | Code: E2   |
|   | Maximum net quantity per inner packaging: 30 ml  |
|   | Maximum net quantity per outer packaging: 500 ml |
| UN "Model Regulation":  | UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.            |
| •   | (METHYLTRIOCTYLAMMONIUM CHLORIDE), 3 (6.1), II   |

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

| · Sara  |   |        |  |
|---|---|--------|--|
| · Section 355 (ext                                | · Section 355 (extremely hazardous substances):   |        |  |
| None of the ingre                                 | None of the ingredients is listed.                |        |  |
| · Section 313 (Spe                                | · Section 313 (Specific toxic chemical listings): |        |  |
| CAS: 108-10-1                                     | Methyl Isobutyl Ketone (4-Methyl-2-pentanone)     |        |  |
| CAS: 7758-95-4                                    | Lead Chloride                                     |        |  |
| · TSCA (Toxic Su                                  | · TSCA (Toxic Substances Control Act):            |        |  |
| Methyl Isobutyl Ketone (4-Methyl-2-pentanone)  AC |   | ACTIVE |  |
| methyltrioctylammonium chloride A                 |   | ACTIVE |  |

(Contd. on page 10)

Reviewed on 06/10/2024 Printing date 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

| Lead Chloride   |  | (Contd. of page ACTIVE |
|---|--|------------------------|
| Hazardous Air Pollu   | tants                                      |                        |
| CAS: 108-10-1 Met   | hyl Isobutyl Ketone (4-Methyl-2-pentanone) |                        |
| CAS: 7758-95-4 Lea  | d Chloride                                 |                        |
| Proposition 65  |  |                        |
| Chemicals known to  | cause cancer:                              |                        |
| CAS: 108-10-1 Met   | hyl Isobutyl Ketone (4-Methyl-2-pentanone) |                        |
| CAS: 7758-95-4 Lea  | d Chloride                                 |                        |
| Chemicals known to cause reproductive toxicity for females: |  |                        |
| None of the ingredients is listed.                          |  |                        |
| Chemicals known to  | cause reproductive toxicity for males:     |                        |
| None of the ingredients is listed.                          |  |                        |
| Chemicals known to cause developmental toxicity:            |  |                        |
| CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) |  |                        |

#### · Carcinogenic categories

| · EPA (Environmental Protection Agency)  |                               |   |    |
|--|-------------------------------|---|----|
| CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) CAS: 7758-95-4 Lead Chloride |                               | Methyl Isobutyl Ketone (4-Methyl-2-pentanone) | I  |
|  |                               | Lead Chloride                                 | B2 |
|  | · TLV (Threshold Limit Value) |   |    |
|  | CAS: 7758-95-4                | Lead Chloride                                 | A3 |

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

· Signal word Danger

#### · Hazard-determining components of labeling:

Methyl Isobutyl Ketone (4-Methyl-2-pentanone) methyltrioctylammonium chloride

#### · Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye damage.

Suspected of causing cancer.

May cause drowsiness or dizziness.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

(Contd. on page 11)

Printing date 06/10/2024 Reviewed on 06/10/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 10)

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 06/10/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

06/10/2024 / 1.0

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$ 

 ${\it IATA: International Air Transport Association}$ 

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

US