

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

## 1 Identification

- **Product identifier**
- **Trade name:** *o-Xylene, Certified*
- **Article number:** X7514
- **CAS Number:**  
95-47-6
- **EC number:**  
202-422-2
- **Index number:**  
601-022-00-9
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Aqua Solutions, Inc.  
6913 Highway 225  
DEER PARK, TX 77536  
USA  
800-256-2586
- **Information department:**  
Technical Coordinator  
Sherman Nelson sherman@aquasolutions.org  
Technical Coordinator  
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**  
Chemtrec: 800-424-9300  
Canutec: 613-996-6666



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning

- **Hazard statements**

Flammable liquid and vapor.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

**Trade name: o-Xylene, Certified**

(Contd. of page 1)

*Harmful in contact with skin or if inhaled.*

*Causes skin irritation.*

**· Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Keep container tightly closed.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*Call a poison center/doctor if you feel unwell.*

*Specific treatment (see on this label).*

*Take off contaminated clothing and wash it before reuse.*

*If skin irritation occurs: Get medical advice/attention.*

*In case of fire: Use for extinction: CO2, powder or water spray.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· Classification system:**

**· NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

**· Other hazards**

**· Results of PBT and vPvB assessment**

**· PBT:** Not applicable.

**· vPvB:** Not applicable.

## 3 Composition/information on ingredients

**· Chemical characterization: Substances**

**· CAS No. Description**

95-47-6 o-Xylene

**· Identification number(s)**

**· EC number:** 202-422-2

**· Index number:** 601-022-00-9

US

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

Trade name: *o*-Xylene, Certified

(Contd. of page 2)

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
- **PAC-1:** Substance is not listed.
- **PAC-2:** Substance is not listed.
- **PAC-3:** Substance is not listed.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

Trade name: *o*-Xylene, Certified

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 95-47-6 *o*-Xylene

|     |   |
|-----|---|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm |
| BEI |   |

- **Ingredients with biological limit values:**

CAS: 95-47-6 *o*-Xylene

|     |   |
|-----|---|
| BEI | 1.5 g/g creatinine<br>LD50 Intraperitoneal: urine<br>Time: end of shift<br>LD50: Methylhippuric acids |
|-----|---|

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

Trade name: *o*-Xylene, Certified

(Contd. of page 4)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

|                        |                 |
|------------------------|-----------------|
| <b>Form:</b>           | Liquid          |
| <b>Color:</b>          | Clear           |
| <b>Odor:</b>           | Distinct        |
| <b>Odor threshold:</b> | Not determined. |

- **pH-value:** Not determined.

- **Change in condition**

|                                     |                     |
|-------------------------------------|---------------------|
| <b>Melting point/Melting range:</b> | -25.2 °C (-13.4 °F) |
| <b>Boiling point/Boiling range:</b> | 144.4 °C (291.9 °F) |

- **Flash point:** 17-30 °C (62.6-22 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 465 °C (869 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

|               |           |
|---------------|-----------|
| <b>Lower:</b> | 1.7 Vol % |
| <b>Upper:</b> | 7.6 Vol % |

- **Vapor pressure at 20 °C (68 °F):** 6.7 hPa (5 mm Hg)

- **Density at 20 °C (68 °F):** 0.878 g/cm<sup>3</sup> (7.32691 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

**Water at 20 °C (68 °F):** 0.2 g/l

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

|                                  |                 |
|----------------------------------|-----------------|
| <b>Dynamic at 20 °C (68 °F):</b> | 0.81 mPas       |
| <b>Kinematic:</b>                | Not determined. |

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

Trade name: *o*-Xylene, Certified

(Contd. of page 5)

· **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

|            |         |                   |
|------------|---------|-------------------|
| Dermal     | LD50    | 1,100 mg/kg (ATE) |
| Inhalative | LC50/4h | 11 mg/l (ATE)     |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)** 3
- **NTP (National Toxicology Program)** Substance is not listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Water hazard class 2 (Assessment by list): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020



Trade name: *o*-Xylene, Certified

(Contd. of page 6)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>· UN-Number</li> <li>· DOT, IMDG, IATA</li> </ul>   | <p style="text-align: right;">UN1307</p>  |
| <ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· DOT</li> <li>· IMDG, IATA</li> </ul>   | <p style="text-align: right;">Xylenes<br/>XYLENES</p>   |
| <ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· DOT</li> </ul>  | <div style="text-align: right;">  </div>  |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>   | <p style="text-align: right;">3 Flammable liquids<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· IMDG, IATA</li> </ul>   | <div style="text-align: right;">  </div> |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>   | <p style="text-align: right;">3 Flammable liquids<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· Packing group</li> <li>· DOT, IMDG, IATA</li> </ul>   | <p style="text-align: right;">III</p>   |
| <ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>  | <p style="text-align: right;">No</p>  |
| <ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul> | <p style="text-align: right;">Warning: Flammable liquids<br/>33<br/>F-E,S-D<br/>B</p>                                       |
| <ul style="list-style-type: none"> <li>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> </ul>  | <p style="text-align: right;">Not applicable.</p>   |
| <ul style="list-style-type: none"> <li>· Transport/Additional information:</li> <li>· DOT</li> <li>· Quantity limitations</li> <li>· Hazardous substance:</li> </ul>                       | <p style="text-align: right;">On passenger aircraft/rail: 5 L<br/>On cargo aircraft only: 60 L<br/>1000 lbs, 454 kg</p>     |

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

Trade name: *o*-Xylene, Certified

(Contd. of page 7)

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul> | <p style="margin-left: 20px;"><i>IL</i></p> <p style="margin-left: 20px;">Code: E2</p> <p style="margin-left: 20px;">Maximum net quantity per inner packaging: 30 ml</p> <p style="margin-left: 20px;">Maximum net quantity per outer packaging: 500 ml</p> |
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>  | <p style="margin-left: 20px;"><i>UN 1307 XYLENES, 3, III</i></p>  |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is not listed.
- **Section 313 (Specific toxic chemical listings):** Substance is listed.
- **TSCA (Toxic Substances Control Act):** ACTIVE
- **Hazardous Air Pollutants** Substance is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency) I**
- **TLV (Threshold Limit Value established by ACGIH) A4**
- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02    GHS07

- **Signal word** Warning
- **Hazard statements**
  - Flammable liquid and vapor.
  - Harmful in contact with skin or if inhaled.
  - Causes skin irritation.
- **Precautionary statements**
  - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
  - Keep container tightly closed.
  - Ground/bond container and receiving equipment.
  - Use explosion-proof electrical/ventilating/lighting/equipment.
  - Use only non-sparking tools.
  - Take precautionary measures against static discharge.
  - Avoid breathing dust/fume/gas/mist/vapors/spray
  - Wash thoroughly after handling.
  - Use only outdoors or in a well-ventilated area.
  - Wear protective gloves/protective clothing/eye protection/face protection.
  - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
  - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
  - Call a poison center/doctor if you feel unwell.

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 11/04/2020

Reviewed on 11/04/2020

**Trade name: o-Xylene, Certified**

(Contd. of page 8)

*Specific treatment (see on this label).*

*Take off contaminated clothing and wash it before reuse.*

*If skin irritation occurs: Get medical advice/attention.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

Revision 0.1, 07-10-2019: updated first aid statements. STN

Revision 1.0, 11-04-2020: Changed DOT packing group from II to III. STN

11/04/2020 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2