

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

## 1 Identification

- **Product identifier**
- **Trade name:** Stainless Steel Etchant Solution
- **Article number:** SPE389
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Aqua Solutions, Inc.  
6913 Highway 225  
DEER PARK, TX 77536  
USA  
800-256-2586
- **Information department:**  
Technical Coordinator  
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**  
Chemtrec: 800-424-9300  
Canutec: 613-996-6666



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS05



GHS07



GHS08

(Contd. on page 2)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Hydrochloric Acid*

*Sulfuric Acid 96 - 98%*

*Ferric Chloride Hexahydrate*

*Nitric Acid*

*Acetic Acid*

· **Hazard statements**

*Flammable liquid and vapor.*

*Causes severe skin burns and eye damage.*

*May cause cancer.*

*May cause respiratory irritation.*

· **Precautionary statements**

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Do not breathe dusts or mists.*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Rinse mouth. Do NOT induce vomiting.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Immediately call a poison center/doctor.*

*IF exposed or concerned: Get medical advice/attention.*

*Specific treatment (see on this label).*

*Wash contaminated clothing before reuse.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



*Health = 3*

*Fire = 2*

*Reactivity = 0*

· **HMIS-ratings (scale 0 - 4)**



*Health = \*3*

*Fire = 2*

*Reactivity = 0*

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 2)

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 7647-01-0	Hydrochloric Acid	38.482%
CAS: 10025-77-1	Ferric Chloride Hexahydrate	14.9701%
CAS: 64-19-7	Acetic Acid	14.308%
CAS: 7697-37-2	Nitric Acid	13.615%
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	5.0004%

- **Table of Nonhazardous Ingredients**

CAS: 7732-18-5	Water	13.624%
----------------	-------	---------

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 7647-01-0	Hydrochloric Acid	1.8 ppm
CAS: 10025-77-1	Ferric Chloride Hexahydrate	15 mg/m <sup>3</sup>
CAS: 64-19-7	Acetic Acid	5 ppm
CAS: 7697-37-2	Nitric Acid	0.16 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.20 mg/m <sup>3</sup>

· **PAC-2:**

CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 10025-77-1	Ferric Chloride Hexahydrate	39 mg/m <sup>3</sup>
CAS: 64-19-7	Acetic Acid	35 ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	8.7 mg/m <sup>3</sup>

· **PAC-3:**

CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 10025-77-1	Ferric Chloride Hexahydrate	240 mg/m <sup>3</sup>
CAS: 64-19-7	Acetic Acid	250 ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	160 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 4)

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

<b>CAS: 7647-01-0 Hydrochloric Acid</b>	
NIOSH RECOMENDED EXP LIM	Ceiling limit value: 7.0 mg/m <sup>3</sup> mg/m <sup>3</sup>
PEL	Ceiling limit value: 7 mg/m <sup>3</sup> , 5 ppm
REL	Ceiling limit value: 7 mg/m <sup>3</sup> , 5 ppm
TLV	Ceiling limit value: 2.98 mg/m <sup>3</sup> , 2 ppm
<b>CAS: 64-19-7 Acetic Acid</b>	
PEL	Long-term value: 25 mg/m <sup>3</sup> , 10 ppm
REL	Short-term value: 37 mg/m <sup>3</sup> , 15 ppm Long-term value: 25 mg/m <sup>3</sup> , 10 ppm
TLV	Short-term value: 37 mg/m <sup>3</sup> , 15 ppm Long-term value: 25 mg/m <sup>3</sup> , 10 ppm
<b>CAS: 7697-37-2 Nitric Acid</b>	
PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
REL	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
TLV	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5.2 mg/m <sup>3</sup> , 2 ppm
<b>CAS: 7664-93-9 Sulfuric Acid 96 - 98%</b>	
PEL	Long-term value: 1 mg/m <sup>3</sup>
REL	Long-term value: 1 mg/m <sup>3</sup>
TLV	Long-term value: 0.2* mg/m <sup>3</sup> *as thoracic fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Color:** Clear water white

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 83 °C (181.4 °F)

· **Flash point:** 40 °C (104 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

**Lower:** 4 Vol %

**Upper:** 17 Vol %

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 6)

· <b>Vapor pressure at 21 °C (69.8 °F):</b>	226.6 hPa (170 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.31009 g/cm <sup>3</sup> (10.9327 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	14.3 %
<b>Water:</b>	13.6 %
<b>VOC content:</b>	14.31 %
	187.5 g/l / 1.56 lb/gal
<b>Solids content:</b>	15.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### ATE (Acute Toxicity Estimate)

Oral	LD50	4,772 mg/kg (rat)
Dermal	LD50	7,408 mg/kg (rabbit)

### CAS: 64-19-7 Acetic Acid

Dermal	LD50	1,100 mg/kg (ATE)
--------	------	-------------------

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**  
Strong caustic effect.  
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 8)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 7664-93-9	Sulfuric Acid 96 - 98%	I
----------------	------------------------	---

· **NTP (National Toxicology Program)**

CAS: 7664-93-9	Sulfuric Acid 96 - 98%	K
----------------	------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN1760

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 8)

· **UN proper shipping name**  
· **DOT** *Corrosive liquids, n.o.s. (Hydrochloric acid, Nitric acid, Acetic acid, glacial, Sulfuric acid)*  
· **IMDG, IATA** *CORROSIVE LIQUID, N.O.S. (HYDROCHLORIC ACID, NITRIC ACID, ACETIC ACID, GLACIAL, SULPHURIC ACID)*

· **Transport hazard class(es)**· **DOT**

· **Class** *8 Corrosive substances*  
· **Label** *8, 3*

· **IMDG**

· **Class** *8 Corrosive substances*  
· **Label** *8/3*

· **IATA**

· **Class** *8 Corrosive substances*  
· **Label** *8 (3)*

· **Packing group**  
· **DOT, IMDG, IATA** *II*

· **Environmental hazards:** *Not applicable.*

· **Special precautions for user** *Warning: Corrosive substances*  
· **Hazard identification number (Kemler code):** *83*  
· **EMS Number:** *F-E,S-C*  
· **Segregation groups** *Alkalis*  
· **Stowage Category** *A*  
· **Segregation Code** *SG35 Stow "separated from" SGG1-acids*

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** *On passenger aircraft/rail: 1 L  
On cargo aircraft only: 30 L*

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 9)

· **IMDG**

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

IL

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1760 CORROSIVE LIQUID, N.O.S. (HYDROCHLORIC ACID, NITRIC ACID, ACETIC ACID, GLACIAL, SULPHURIC ACID), 8 (3), II

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

CAS: 7697-37-2	Nitric Acid
CAS: 7664-93-9	Sulfuric Acid 96 - 98%

· **Section 313 (Specific toxic chemical listings):**

CAS: 7697-37-2	Nitric Acid
CAS: 7664-93-9	Sulfuric Acid 96 - 98%

· **TSCA (Toxic Substances Control Act):**

Hydrochloric Acid	ACTIVE
Acetic Acid	ACTIVE
Water	ACTIVE
Nitric Acid	ACTIVE
Sulfuric Acid 96 - 98%	ACTIVE

· **Hazardous Air Pollutants**

CAS: 7647-01-0	Hydrochloric Acid
----------------	-------------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 7664-93-9	Sulfuric Acid 96 - 98%	A2
----------------	------------------------	----

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 10)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS05   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Hydrochloric Acid*

*Sulfuric Acid 96 - 98%*

*Ferric Chloride Hexahydrate*

*Nitric Acid*

*Acetic Acid*

· **Hazard statements**

*Flammable liquid and vapor.*

*Causes severe skin burns and eye damage.*

*May cause cancer.*

*May cause respiratory irritation.*

· **Precautionary statements**

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Do not breathe dusts or mists.*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Rinse mouth. Do NOT induce vomiting.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Immediately call a poison center/doctor.*

*IF exposed or concerned: Get medical advice/attention.*

*Specific treatment (see on this label).*

*Wash contaminated clothing before reuse.*

*In case of fire: Use for extinction: CO2, powder or water spray.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 12)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/20/2020

Reviewed on 04/20/2020

**Trade name: Stainless Steel  
Etchant Solution**

(Contd. of page 11)

- **National regulations:**
- **Information about limitation of use:**  
*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** *Environment protection department.*

- **Contact:**

- **Date of preparation / last revision**

*Revision 0.0, 04-06-2020: Creation date for SDS. STN  
04/20/2020 / -*

- **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flam. Liq. 3: Flammable liquids – Category 3  
Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Carc. 1A: Carcinogenicity – Category 1A  
STOT/SE 3: Specific target organ toxicity (single exposure) – Category 3*

US