

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

1 Identification

- **Product identifier**
- **Trade name:** OH lvl 2
- **Article number:** HON198
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Isopropanol
Acetaldehyde, Reagent ACS Grade
- **Hazard statements**
Highly flammable liquid and vapor.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 1)

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-63-0	Isopropanol	20.0%
CAS: 75-65-0	tert-Butyl Alcohol	1.0%
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	0.1%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 2)

· Table of Nonhazardous Ingredients

CAS: 7732-18-5	Water	77.8%
CAS: 75-85-4	2-methyl-2-butanol	0.5%
CAS: 625-23-0	2-Methyl-2-Hexanol	0.5%
CAS: 79-10-7	Acrylic Acid	0.1%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 67-63-0	Isopropanol	400 ppm
CAS: 75-65-0	tert-Butyl Alcohol	150 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: **OH lvl 2**

(Contd. of page 3)

CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	45 ppm
CAS: 79-10-7	Acrylic Acid	1.5 ppm
· PAC-2:		
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 75-65-0	tert-Butyl Alcohol	1,300 ppm
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	270 ppm
CAS: 79-10-7	Acrylic Acid	46 ppm
· PAC-3:		
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 75-65-0	tert-Butyl Alcohol	8000* ppm
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	840 ppm
CAS: 79-10-7	Acrylic Acid	180 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**
*Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**
*Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.*
- **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see section 7.*
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 67-63-0 Isopropanol	
PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 4)

CAS: 75-65-0 tert-Butyl AlcoholPEL Long-term value: 300 mg/m³, 100 ppmREL Short-term value: 450 mg/m³, 150 ppmLong-term value: 300 mg/m³, 100 ppm

TLV Long-term value: 100 ppm

A4

CAS: 75-07-0 Acetaldehyde, Reagent ACS GradePEL Long-term value: 360 mg/m³, 200 ppm

REL See Pocket Guide Apps. A and C

TLV Ceiling limit value: 25 ppm

A2

· Ingredients with biological limit values:**CAS: 67-63-0 Isopropanol**

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek

LD50: Acetone (background, nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	82 °C (179.6 °F)

· **Flash point:** 13 °C (55.4 °F)· **Flammability (solid, gaseous):** Highly flammable.· **Auto igniting:** 425 °C (797 °F)· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

· Lower:	2 Vol %
· Upper:	12 Vol %

· **Vapor pressure at 20 °C (68 °F):** 43 hPa (32.3 mm Hg)· **Density at 20 °C (68 °F):** 0.95264 g/cm³ (7.94978 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Fully miscible.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**· **Organic solvents:** 20.0 %

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 6)

Water:	77.8 %
VOC content:	20.00 %
	190.5 g/l / 1.59 lb/gal

Solids content:	1.1 %
------------------------	-------

Other information	No further relevant information available.
--------------------------	--

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4h	1,100 mg/l
------------	---------	------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 67-63-0	Isopropanol	3
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	2B
CAS: 79-10-7	Acrylic Acid	3

- **NTP (National Toxicology Program)**

CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	R
--------------	---------------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*
- **Recommended cleansing agent:** *Water, if necessary with cleansing agents.*

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1993
- **UN proper shipping name**
- **DOT** *Flammable liquids, n.o.s. (Isopropanol, tert-Butyl Alcohol)*
- **IMDG, IATA** *FLAMMABLE LIQUID, N.O.S. (Isopropanol, tert-Butyl Alcohol)*
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, IMDG, IATA** II

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 8)

· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Segregation groups	(SGGI) Acids
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL , TERT-BUTYL ALCOHOL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-63-0	Isopropanol
CAS: 75-65-0	tert-Butyl Alcohol
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade
CAS: 79-10-7	Acrylic Acid

· **TSCA (Toxic Substances Control Act):**

Water	ACTIVE
Isopropanol	ACTIVE
tert-Butyl Alcohol	ACTIVE
2-methyl-2-butanol	ACTIVE
Acetaldehyde, Reagent ACS Grade	ACTIVE
Acrylic Acid	ACTIVE

· **Hazardous Air Pollutants**

CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade
CAS: 79-10-7	Acrylic Acid

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 9)

· **Proposition 65**· **Chemicals known to cause cancer:**

CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

CAS: 75-65-0 tert-Butyl Alcohol

SC

CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade

B2

· **TLV (Threshold Limit Value)**

CAS: 67-63-0 Isopropanol

A4

CAS: 75-65-0 tert-Butyl Alcohol

A4

CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade

A3

CAS: 79-10-7 Acrylic Acid

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02

GHS07

GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

Isopropanol

Acetaldehyde, Reagent ACS Grade

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: OH lvl 2

(Contd. of page 10)

Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Environment protection department.

• **Contact:**

Date of Preparation / Last Revision:

• **Date of preparation / last revision**

Revision 1.2, 07-25-2024: Reviewed SDS for accuracy. STN/GW
07/25/2024 / -

• **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**