

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

1 Identification

- **Product identifier**
- **Trade name:** Color Standard 500 PCU
for EZ1008 Colour Analyzer
- **Article number:** HAC633
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemirec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Sensitization - Respiratory 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corrosion 1A

H314 Causes severe skin burns and eye damage.

Eye Damage 1

H318 Causes serious eye damage.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS08

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Hydrochloric Acid

Potassium Platinum Chloride

· **Hazard statements**

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



*Health = *3*

Fire = 0

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** *Mixture of the substances listed below with nonhazardous additions.*

· **Dangerous components:**

CAS: 7647-01-0	Hydrochloric Acid	11.315%
----------------	-------------------	---------

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 2)

CAS: 16921-30-5	Potassium Platinum Chloride	0.123%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-5	Water	88.464%
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	0.098%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 7647-01-0	Hydrochloric Acid	1.8 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	0.24 mg/m ³
· PAC-2:		
CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	25 mg/m ³
· PAC-3:		
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	150 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
CAS: 7647-01-0 Hydrochloric Acid	
NIOSH RECOMENDED EXP LIM	Ceiling limit value: 7.0 mg/m ³ mg/m ³
PEL	Ceiling limit value: 7 mg/m ³ , 5 ppm
REL	Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV	Ceiling limit value: 2 ppm A4
CAS: 16921-30-5 Potassium Platinum Chloride	
PEL	Long-term value: 0.002 mg/m ³ as Pt
REL	Long-term value: 0.002 mg/m ³ as Pt
TLV	Long-term value: 0.002 mg/m ³ as Pt

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 4)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Yellow-brown

- **Odor:** Odorless

- **Odor threshold:** Not determined.

- **pH-value at 20 °C (68 °F):** <2

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C (212 °F)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 5)

· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.01637 g/cm ³ (8.48161 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	88.5 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US
(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	81,566 mg/kg
------	------	--------------

- **Primary irritant effect:**

- **on the skin:** Strong caustic effect on skin and mucous membranes.

- **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 7791-13-1	Cobalt Chloride Hexahydrate	2B
----------------	-----------------------------	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**



(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	UN3264
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric Acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric Acid)
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  <p>CORROSIVE 8</p> </div>
<ul style="list-style-type: none"> · Class · Label 	8 Corrosive substances 8
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  <p>CORROSIVE 8</p> </div>
<ul style="list-style-type: none"> · Class · Label 	8 Corrosive substances 8
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	II
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category · Stowage Code 	Warning: Corrosive substances 80 F-A,S-B (SGG1) Acids B SW2 Clear of living quarters.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 8)

· Segregation Code	SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID), 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 7791-13-1 | Cobalt Chloride Hexahydrate

· **TSCA (Toxic Substances Control Act):**

Water

ACTIVE

Hydrochloric Acid

ACTIVE

Potassium Platinum Chloride

ACTIVE

· **Hazardous Air Pollutants**

CAS: 7647-01-0 | Hydrochloric Acid

CAS: 7791-13-1 | Cobalt Chloride Hexahydrate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 9)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Hydrochloric Acid

Potassium Platinum Chloride

· **Hazard statements**

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2024

Reviewed on 07/23/2024

**Trade name: Color Standard 500 PCU
for EZ1008 Colour Analyzer**

(Contd. of page 10)

- **Contact:**

- Date of Preparation / Last Revision:*

- **Date of preparation / last revision**

- Revision 1.2, 07-23-2024: Reviewed SDS for accuracy. STN/GW
07/23/2024 / 1.1*

- **Abbreviations and acronyms:**

- IMDG: International Maritime Code for Dangerous Goods*

- DOT: US Department of Transportation*

- IATA: International Air Transport Association*

- EINECS: European Inventory of Existing Commercial Chemical Substances*

- ELINCS: European List of Notified Chemical Substances*

- CAS: Chemical Abstracts Service (division of the American Chemical Society)*

- NFPA: National Fire Protection Association (USA)*

- HMIS: Hazardous Materials Identification System (USA)*

- VOC: Volatile Organic Compounds (USA, EU)*

- LC50: Lethal concentration, 50 percent*

- LD50: Lethal dose, 50 percent*

- PBT: Persistent, Bioaccumulative and Toxic*

- vPvB: very Persistent and very Bioaccumulative*

- NIOSH: National Institute for Occupational Safety*

- OSHA: Occupational Safety & Health*

- TLV: Threshold Limit Value*

- PEL: Permissible Exposure Limit*

- REL: Recommended Exposure Limit*

- Skin Corrosion 1A: Skin corrosion/irritation – Category 1A*

- Eye Damage 1: Serious eye damage/eye irritation – Category 1*

- Sensitization - Respiratory 1: Respiratory sensitisation – Category 1*

- Sensitization - Skin 1: Skin sensitisation – Category 1*

- Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2*

- *** Data compared to the previous version altered.**