Printing date 05/23/2024

Reviewed on 05/23/2024

# **1** Identification

- · Product identifier
- · Trade name: Ferrous Sulfate Solution
- · Article number: ND332
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225
- DEER PARK, TX 77536 USA 800-256-2586
- Information department: Technical Coordinator
   Sherman Nelson shermann@aquasolutions.org
   Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

# 2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.

GHS06 Skull and crossbones

Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled.

GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer. Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and the visual organs.

#### · Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• Hazard-determining components of labeling: Methanol

(Contd. on page 2)

<sup>-</sup> US

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

Sulfuria Acid 06 080	(Contd. of page 1)
Sulfuric Acid 96 - 98% Hazard statements	
Highly flammable liquid and vapor.	
Toxic if swallowed, in contact with skin or if inhaled.	
May cause cancer.	
Causes damage to the central nervous system and the visual organs.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Rinse mouth.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/show	er.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
<i>IF exposed or concerned: Get medical advice/attention.</i>	
Call a poison center/doctor if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulati	ons.
Classification system:	
NFPÅ ratings (scale 0 - 4)	
Health = 2	
Fire = $3$	
2 <i>Q Reactivity</i> = 0	
HMIS-ratings (scale 0 - 4)	
<b>HEALTH</b> 2 $Health = 2$	
FIRE 3 Fire = 3	
$\frac{1}{\text{REACTIVITY}} \begin{bmatrix} 0 \\ 0 \end{bmatrix} Reactivity = 0$	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
<b>vPvB:</b> Not applicable.	

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

		(Contd. of page 2)
· Dangerous comp	onents:	
CAS: 67-56-1	Methanol	48.0%
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.5%
	ardous Ingredients	
CAS: 7732-18-5		50.3%
	Ferrous Sulfate Heptahydrate	0.9%
CAS: 7439-89-6	Iron Metal	0.3%

### 4 First-aid measures

### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
- Supply fresh air or oxygen; call for doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5** *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
• Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
*	(Contd. on page 4)

Printing date 05/23/2024

Reviewed on 05/23/2024

### Trade name: Ferrous Sulfate Solution

		(Contd. of page 3
See Section 8 for See Section 13 fo	<b>er sections</b> information on safe handling. information on personal protection equipment. r disposal information. <b>a Criteria for Chemicals</b>	
• PAC-1:		
CAS: 67-56-1	Methanol	530 ppm
CAS: 7782-63-0	Ferrous Sulfate Heptahydrate	15 mg/m <sup>3</sup>
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.20 mg/m <sup>3</sup>
CAS: 7439-89-6	Iron Metal	3.2 mg/m <sup>3</sup>
PAC-2:		<u>.</u>
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 7782-63-0	Ferrous Sulfate Heptahydrate	170 mg/m <sup>3</sup>
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	8.7 mg/m <sup>3</sup>
CAS: 7439-89-6	Iron Metal	35 mg/m <sup>3</sup>
PAC-3:		
CAS: 67-56-1	Methanol	7200* ppm
CAS: 7782-63-0	Ferrous Sulfate Heptahydrate	990 mg/m <sup>3</sup>
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	160 mg/m <sup>3</sup>
CAS: 7439-89-6	Iron Metal	150 mg/m <sup>3</sup>

# 7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- *Specific end use(s) No further relevant information available.*

# 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

US

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

	(Contd. of page 4)
· Con	ntrol parameters
· Con	nponents with limit values that require monitoring at the workplace:
	S: 67-56-1 Methanol
PEI	L Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REI	L Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	<ul> <li>Nort-term value: 250 ppm</li> <li>Long-term value: 200 ppm</li> <li>Skin; BEI</li> </ul>
CA	S: 7664-93-9 Sulfuric Acid 96 - 98%
PEI	L Long-term value: 1 mg/m <sup>3</sup>
REI	L Long-term value: 1 mg/m <sup>3</sup>
TLV	<ul> <li><i>V</i> Long-term value: 0.2* mg/m<sup>3</sup></li> <li>*as thoracic fraction, A2</li> </ul>
·Ing	redients with biological limit values:
CA	S: 67-56-1 Methanol
BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)
· Ada	litional information: The lists that were valid during the creation were used as basis.
• Per • Gen Kee Imm Was Stor Avo • Bre In c resp	posure controls sonal protective equipment: meral protective and hygienic measures: up away from foodstuffs, beverages and feed. mediately remove all soiled and contaminated clothing. sh hands before breaks and at the end of work. re protective clothing separately. wid contact with the eyes and skin. athing equipment: wase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use poiratory protective device that is independent of circulating air. tection of hands:
W	Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

(Contd. of page 5)

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

• Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form: Color:	Liquid Light green
Odor:	de l'alcool
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.939 g/cm³ (7.83596 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity: Dynamic:	Not determined.

Printing date 05/23/2024

Reviewed on 05/23/2024

### Trade name: Ferrous Sulfate Solution

		(Contd. of page 6
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	48.0 %	
Water:	50.3 %	
VOC content:	48.00~%	
	450.7 g/l / 3.76 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

### 10 Stability and reactivity

• *Reactivity* No further relevant information available.

#### · Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

### · Information on toxicological effects

· Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)		
Oral		208 mg/kg
Dermal	LD50	625 mg/kg
Inhalative	LC50/4h	6.25 mg/l

#### · Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· NTP (National Toxicology Program)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 8)

1

K

US

Printing date 05/23/2024

Reviewed on 05/23/2024

### Trade name: Ferrous Sulfate Solution

(Contd. of page 7)

# **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, IMDG, IATA	UN1993
	011775
UN proper shipping name DOT	Flammable liquids, n.o.s. (Methanol)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Methanol)
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

	(Contd. of pag
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	33
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	В
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANOL), 3, II

# 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

CAS: 7664-93-9 Sulfuric Acid 96 - 98%	
Section 313 (Specific toxic chemical listings):	
CAS: 67-56-1 Methanol	
CAS: 7664-93-9 Sulfuric Acid 96 - 98%	
TSCA (Toxic Substances Control Act):	
Water	ACTIV
Methanol	ACTIV
Sulfuric Acid 96 - 98%	ACTIV
Iron Metal	ACTIV
Hazardous Air Pollutants	· .
CAS: 67-56-1 Methanol	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

(Contd. of page 9)

A2

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ferrous Sulfate Solution

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Methanol Sulfuric Acid 96 - 98% · Hazard statements Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. May cause cancer. Causes damage to the central nervous system and the visual organs. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 11)

<sup>–</sup> US

Printing date 05/23/2024

Reviewed on 05/23/2024

#### Trade name: Ferrous Sulfate Solution

(Contd. of page 10)

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

• Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. *Exceptions can be made by the authorities in certain cases.* 

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision:

Date of preparation / last revision Revision 1.2, 05/23/2024: Reviewed SDS for accuracy. MH/STN 05/23/2024
Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 3: Acute toxicity – Category 3 Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

 $\cdot$  \* Data compared to the previous version altered.