Printing date 05/31/2024 Reviewed on 05/31/2024

1 Identification

· Product identifier

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

· Article number: SPX191

· Restrictions

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 3 H311 Toxic in contact with skin.



GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer.

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and the visual organs.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



(Contd. on page 2)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 1)

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms











GHS05

GHS06

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Acetic Acid, Glacial

Methanol

Dichloromethane (Methylene Chloride)

Sulfuric Acid 96 - 98%

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 2)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3Fire = 2REACTIVITY $\boxed{1}$ Reactivity = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

	*	v	
· Dangerous components:			
	CAS: 64-19-7	Acetic Acid, Glacial	71.944%
	CAS: 75-09-2	Dichloromethane (Methylene Chloride)	17.045%
	CAS: 67-56-1	Methanol	10.185%
	CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.826%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

5 ppm		
200 ppm		
530 ppm		
0.20 mg/m³		
35 ppm		
560 ppm		
2,100 ppm		
8.7 mg/m³		
· PAC-3:		
250 ppm		
6,900 ppm		
7200* ppm		

US

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

 CAS: 7664-93-9
 Sulfuric Acid 96 - 98%
 (Contd. of page 4)

 160 mg/m³
 160 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Long-term value: 260 mg/m³, 200 ppm

Skin

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters		
· Components with limit values that require monitoring at the workplace:		
CAS: 64-19-7 Acetic Acid, Glacial		
PEL Long-term value: 25 mg/m³, 10 ppm		
REL Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm		
TLV Short-term value: 15 ppm Long-term value: 10 ppm		
CAS: 75-09-2 Dichloromethane (Methylene Chloride)		
PEL Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052		
REL See Pocket Guide App. A		
TLV Long-term value: 50 ppm BEI, A3		
CAS: 67-56-1 Methanol		
PEL Long-term value: 260 mg/m³, 200 ppm		
REL Short-term value: 325 mg/m³, 250 ppm		

(Contd. on page 6)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 5)

TLV Short-term value: 250 ppm Long-term value: 200 ppm

Skin; BEI

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

PEL Long-term value: 1 mg/m³
REL Long-term value: 1 mg/m³
TLV Long-term value: 0.2* mg/m³
*as thoracic fraction, A2

· Ingredients with biological limit values:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

BEI 0.3 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Dichloromethane (semi-quantitative)

CAS: 67-56-1 Methanol

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

· Information on basic physical and chemical properties · General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Vinegar
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	118 °C (244.4 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
Density at 20 °C (68 °F):	1.06597 g/cm³ (8.89552 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 8)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

	(Contd. of page 7)
· Solvent content: Organic solvents: VOC content:	99.2 % 82.13 % 875.5 g/l / 7.31 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:
ATE (Acute Toxicity Estimate)

,		,
Oral	LD50	982 mg/kg
Dermal	LD50	982 mg/kg
Inhalative	LC50/4h	29.5 mg/l

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Internati	onal Agency for Research on Cancer)	
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	2A
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	1

(Contd. on page 9)

Reviewed on 05/31/2024 Printing date 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

		(Contd. of page 8
· NTP (National Toxicology Program)		
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	R
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	K
· OSHA-Ca (Occupational Safety & Health Administration)		
CAS: 75-09-2 Dichloromethane (Methylene Chloride)		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, IMDG, IATA	UN3286
UN proper shipping name	
DOT	Flammable liquid, toxic, corrosive, n.o.s. (Methanol
	Dichloromethane, Acetic Acid, Glacial
· IMDG, IATA	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (Methanol
	Dichloromethane, Acetic Acid, Glacial

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 9) · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids · Label 3, 6.1, 8 · IMDG · Class 3 Flammable liquids · Label 3/6.1/8 \cdot IATA · Class 3 Flammable liquids · Label 3 (6.1, 8) · Packing group · DOT, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 3 · EMS Number: *F-E,S-C* · Stowage Category · Stowage Code SW2 Clear of living quarters. · Segregation Code SG5 Segregation as for class 3 SG8 Stow "away from" class 4.1 · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: \cdot IMDG · Limited quantities (LQ) 1LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Contd. on page 11)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 10)

· UN "Model Regulation":

UN 3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHANOL, DICHLOROMETHANE, ACETIC ACID, GLACIAL), 3 (6.1+8), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

	· Section 355 (extremely hazardous substances):	
CAS: 7664-93-9 Sulfuric Acid 96 - 98%		Sulfuric Acid 96 - 98%
· Section 313 (Specific toxic chemical listings):		ecific toxic chemical listings):
	CAS: 75-09-2	Dichloromethane (Methylene Chloride)
	CAS: 67-56-1	Methanol
Ī	CAS: 7664-93-9	Sulfuric Acid 96 - 98%

· TSCA (Toxic Substances Control Act):

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Acetic Acid, Glacial	ACTIVE
Dichloromethane (Methylene Chloride)	ACTIVE
Methanol	ACTIVE
Sulfuric Acid 96 - 98%	ACTIVE

· Hazardous Air Pollutants

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 67-56-1 Methanol

- · Proposition 65
- · Chemicals known to cause cancer:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)	
CAS: 75-09-2 Dichloromethane (Methylene Chloride)	L

· TLV (Threshold Limit Value)

CAS: 75-09-2	Dichloromethane (Methylene Chloride)	<i>A3</i>
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 11)

· Hazard pictograms











GHS02

GHS05

GHS06

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Acetic Acid, Glacial

Methanol

Dichloromethane (Methylene Chloride)

Sulfuric Acid 96 - 98%

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

 $Use\ explosion-proof\ electrical/ventilating/lighting/equipment.$

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 13)

Printing date 05/31/2024 Reviewed on 05/31/2024

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 12)

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 05/30/2024: Reviewed SDS for accuracy. MH/STN 05/31/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 3: Acute toxicity - Category 3

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1 Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1

* Data compared to the previous version altered.