Printing date 07/24/2024

Reviewed on 07/24/2024

1 Identification · Product identifier · Trade name: 50.0 mg/L 14 Component **Mixed Metal Working Solution** · Article number: SAY006 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 2 Hazard(s) identification · Classification of the substance or mixture GHS08 Health hazard Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS05 Corrosion Eye Damage 1 H318 Causes serious eye damage. GHS07 Skin Irritation 2 H315 Causes skin irritation. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS05 GHS08 · Signal word Danger · Hazard-determining components of labeling: Hydrochloric Acid · Hazard statements Causes skin irritation.

(Contd. on page 2)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

(Contd. of page 1)	_
Causes serious eye damage.	
May cause damage to organs through prolonged or repeated exposure.	
· Precautionary statements	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Wear protective gloves / eye protection / face protection.	
If on skin: Wash with plenty of water.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.	
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 0	
$\frac{3}{Reactivity} = 0$	
Keuchvily = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH *3 $Health = *3$	
FIRE 0 $Fire = 0$	
REACTIVITY 0 Reactivity = 0	
REACTIVITY Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• <i>PBT:</i> Not applicable.	
· vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical	characterization:	Mixtures
------------	-------------------	-----------------

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
CAS: 7647-01-0 Hydrochloric Acid	3.28%
CAS: 7697-37-2 Nitric Acid	0.514%
· Table of Nonhazardous Ingredients	
CAS: 7732-18-5 Water	95.435%
CAS: 12007-60-2 Lithium Tetraborate, Reagent	0.36%
CAS: 87-69-4 L-Tartaric Acid	0.347%
CAS: 7789-24-4 Lithium Fluoride	0.04%
CAS: 19004-19-4 Cupric Nitrate Hydrate	0.018%
CAS: 7440-38-2 arsenic	0.005%

(Contd. on page 3)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

(Contd. of page 2)

1.8 ppm 0.16 ppm 4.3 mg/m³ 1.6 mg/m³

10 mg/m³ (Contd. on page 4)

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters

CAS: 7789-24-4

· Protective equipment: Mouth respiratory protective device.

Lithium Fluoride

6 Accidental release measures

D 1	
• Personal precauti Mount respiratory	ons, protective equipment and emergency procedures
	quipment. Keep unprotected persons away.
 Environmental pr 	
Dilute with plenty	of water.
Do not allow to en	ter sewers/ surface or ground water.
	erial for containment and cleaning up:
	l-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing a	
Ū	
1	ated material as waste according to section 13.
Ensure adequate v	
· Reference to other	r sections
See Section 7 for i	nformation on safe handling.
See Section 8 for i	nformation on personal protection equipment.
See Section 13 for	disposal information.
· Protective Action	Criteria for Chemicals
· PAC-1:	
CAS: 7647-01-0	Hydrochloric Acid
CAS: 7697-37-2	Nitric Acid
CAS: 12007-60-2	Lithium Tetraborate, Reagent
CAS: 87-69-4	L-Tartaric Acid

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

		(Contd. of page 3)
CAS: 19004-19-4	Cupric Nitrate Hydrate	42 mg/m ³
CAS: 7440-38-2	arsenic	1.5 mg/m ³
· PAC-2:		
CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 12007-60-2	Lithium Tetraborate, Reagent	47 mg/m ³
CAS: 87-69-4	L-Tartaric Acid	17 mg/m ³
CAS: 7789-24-4	Lithium Fluoride	110 mg/m ³
CAS: 19004-19-4	Cupric Nitrate Hydrate	150 mg/m ³
CAS: 7440-38-2	arsenic	17 mg/m ³
· PAC-3:		
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 12007-60-2	Lithium Tetraborate, Reagent	280 mg/m ³
CAS: 87-69-4	L-Tartaric Acid	100 mg/m ³
CAS: 7789-24-4	Lithium Fluoride	680 mg/m ³
CAS: 19004-19-4	Cupric Nitrate Hydrate	240 mg/m ³
CAS: 7440-38-2	arsenic	100 mg/m ³

7 Handling and storage

- · Handling:
- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with	limit values that r	eauire monitoring	at the workplace:

CAS: 7647-01-0 Hydrochloric Acid	
NIOSH RECOMENDED EXP LIMI	Ceiling limit value: 7.0 mg/m3 mg/m ³
PEL	Ceiling limit value: 7 mg/m³, 5 ppm
REL	Ceiling limit value: 7 mg/m³, 5 ppm
	(Contd. on page 5)

US

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

		(Contd. of page 4)
TLV	Ceiling limit value: 2 ppm	
	A4	
CAS: 7697-37-2 Nit	ric Acid	
PEL	Long-term value: 5 mg/m ³ , 2 ppm	
REL	Short-term value: 10 mg/m ³ , 4 ppm	
	Long-term value: 5 mg/m ³ , 2 ppm	
TLV	Short-term value: (4) NIC-0.025 ppm	
	Long-term value: (2) ppm	
	NIC-A4	

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 6)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

(Contd. of page 5)

Information on busic abusical and a		
Information on basic physical and cl General Information	iemicai properties	
Appearance:		
Form:	Liquid	
Color:	Colorless	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	$100 ^{\circ}C (212 ^{\circ}F)$	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.00791 g/cm ³ (8.41101 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water		
Viscosity:	<u>·</u>	
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:	95.4 %	
Water:	93.4 % 0.00 %	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content:	0.8~%	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7) US

Printing date 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution Reviewed on 07/24/2024

(Contd. of page 6)

· Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

• Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 583 mg/l

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)CAS: 7789-24-4Lithium Fluoride3CAS: 7440-38-2arsenic1· NTP (National Toxicology Program)1CAS: 7440-38-2arsenicK· OSHA-Ca (Occupational Safety & Health Administration)KCAS: 7440-38-2arsenic

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN3264
· UN proper shipping name · DOT · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Aci
· Transport hazard class(es)	
·DOT	
CORROSIVE 8	
· Class	8 Corrosive substances
· Label	8
- Class	8 Corrosive substances
· Label	8
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 9)

⁻ US

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

Sara		(Contd. of page
	emely hazardous substances):	
CAS: 7697-37-2	•	
Section 313 (Spe	cific toxic chemical listings):	
CAS: 7697-37-2		
CAS: 7440-38-2	arsenic	
TSCA (Toxic Su	bstances Control Act):	
Water	······································	ACTIV
Hydrochloric Ac	id	ACTIV
Nitric Acid		ACTIV
Lithium Tetrabor	ate, Reagent	ACTIV
L-Tartaric Acid		ACTIV
Lithium Fluoride		ACTIV
arsenic		ACTIV
Hazardous Air H	ollutants	I
	Hydrochloric Acid	
Proposition 65	-	
Chemicals know	n to cause cancer:	
CAS: 7440-38-2	arsenic	
Chemicals know	n to cause reproductive toxicity for females:	
None of the ingr		
Chemicals know	n to cause reproductive toxicity for males:	
None of the ingre		
	n to cause developmental toxicity:	
None of the ingr		
Carcinogenic ca	-	
	ental Protection Agency)	
	Lithium Tetraborate, Reagent	I (oral
CAS: 7440-38-2		A
TLV (Threshold		
	Lithium Fluoride	A
	arsenic	A
CAS: 7440-38-2		
	ional Institute for Occupational Safety and Health)	

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

(Contd. on page 10)

US -

Printing date 07/24/2024

Reviewed on 07/24/2024

Trade name: 50.0 mg/L 14 Component Mixed Metal Working Solution

(Contd. of page 9)

Hazard-determining co	mponents of labeling:
Hydrochloric Acid	
Hazard statements	
Causes skin irritation.	
Causes serious eye dam	age.
May cause damage to o	rgans through prolonged or repeated exposure.
Precautionary statemen	uts
Do not breathe dust/fun	ne/gas/mist/vapors/spray.
Wash thoroughly after h	nandling.
Wear protective gloves	/ eye protection / face protection.
If on skin: Wash with pl	enty of water.
If in eyes: Rinse caution	busly with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.	
Immediately call a poise	on center/doctor.
Specific treatment (see a	on this label).
Get medical advice/atte	ntion if you feel unwell.
Take off contaminated of	lothing and wash it before reuse.
If skin irritation occurs:	Get medical advice/attention.
Dispose of contents/con	tainer in accordance with local/regional/national/international regulations.
÷ •	nent: A Chemical Safety Assessment has not been carried out.
	v ·

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2 07/24/2024: Reviewed SDS for accuracy. MH/STN 07/24/2024 / 1.1 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 \cdot * Data compared to the previous version altered.