

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

1 Identification

- **Product identifier**
- **Trade name:** TBAOH 0.1 Normal
in Xylene/Butanol 3:1
- **Article number:** DC998
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371 May cause damage to the central nervous system and the visual organs.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

Xylene (Xylol)
n-Butyl Alcohol
Methanol
Tetrabutylammonium Hydroxide 30-Hydrate

· **Hazard statements**

Highly flammable liquid and vapor.
Harmful if swallowed, in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye damage.
May cause damage to the central nervous system and the visual organs.
May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Call a poison center/doctor.
Specific treatment (see on this label).
Rinse mouth.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 3
Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = *3
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7	Xylene (Xylol)	67.5%
CAS: 71-36-3	n-Butyl Alcohol	22.5%
CAS: 67-56-1	Methanol	6.924%
CAS: 2052-49-5	Tetrabutylammonium Hydroxide 30-Hydrate	3.076%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

CAS: 1330-20-7	Xylene (Xylol)	130 ppm
CAS: 71-36-3	n-Butyl Alcohol	60 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 2052-49-5	Tetrabutylammonium Hydroxide 30-Hydrate	1.2 mg/m ³

- **PAC-2:**

CAS: 1330-20-7	Xylene (Xylol)	920* ppm
CAS: 71-36-3	n-Butyl Alcohol	800 ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 2052-49-5	Tetrabutylammonium Hydroxide 30-Hydrate	13 mg/m ³

- **PAC-3:**

CAS: 1330-20-7	Xylene (Xylol)	2500* ppm
CAS: 71-36-3	n-Butyl Alcohol	8000** ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 2052-49-5	Tetrabutylammonium Hydroxide 30-Hydrate	79 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

CAS: 1330-20-7 Xylene (Xylol)

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

CAS: 71-36-3 n-Butyl Alcohol

PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Ceiling limit value: 150 mg/m ³ , 50 ppm Skin
TLV	Long-term value: 20 ppm

CAS: 67-56-1 Methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

- **Ingredients with biological limit values:**

CAS: 1330-20-7 Xylene (Xylol)

BEI	1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids
-----	---

CAS: 67-56-1 Methanol

BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)
-----	--

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 5)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 64 °C (147.2 °F)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 6)

· Flash point:	11 °C (51.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	340 °C (644 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	9.4 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	0.85385 g/cm ³ (7.12538 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	96.9 %
VOC content:	96.92 %
	827.6 g/l / 6.91 lb/gal
Solids content:	3.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 7)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	875 mg/kg
Dermal	LD50	1,184 mg/kg
Inhalative	LC50/4h	11.8 mg/l

CAS: 1330-20-7 Xylene (Xylol)

Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4h	11 mg/l (ATE)

CAS: 71-36-3 n-Butyl Alcohol

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

CAS: 67-56-1 Methanol

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4h	3 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 1330-20-7 Xylene (Xylol)	3
-------------------------------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 8)



Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	UN1993
· DOT, IMDG, IATA	
· UN proper shipping name	Flammable liquids, n.o.s. (Xylene (Xylol), Methanol, n-Butyl Alcohol)
· DOT	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Xylene (Xylol), Methanol, n-Butyl Alcohol)
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 9)

· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENE (XYLOL), METHANOL, N-BUTYL ALCOHOL), 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 1330-20-7 Xylene (Xylol)

CAS: 71-36-3 n-Butyl Alcohol

CAS: 67-56-1 Methanol

· **TSCA (Toxic Substances Control Act):**

Xylene (Xylol)

ACTIVE

n-Butyl Alcohol

ACTIVE

Methanol

ACTIVE

Tetrabutylammonium Hydroxide 30-Hydrate

ACTIVE

· **Hazardous Air Pollutants**

CAS: 1330-20-7 Xylene (Xylol)

CAS: 67-56-1 Methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 10)

· **Chemicals known to cause developmental toxicity:**

CAS: 67-56-1	Methanol
--------------	----------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 1330-20-7	Xylene (Xylol)	I
----------------	----------------	---

CAS: 71-36-3	n-Butyl Alcohol	D
--------------	-----------------	---

· **TLV (Threshold Limit Value)**

CAS: 1330-20-7	Xylene (Xylol)	A4
----------------	----------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Xylene (Xylol)

n-Butyl Alcohol

Methanol

Tetrabutylammonium Hydroxide 30-Hydrate

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause damage to the central nervous system and the visual organs.

May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2021

Reviewed on 12/13/2021

**Trade name: TBAOH 0.1 Normal
in Xylene/Butanol 3:1**

(Contd. of page 11)

*IF exposed or concerned: Call a poison center/doctor.
Specific treatment (see on this label).
Rinse mouth.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

Revision 1.0, 11-16-2021: Updated product information. STN

Revision 0.1, 02-20-18: revised ingredient list, ALIZARIN RED S BIOLOGICAL STAIN was not listed. STN 12/13/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2