Printing date 06/06/2024

*

*

Reviewed on 06/06/2024

Identification	
Product identifier	
Trade name: BHT Standard	
20.0 ppm w/w in n-Pentane	
Article number: SAY024	
Details of the supplier of the safety data sh	heet
Manufacturer/Supplier:	AQUA
Aqua Solutions, Inc. 6913 Highway 225	SOLUTIONS
<i>DEER PARK, TX 77536</i>	UVED HONO
USA	
800-256-2586	
Information department:	
Technical Coordinator	
Sherman Nelson shermann@aquasolutions Emergency telephone number:	s.org
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02 Flame	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
GHS08 Health hazard	
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
$\mathbf{\wedge}$	
GHS07	
\mathbf{V}	
\mathbf{V}	posure 3 H336 May cause drowsiness or dizziness.
$\mathbf{\mathbf{v}}$	posure 3 H336 May cause drowsiness or dizziness. H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi	•••••••••••••••••••••••••••••••••••••••
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi Hazard pictograms	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi Hazard pictograms	H320 Causes eye irritation.
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi Hazard pictograms GHS02 GHS07 GHS08	H320 Causes eye irritation. Tied and labeled according to the Globally Harmonized System (GHS
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi Hazard pictograms GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeli Pentane	H320 Causes eye irritation. Tied and labeled according to the Globally Harmonized System (GHS
Specific Target Organ Toxicity - Single Exp Eye Irritation 2B Label elements GHS label elements The product is classifi Hazard pictograms GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeli	H320 Causes eye irritation. Tied and labeled according to the Globally Harmonized System (GHS

Printing date 06/06/2024

*

Reviewed on 06/06/2024

Trade name: BHT Standard 20.0 ppm w/w in n-Pentane

(Contd. of page 1)
Causes eye irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Precautionary statements Kommunication for a firm of the second statements
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling. Do not touch eyes.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical help.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification system:
· NFPA ratings (scale 0 - 4)
Health = 1
$\frac{4}{Fire} = 4$
$\frac{1}{10} \frac{1}{Reactivity} = 0$
· HMIS-ratings (scale 0 - 4)
HEALTH 1 Health -1
HEALTH1Health = 1FIRE4Fire = 4
REACTIVITY O Reactivity = 0
· Other hazards
· Results of PBT and vPvB assessment
• PBT: Not applicable.
· vPvB: Not applicable.
3 Composition/information on ingredients
· Chemical characterization: Mixtures
• Description: Mixture of the substances listed below with nonhazardous additions.
· Dangerous components:
CAS: 109-66-0 Pentane 99.998%

99.998% (Contd. on page 3)

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

(Contd. of page 2)

0.002%

· Table of Nonhazardous Ingredients

CAS: 128-37-0 Butylated hydroxytoluene

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available. • Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Do not allow product to reach sewage system or any water course.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
· Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 109-66-0 Pentane	3000* ppm
· PAC-2:	
CAS: 109-66-0 Pentane 3	3000*** ppm
	(Contd. on page 4)

US

Printing date 06/06/2024

Reviewed on 06/06/2024

(Contd. of page 3)

200000*** ppm

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

· PAC-3:

CAS: 109-66-0 Pentane

7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- *Specific end use(s)* No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 109-66-0 Pentane

- PEL Long-term value: 2950 mg/m³, 1000 ppm
- REL Long-term value: 350 mg/m³, 120 ppm Ceiling limit value: 1800* mg/m³, 610* ppm *15-min
- TLV Long-term value: 1000 ppm
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

US

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard 20.0 ppm w/w in n-Pentane

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Physical and chemical proper	rties
· Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Colorless
· Odor:	Aromatic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-129.7 °C (-201.5 °F)
Boiling point/Boiling range:	36.1 °C (97 °F)
· Flash point:	-35 °C (-31 °F)
· Flammability (solid, gaseous):	Highly flammable.
• Auto igniting:	285 °C (545 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	
Lower:	1.4 Vol %

(Contd. on page 6)

US

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

	(Contd. of p	bage 5
Upper:	7.8 Vol %	
· Vapor pressure at 20 °C (68 °F):	573 hPa (429.8 mm Hg)	
· Density at 20 °C (68 °F):	0.62666 g/cm ³ (5.22948 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.01 g/l	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	626.6 g/l / 5.23 lb/gal	
Solids content:	0.1 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- CAS: 128-37-0 Butylated hydroxytoluene

(Contd. on page 7)

3

US –

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1265	
UN proper shipping name		
DOT	Pentanes	
IMDG	PENTANES, MARINE POLLUTANT	
IATA	PENTANES	
Transport hazard class(es)		
DOT		
RAMABLE LODO		
PLAMARIE LOUD		
Class	3 Flammable liquids	

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

7 7 7	(Contd. of pa
Label	3
IMDG	
· Class	3 Flammable liquids
· Label	3
	2 Elammahla liquida
Class Label	3 Flammable liquids 3
	5
Packing group	,
DOT, IMDG, IATA	Ι
Environmental hazards:	Product contains environmentally hazardous substances: Penta
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code	
EMS Number:	F-E,S-D
Stowage Category	В
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
· IMDG	
LIMDG Limited quantities (LQ)	51.
Excepted quantities (EQ)	Code: E2
Lacepten quantities (DQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1265 PENTANES, 3, 1

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

*

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US -

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard

20.0 ppm w/w in n-Pentane

	(Contd. of page
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	
Pentane	ACTIV
Butylated hydroxytoluene	ACTIV
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 128-37-0 Butylated hydroxytoluene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Pentane
Hazard statements
Highly flammable liquid and vapor. Causes eye irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 10)

A4

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: BHT Standard 20.0 ppm w/w in n-Pentane

Do NOT induce vomiting.

(Contd. of page 9) Wash thoroughly after handling. Do not touch eyes. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Call a poison center/doctor if you feel unwell.

Use only outdoors or in a well-ventilated area.

If eye irritation persists: Get medical help.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department. · Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN 06/06/2024 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids - Category 2 Eye Irritation 2B: Serious eye damage/eye irritation - Category 2B Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Aspiration Hazard 1: Aspiration hazard – Category 1 \cdot * Data compared to the previous version altered.