Printing date 07/03/2024

*

Reviewed on 07/03/2024

Trade name: <u>Chloride Standard 1.0 mg/kg</u> in P-xylene (ASTM D 7536-0	<u>9)</u>
Article number: CG034	
Details of the supplier of the safety data sho Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	eet
Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions. Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	org
Hazard(s) identification	
GHS02 Flame Flammable Liquids 3	H226 Flammable liquid and vapor.
•	
GHS08 Health hazard	
	Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.
Specific Target Organ Toxicity - Repeated E	repeated exposure.
Specific Target Organ Toxicity - Repeated E Aspiration Hazard 1	repeated exposure.
Specific Target Organ Toxicity - Repeated E Aspiration Hazard 1 GHS07	repeated exposure. H304 May be fatal if swallowed and enters airways.
Specific Target Organ Toxicity - Repeated E Aspiration Hazard 1 GHS07 Acute Toxicity - Dermal 4	repeated exposure. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin.
Specific Target Organ Toxicity - Repeated E Aspiration Hazard 1 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4	repeated exposure. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H332 Harmful if inhaled.

GHS02 GHS07 GHS08

(Contd. on page 2)

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

• Signal word Danger	Contd. of page 1)
• Hazard-determining components of labeling:	
p-Xylene	
· Hazard statements	
Flammable liquid and vapor.	
Harmful in contact with skin or if inhaled.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present an	nd easy to do.
Continue rinsing.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.	
• Classification system:	
· Classification system: · NFPA ratings (scale 0 - 4)	
A raings (scale 0 - 4)	
Health = 2	
Fire = 3	
2 0 Reactivity = 0	
• HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
\square $Meduli = 2$	
FIRE 3 Fire = 3 $P_{\text{restriction}} = 0$	
REACTIVITY 0 Reactivity = 0	

• Other hazards

- Results of PBT and vPvB assessment PBT: Not applicable.

(Contd. on page 3)

US

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

(Contd. of page 2)

100.0%

0.0002%

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 106-42-3 p-Xylene

· Table of Nonhazardous Ingredients

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- *Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

	(Contd.	of page	3)
--	---------	---------	----

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals 	(
· PAC-1:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	$2.5 mg/m^3$
· PAC-2:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	27 mg/m ³
· PAC-3:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	160 mg/m ³

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 106-42-3 p-Xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm BEI, OTO, A4

(Contd. on page 5)

US –

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

(Contd. of page 4)

· Ingredients	with	biological	limit values:

CAS: 106-42-3 p-Xylene

BEI 1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic phy	sical and chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Distinct	

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

	(Contd. of page 5)
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	13.3 °C (55.9 °F) 138 °C (280.4 °F)
· Flash point:	25 °C (77 °F)
· Flammability (solid, gaseous):	Flammable.
· Auto igniting:	525 °C (977 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.7 Vol % 7.6 Vol %
· Vapor pressure at 20 °C (68 °F):	8.2 hPa (6.2 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.85666 g/cm ³ (7.14883 lbs/gal) Not determined. Not determined. Not determined.
• Solubility in / Miscibility with Water at 20 °C (68 °F):	0.2 g/l
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC content:	100.0 % 100.00 % 856.7 g/l / 7.15 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

US

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 1,100 mg/kg

Inhalative LC50/4h 11 mg/l

• Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 106-42-3 p-Xylene	3
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	28
· NTP (National Toxicology Program)	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

• General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.

• **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

UN-Number	10/1002
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (p-Xylene)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (p-Xylene)
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
Luanay anaanons	On cargo aircraft only: 220 L

(Contd. of maga 8)

ACTIVE

ACTIVE

Safety Data Sheet acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

	(Conta. of page 8
·IMDG	
\cdot Limited quantities (LQ)	5L
· Excepted quantities ($\widetilde{E}Q$)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (P-XYLENE), 3, III

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

• TSCA (Toxic Substances Control Act):

p-Xylene

2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

· Hazardous Air Pollutants

All ingredients are listed.

· Proposition 65

• Chemicals known to cause cancer:

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 106-42-3 p-Xylene

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

• TLV (Threshold Limit Value)

CAS: 106-42-3 p-Xylene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

Ι

B2

A4

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)



16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

(Contd. on page 11)

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloride Standard 1.0 mg/kg in P-xylene (ASTM D 7536-09)

	(Contd. of page 10)
Date of Preparation / Last Revision:	
Date of preparation / last revision	
Revision 1.2 07/03/2024: Reviewed SDS for accuracy. MH/STN	
07/03/2024 / 1.0	
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 3: Flammable liquids – Category 3	
Acute Toxicity - Dermal 4: Acute toxicity - Category 4	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A	
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category	2
Aspiration Hazard 1: Aspiration hazard – Category 1	
* Data compared to the previous version altered.	