Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

1 Identification

· **Product identifier**

· **Trade name: HBBLI Level 1 Standard**

· **Article number:** ARL029

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586

· **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
· **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666

2 Hazard(s) identification

· **Classification of the substance or mixture**

GHS02 Flame

Flammable Liquids 2	H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Carcinogenicity 1B	H350 May cause cancer.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Repeated Exposure 1	H372 Causes damage to the hearing organs through prolonged or repeated exposure.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

GHS07

Skin Irritation 2	H315 Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.

· **Label elements**
· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 1)

· **Hazard-determining components of labeling:**
Cyclohexane
Styrene 99+%
Hexane
4-Vinyl-1-Cyclohexene
· **Hazard statements**
Highly flammable liquid and vapor.
Causes skin irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
Causes damage to the hearing organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Classification system:**
· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = *1
Fire = 3
Reactivity = 0

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 2)

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**		
CAS: 110-82-7	Cyclohexane	90.0%
CAS: 110-54-3	Hexane	4.0%
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	3.0%
CAS: 100-42-5	Styrene 99+%	3.0%

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:**
Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
CAS: 110-82-7	Cyclohexane	300 ppm
CAS: 110-54-3	Hexane	260 ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	0.3 ppm
CAS: 100-42-5	Styrene 99+%	20 ppm

· **PAC-2:**		
CAS: 110-82-7	Cyclohexane	1700* ppm
CAS: 110-54-3	Hexane	2900* ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	210 ppm
CAS: 100-42-5	Styrene 99+%	130 ppm

· **PAC-3:**		
CAS: 110-82-7	Cyclohexane	10000** ppm
CAS: 110-54-3	Hexane	8600** ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	340 ppm
CAS: 100-42-5	Styrene 99+%	1100* ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

· **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** Store in a cool location.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **Specific end use(s)** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 1 Standard

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 110-82-7 Cyclohexane

PEL	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 100 ppm BEI

CAS: 110-54-3 Hexane

PEL	Long-term value: 1800 mg/m³, 500 ppm
REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 50 ppm Skin; BEI

CAS: 100-40-3 4-Vinyl-1-Cyclohexene

TLV	Long-term value: 0.1 ppm A3
WEEL	Long-term value: 4.4 mg/m³, 1 ppm

CAS: 100-42-5 Styrene 99+%

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3

· **Ingredients with biological limit values:**

CAS: 110-82-7 Cyclohexane

BEI	NIC-50 mg/g creatinine LD50 Intraperitoneal: - Time: end of shift at end of workweek LD50: NIC-1.2-Cyclohexanediol (nonspecific)

CAS: 110-54-3 Hexane

BEI	0.5 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: 2.5-Hexanedione without hydrolysis

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 1 Standard

(Contd. of page 5)

CAS: 100-42-5 Styrene 99+%	
BEI	400 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Mandelic acid plus phenylglyoxylic acid (nonspecific) 40 µg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Styrene

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 1 Standard

(Contd. of page 6)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Liquid
Color:	Clear
· **Odor:**	Organic
· **Odor threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	81 °C (177.8 °F)
· **Flash point:**	-18 °C (-0.4 °F)
· **Flammability (solid, gaseous):**	Highly flammable.
· **Auto igniting:**	260 °C (500 °F)
· **Decomposition temperature:**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· **Explosion limits:**	
Lower:	1.2 Vol %
Upper:	8.3 Vol %
· **Vapor pressure at 20 °C (68 °F):**	104 hPa (78 mm Hg)
· **Vapor pressure at 50 °C (122 °F):**	335 hPa (251.3 mm Hg)
· **Density at 20 °C (68 °F):**	0.7805 g/cm³ (6.51327 lbs/gal)
· **Relative density**	Not determined.
· **Vapor density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	97.0 %
VOC content:	97.00 % 757.1 g/l / 6.32 lb/gal
Solids content:	0.0 %
· **Other information**	No further relevant information available.

US

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 1 Standard

(Contd. of page 7)

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
ATE (Acute Toxicity Estimate)		
Inhalative	LC50/4h	367 mg/l

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	2B
CAS: 100-42-5	Styrene 99+%	2A

· **NTP (National Toxicology Program)**		
CAS: 100-42-5	Styrene 99+%	R

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 1 Standard

(Contd. of page 8)

· **vPvB:** Not applicable.
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **DOT, IMDG, IATA**	UN1993
· **UN proper shipping name**	
· **DOT**	Flammable liquids, n.o.s. (Cyclohexane, Hexane, Styrene 99+%, 4-Vinyl-1-Cyclohexene)
· **IMDG, IATA**	FLAMMABLE LIQUID, N.O.S. (Cyclohexane, Hexane, Styrene 99+%, 4-Vinyl-1-Cyclohexene)
· **Transport hazard class(es)**	
· **DOT**	

· **Class**	3 Flammable liquids
· **Label**	3
· **IMDG, IATA**	

· **Class**	3 Flammable liquids
· **Label**	3
· **Packing group**	
· **DOT, IMDG, IATA**	II
· **Environmental hazards:**	Product contains environmentally hazardous substances: Cyclohexane
· **Special precautions for user**	Warning: Flammable liquids
· **Hazard identification number (Kemler code):**	33
· **EMS Number:**	F-E,S-D
· **Stowage Category**	B
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 9)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **UN "Model Regulation":**	UN 1993 FLAMMABLE LIQUID, N.O.S. (CYCLOHEXANE, HEXANE, STYRENE 99+%, 4-VINYL-1-CYCLOHEXENE), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 110-82-7	Cyclohexane
CAS: 110-54-3	Hexane
CAS: 100-42-5	Styrene 99+%

· **TSCA (Toxic Substances Control Act):**

Cyclohexane	ACTIVE
Hexane	ACTIVE
4-Vinyl-1-Cyclohexene	ACTIVE
Styrene 99+%	ACTIVE

· **Hazardous Air Pollutants**

CAS: 110-54-3	Hexane
CAS: 100-42-5	Styrene 99+%

· **Proposition 65**

· **Chemicals known to cause cancer:**

CAS: 100-40-3	4-Vinyl-1-Cyclohexene
CAS: 100-42-5	Styrene 99+%

· **Chemicals known to cause reproductive toxicity for females:**

CAS: 100-40-3	4-Vinyl-1-Cyclohexene

· **Chemicals known to cause reproductive toxicity for males:**

CAS: 110-54-3	Hexane

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 10)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**		
CAS: 110-82-7	Cyclohexane	I
CAS: 110-54-3	Hexane	II

· **TLV (Threshold Limit Value)**		
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	A3
CAS: 100-42-5	Styrene 99+%	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Cyclohexane
Styrene 99+%
Hexane
4-Vinyl-1-Cyclohexene
· **Hazard statements**
Highly flammable liquid and vapor.
Causes skin irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
Causes damage to the hearing organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Trade name: HBBLI Level 1 Standard

(Contd. of page 11)

Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Environment protection department.*
· **Contact:**
Date of Preparation / Last Revision:
· **Date of preparation / last revision**
Revision 0.0, 11-13-2023: creation date for SDS STN/CMC
11/13/2023
· **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Carcinogenicity 1B: Carcinogenicity – Category 1B
Toxic to Reproduction 2: Reproductive toxicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1
Aspiration Hazard 1: Aspiration hazard – Category 1