Printing date 06/17/2024

Reviewed on 06/17/2024


1 Identification

- · Product identifier
- Trade name: <u>Lead Acetate 5% w/v</u> <u>Solution, ASTM D3227-16</u>
- Article number: 5158
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification





Carcinogenicity 1BH350 May cause cancer.Toxic to Reproduction 1AH360 May damage fertility or the unborn child.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or
repeated exposure.

GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Lead Acetate Acetic Acid, Glacial
Hazard statements May cause an allergic skin reaction.

(Contd. on page 2)

⁻ US

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

		(Contd. of page 1)
May cause cance		
	ility or the unborn child.	
	ge to organs through prolonged or repeated exposure.	
• Precautionary st		
	structions before use.	
	til all safety precautions have been read and understood.	
	ust/fume/gas/mist/vapors/spray.	
	Contaminated work clothing must not be allowed out of the workplace.	
	cloves/protective clothing/eye protection/face protection.	
	with plenty of water. ncerned: Get medical advice/attention.	
	t (see on this label).	
	ce/attention if you feel unwell.	
	<i>br rash occurs: Get medical advice/attention.</i>	
	ed clothing before reuse.	
Store locked up.	eu cioning bejore reuse.	
	nts/container in accordance with local/regional/national/international regulations.	
· Classification sys		
· NFPA ratings (se		
He	alth = 2	
Fin	e = 0	
	activity = 0	
• HMIS-ratings (se	cale 0 - 4)	
HEALTH 2 H	ealth = 2	
	ire = 0	
REACTIVITY 0 R		
	eacuvuy = 0	
• Other hazards		
	nd vPvB assessment	
• PBT: Not applied		
• vPvB: Not applic		
3 Composition/i	nformation on ingredients	
Chamie - 1 - 1-	touizations Mintures	
• Chemical characterization: Mixtures		
• Description: Mixture of the substances listed below with nonhazardous additions.		
· Dangerous components:		
CAS: 6080-56-4	Lead Acetate	4.958%
CAS: 64-19-7	Acetic Acid, Glacial	0.209%

• Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

*

4 First-aid measures

 \cdot Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

94.833%

US

Printing date 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

(Contd. of page 2)

Reviewed on 06/17/2024

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

• Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:			
CAS: 6080-56-4 Lead Acetate	14 mg/m ³		
CAS: 64-19-7 Acetic Acid, Glacial	5 ppm		
• PAC-2:			
CAS: 6080-56-4 Lead Acetate	150 mg/m ³		
CAS: 64-19-7 Acetic Acid, Glacial	35 ppm		
· PAC-3:			
CAS: 6080-56-4 Lead Acetate	920 mg/m ³		
CAS: 64-19-7 Acetic Acid, Glacial	250 ppm		

(Contd. on page 4)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

(Contd. of page 3)

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 64-19-7 Acetic Acid, Glacial

PEL Long-term value: 25 mg/m³, 10 ppm

- REL Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
- TLV Short-term value: 15 ppm

Long-term value: 10 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

US

Printing date 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

Reviewed on 06/17/2024

• Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	Not applicable.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.00844 g/cm ³ (8.41543 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with Water:	Soluble.	

(Contd. on page 6)

US

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

		(Contd. of page
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.2 %	
Water:	94.8 %	
VOC content:	0.21 %	
Solids content:	5.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 10,084 mg/kg

Inhalative LC50/4h 30.3 mg/l

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

CAS: 6080-56-4 Lead Acetate

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

R

1 I S

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN2810
· UN proper shipping name	
$\cdot DOT$	Toxic, liquids, organic, n.o.s. (Lead Acetate)
· IMDG, IATA	TOXIC LIQUID, ORGANIC, N.O.S. (Lead Acetate)
· Transport hazard class(es)	
·DOT	
Toxic a	
· Class	6.1 Toxic substances
· Label	6.1

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name:	: Lead Acetate 5% w/v
	Solution, ASTM D3227-16

	(Contd. of page 2
· IMDG	
· Class · Label	6.1 Toxic substances 6.1
· IATA	
· Class · Label	6.1 Toxic substances 6.1
· Packing group · DOT, IMDG, IATA	III
• Environmental hazards: • Marine pollutant:	Yes Symbol (fish and tree)
 Special precautions for user Hazard identification number (Kemler code). EMS Number: Stowage Category Stowage Code 	Warning: Toxic substances 6.1 F-A,S-A A SW2 Clear of living quarters.
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (LEAD ACETATE) 6.1, III

15 Regulatory information

*

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (ext	remely hazardous substances):	
None of the ingre	edients is listed.	
· Section 313 (Specific toxic chemical listings):		
CAS: 6080-56-4	Lead Acetate	
· TSCA (Toxic Substances Control Act):		
Water		ACTIVE
Acetic Acid, Gla	cial	ACTIVE
· Hazardous Air Pollutants		
CAS: 6080-56-4	Lead Acetate	
	(Con	td. on page 9)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

CAS: 6080-56-4 Lead Acetate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: Lead Acetate Acetic Acid. Glacial · Hazard statements May cause an allergic skin reaction. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

Printing date 06/17/2024

Trade name: Lead Acetate 5% w/v Solution, ASTM D3227-16 Reviewed on 06/17/2024

(Contd. of page 9)

US

	 National regulations: Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).
	 Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
*	16 Other information
	This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
	· Department issuing SDS: Environment protection department.
	· Contact:
	Date of Preparation / Last Revision:
	· Date of preparation / last revision
	Revision 0.1, 06/17/2024: Reviewed SDS for accuracy. MH/STN
	06/17/2024 / 1.0
	· Abbreviations and acronyms:
	IMDG: International Maritime Code for Dangerous Goods
	DOT: US Department of Transportation
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	NFPA: National Fire Protection Association (USA)
	HMIS: Hazardous Materials Identification System (USA)
	VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health
	TLV: Threshold Limit Value
	PEL: Permissible Exposure Limit
	REL: Recommended Exposure Limit
	Sensitization - Skin 1: Skin sensitisation – Category 1
	Carcinogenicity 1B: Carcinogenicity – Category 1B
	Toxic to Reproduction 1A: Reproductive toxicity – Category 1A
	Source if a many dependent of the Dependent dependence of the second state (second dependence). Contract 2

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 • * Data compared to the previous version altered.