Printing date 05/31/2024

Reviewed on 05/31/2024

Identification	
Product identifier	
Trade name: <u>2-Dimethylaminoethane</u> 0.1 Molar In Isopropand	
Article number: SPX318	
Details of the supplier of the safety da Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	ata sheet
Information department: Technical Coordinator Sherman Nelson shermann@aquasolut Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	tions.org
Hazard(s) identification	
Classification of the substance or mix	ture
GHS02 Flame	
GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor.
	H225 Highly flammable liquid and vapor.
Flammable Liquids 2	H225 Highly flammable liquid and vapor. H315 Causes skin irritation.
Flammable Liquids 2	
Flammable Liquids 2 GHS07 Skin Irritation 2 Eye Irritation 2A	H315 Causes skin irritation.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Label elements	H315 Causes skin irritation. H319 Causes serious eye irritation.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Label elements GHS label elements The product is cla Hazard pictograms Flammable Liquids 2 Hazard pictograms	H315 Causes skin irritation. H319 Causes serious eye irritation. e Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Label elements GHS label elements The product is cla Hazard pictograms GHS02 GHS07	H315 Causes skin irritation. H319 Causes serious eye irritation. e Exposure 3 H336 May cause drowsiness or dizziness. assified and labeled according to the Globally Harmonized System (GHS

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

	(Contd. of pag
	ury statements
	from heat/sparks/open flames/hot surfaces No smoking.
	d container and receiving equipment.
	on-proof electrical/ventilating/lighting/equipment.
•	n-sparking tools.
	itionary measures against static discharge.
	hing dust/fume/gas/mist/vapors/spray
	ughly after handling.
	tdoors or in a well-ventilated area.
	tive gloves/protective clothing/eye protection/face protection.
	r hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	D: Remove person to fresh air and keep comfortable for breathing.
If in eyes: I	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to a
Continue rit	ising.
Call a poise	n center/doctor if you feel unwell.
Specific tree	atment (see on this label).
Take off con	ntaminated clothing and wash it before reuse.
If skin irrita	tion occurs: Get medical advice/attention.
If eye irritat	ion persists: Get medical advice/attention.
In case of fi	re: Use CO2, powder or water spray to extinguish.
Store in a w	ell-ventilated place. Keep container tightly closed.
Store in a w	ell-ventilated place. Keep cool.
Store locked	l up.
Dispose of a	contents/container in accordance with local/regional/national/international regulations.
Classification	on system:
NFPA ratin	gs (scale 0 - 4)
	Health = 2
	Fire = 3
2	Reactivity = 0
HMIS_rativ	295 (scale 0 - 4)
	² Health = 2
	3 Fire = 3
REACTIVITY	eactivity = 0
Other hazar	rds
Results of H	BT and vPvB assessment
PBT: Not a	pplicable.
vPvB: Not d	pplicable.
Composit	ion/information on ingredients

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
CAS: 67-63-0 Isopropanol	98.745%
CAS: 108-01-0 N,N-Dimethylethanolamine	1.255%
	-US

(Contd. on page 3)

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. • Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: CAS: 67-63-0 Isopropanol CAS: 108-01-0 N,N-Dimethylethanolamine · PAC-2: CAS: 67-63-0 Isopropanol CAS: 108-01-0 N,N-Dimethylethanolamine · PAC-3: CAS: 67-63-0 Isopropanol

400 ppm

3.7 ppm

2000* ppm

40 ppm

12000** ppm

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

CAS: 108-01-0 N,N-Dimethylethanolamine

(Contd. of page 3) 72 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 67-63-0 Isopropanol

- PEL Long-term value: 980 mg/m³, 400 ppm
- REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
- TLV Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

· Ingredients with biological limit values:

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

US

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 4) Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles · Body protection: Protective work clothing **9** Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Clear de l'alcool · Odor: l · Odor threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: -89.5 °C (-129.1 °F) Boiling point/Boiling range: 82 °C (179.6 °F) · Flash point: 13 °C (55.4 °F) · Flammability (solid, gaseous): Highly flammable. (Contd. on page 6)

US

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

	(Contd. of page :
• Auto igniting:	425 °C (797 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
• Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
· Density at 20 °C (68 °F):	0.79058 g/cm ³ (6.59739 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	98.7 %
VOC content:	98.75 %
	780.7 g/l / 6.51 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 159,388 mg/kg (rat)

(Contd. on page 7)

US -

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 6)

3

Dermal	LD50	96,748 mg/kg ((rabbit)

Inhalative LC50/4h 130,778 mg/l (rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

 \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 8)

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 7)

US

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Isopropanol
IMDG, IATA) FLAMMABLE LIQUID, N.O.S. (Isopropanol
)
Transport hazard class(es)	
DOT	
R.AMABLE LOUD	
3	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code). EMS Number:	
EMS Number: Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex II of	-
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 8)

· UN ''Model Regulation'':

Printing date 05/31/2024

UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

None of the ingredients is listed.	
• •	
Section 313 (Specific toxic chemical listings):	
CAS: 67-63-0 Isopropanol	
TSCA (Toxic Substances Control Act):	
Isopropanol	ACTIVI
N,N-Dimethylethanolamine	ACTIVI
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value)	
	A_{1}

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 10)

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

	(Contd. of page 9)
Hazard-determining components of labeling:	
Isopropanol	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause drowsiness or dizziness.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/show	wer.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres	ent and easy to do.
Continue rinsing.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regular	tions.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

- Date of Preparation / Last Revision: • Date of preparation / last revision Revision 1.2, 05/31/2024: Reviewed SDS for accuracy. MH/STN 05/31/2024
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

(Contd. on page 11)

US

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: 2-Dimethylaminoethane 0.1 Molar In Isopropanol

(Contd. of page 10)

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Syn: Irritation 2A: Serious eye damage/eye irritation – Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.