Printing date 04/12/2024

Reviewed on 04/12/2024

1 Identification · Product identifier · Trade name: Bright Dip • Article number: FIS171 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 **2** *Hazard*(*s*) *identification* · Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS06 Skull and crossbones Acute Toxicity - Inhalation 3 H331 Toxic if inhaled. GHS08 Health hazard Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. GHS07 Acute Toxicity - Dermal 4 H312 Harmful in contact with skin. Sensitization - Skin 1 H317 May cause an allergic skin reaction. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US –

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

(Contd. of page 1) · Hazard pictograms GHS05 GHS06 GHS07 GHS02 GHS · Signal word Danger · Hazard-determining components of labeling: Acetic Acid, Glacial Nitric Acid Hydrochloric Acid · Hazard statements Flammable liquid and vapor. Harmful in contact with skin. Toxic if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 2Reactivity = 0(Contd. on page 3)

- US

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

(Contd. of page 2)

66.747%

31.757%

1.496%

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64-19-7 Acetic Acid, Glacial

CAS: 7697-37-2 Nitric Acid

CAS: 7647-01-0 Hydrochloric Acid

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

US

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

· Advice for firefighters

• Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

. Personal precau	tions, protective equipment and emergency procedures		
	y protective device.		
Wear protective equipment. Keep unprotected persons away.			
· Environmental p			
	duct to reach sewage system or any water course.		
	e authorities in case of seepage into water course or sewage system.		
Dilute with plent			
	nter sewers/ surface or ground water.		
	terial for containment and cleaning up:		
	d-binding material (sand, diatomite, acid binders, universal binders, sawdust).		
Use neutralizing			
Dispose contami	nated material as waste according to section 13.		
Ensure adequate	ventilation.		
· Reference to oth	er sections		
See Section 7 for	information on safe handling.		
See Section 8 for information on personal protection equipment.			
See Section 13 for disposal information.			
· Protective Action Criteria for Chemicals			
· PAC-1:			
CAS: 64-19-7	Acetic Acid, Glacial	5 ppm	
CAS: 7697-37-2	Nitric Acid	0.16 ppm	
CAS: 7647-01-0	Hydrochloric Acid	1.8 ppm	
· PAC-2:			
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm	
CAS: 7697-37-2	Nitric Acid	24 ppm	

CAS: 7647-01-0	Hydrochloric Acid	22 ppm
· PAC-3:		
CAS: 64-19-7	Acetic Acid, Glacial	250 ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 7647-01-0	Hydrochloric Acid	100 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- *Information about protection against explosions and fires. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.*

(Contd. on page 5)

US

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

control parameters		
· Components with limit values that require monitoring at the workplace:		
CAS: 64-19-7 Acetic Acid, Glacial		
PEL	Long-term value: 25 mg/m ³ , 10 ppm	
REL	Short-term value: 37 mg/m ³ , 15 ppm	
	Long-term value: 25 mg/m³, 10 ppm	
TLV	Short-term value: 15 ppm	
	Long-term value: 10 ppm	
CAS: 7697-37-2 Nitric Acid		
PEL	Long-term value: 5 mg/m ³ , 2 ppm	
REL	Short-term value: 10 mg/m³, 4 ppm	
	Long-term value: 5 mg/m ³ , 2 ppm	
TLV	Short-term value: (4) NIC-0.025* ppm	
	Long-term value: (2) ppm	
	*inh. fraction + vapor, NIC-A4	
CAS: 7647-01-0 Hydrochloric Acid		
NIOSH RECOMENDED EXP LIMI	Ceiling limit value: 7.0 mg/m3 mg/m ³	
PEL	Ceiling limit value: 7 mg/m³, 5 ppm	
REL	Ceiling limit value: 7 mg/m³, 5 ppm	
TLV	Ceiling limit value: 2 ppm	
	A4	

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

IS -

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
• General Information • Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Acetic Acid Odor
· Odor threshold:	Not determined.
• pH-value at 20 •C (68 •F):	<1
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 83 °C (181.4 °F)
Flash point:	40 °C (104 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	485 °C (905 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	17 Vol %

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

		(Contd. of page 6
· Vapor pressure at 20 °C (68 °F):	16 hPa (12 mm Hg)	
• Density at 20 •C (68 •F):	1.1612 g/cm ³ (9.69021 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	66.7 %	
VOC content:	66.75 %	
	775.1 g/l / 6.47 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 1,588 mg/kg (rabbit)

Inhalative LC50/4h 9.45 mg/l

· Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

• on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

(Contd. on page 8)

US

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, IMDG, IATA

UN1760

(Contd. on page 9)

US

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

	(Contd. of pag
UN proper shipping name	Company liquida a o c (Nitri- Arid A Arid Cl. 1)
DOT	Corrosive liquids, n.o.s. (Nitric Acid, Acetic Acid, Glacial
IMDG, IATA	CORROSIVE LIQUID, N.O.S. (Nitric Acid, Acetic Acid, Glacial)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code)	
EMS Number:	F-A,S-B
Segregation groups Stowage Category	(SGG1a) Strong acids
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	5 0 I
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (NITRIC ACID, ACET ACID, GLACIAL
), 8, <i>II</i>

(Contd. on page 10)

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

(Contd. of page 9)

\cdot Safety, health and environmental regulations/legislation specific for the substance or i	mixture
No further relevant information available. • Sara	
· Section 355 (extremely hazardous substances):	
CAS: 7697-37-2 Nitric Acid	
Section 313 (Specific toxic chemical listings):	
CAS: 7697-37-2 Nitric Acid	
· TSCA (Toxic Substances Control Act):	
Acetic Acid, Glacial	ACTIVE
Nitric Acid	ACTIVE
Hydrochloric Acid	ACTIVE
· Hazardous Air Pollutants	
CAS: 7647-01-0 Hydrochloric Acid	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
• GHS label elements The product is classified and labeled according to the Globally Har • Hazard pictograms	rmonized System (GHS).
GHS02 GHS05 GHS06 GHS07 GHS08	
· Signal word Danger	
• <i>Hazard-determining components of labeling:</i> Acetic Acid, Glacial Nitric Acid	
Hydrochloric Acid	
· Hazard statements	
Flammable liquid and vapor.	

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

(Contd. of page 10)
Harmful in contact with skin.
Toxic if inhaled.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause damage to organs through prolonged or repeated exposure.
· Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- · Date of preparation / last revision
- *Revision 1.1, 04-12-2024: Updated formulation based on new customer information. STN Revision 0.0 04-12-2024: Creation date for SDS. CMC/STN 04/12/2024*

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

⁻ US

US

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2024

Reviewed on 04/12/2024

Trade name: Bright Dip

	(Contd. of page 11)
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable Liquids 3: Flammable liquids – Category 3	
Acute Toxicity - Dermal 4: Acute toxicity – Category 4	
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3	
Skin Corrosion 1A: Skin corrosion/irritation – Category 1A	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	
Sensitization - Skin 1: Skin sensitisation – Category 1	
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2	
• * Data compared to the previous version altered.	