*Printing date 08/22/2024* 

Reviewed on 08/22/2024

## **1** Identification

- · Product identifier
- · Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl
- · Article number: VWR101
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Aqua Solutions, Inc.
  6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS05 Corrosion

Skin Corrosion 1A Eye Damage 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 




· Signal word Danger

Hazard-determining components of labeling: Nitric Acid Hydrochloric Acid
Hazard statements Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling.

(Contd. on page 2)

Printing date 08/22/2024

Reviewed on 08/22/2024



(Contd. of page 1) Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH \*3 Health = \*3 Fire = 00 FIRE **REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous comp	onents:	
CAS: 7697-37-2	Nitric Acid	3.883%
CAS: 7647-01-0	Hydrochloric Acid	2.0%
• Table of Nonhaza	urdous Ingredients	
CAS: 7732-18-5	Water	93.821%
CAS: 7789-02-8	Chromium Nitrate Nonahydrate	0.075%
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	0.058%
CAS: 6156-78-1	Manganese Acetate Tetrahydrate	0.044%
CAS: 19004-19-4	Cupric Nitrate Hydrate	0.037%
CAS: 7631-99-4	Sodium Nitrate	0.036%
CAS: 7757-79-1	Potassium Nitrate	0.025%
CAS: 7439-89-6	Iron Metal	0.01%
CAS: 7440-02-0	Nickel Metal	0.01%

(Contd. on page 3)

Printing date 08/22/2024

Reviewed on 08/22/2024

#### Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

(Contd. of page 2)

#### **4** First-aid measures

#### · Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- *Protective equipment:* Mouth respiratory protective device.

#### **6** Accidental release measures

Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 7697-37-2 N	Nitric Acid	0.16 ppm
CAS: 7647-01-0 H	Hydrochloric Acid	1.8 ppm
CAS: 13477-34-4 C	Calcium Nitrate Tetrahydrate	12 mg/m <sup>3</sup>
CAS: 6156-78-1 M	Manganese Acetate Tetrahydrate	13 mg/m <sup>3</sup>
CAS: 19004-19-4 C	Cupric Nitrate Hydrate	42 mg/m <sup>3</sup>
CAS: 7631-99-4 S	Sodium Nitrate	4.1 mg/m <sup>3</sup>
· · · · ·	(Co	ntd. on page 4)

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

CAS: 7757-79-1	Potassium Nitrate	(Contd. of page 9 mg/m <sup>3</sup>
CAS: 7439-89-6	Iron Metal	3.2 mg/m
CAS: 7440-02-0	Nickel Metal	4.5 mg/m
PAC-2:		
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	130 mg/m
CAS: 6156-78-1	Manganese Acetate Tetrahydrate	22 mg/m <sup>3</sup>
CAS: 19004-19-4	Cupric Nitrate Hydrate	150 mg/m
CAS: 7631-99-4	Sodium Nitrate	45 mg/m <sup>3</sup>
CAS: 7757-79-1	Potassium Nitrate	100 mg/m
CAS: 7439-89-6	Iron Metal	35 mg/m <sup>3</sup>
CAS: 7440-02-0	Nickel Metal	50 mg/m <sup>3</sup>
PAC-3:		<u>.</u>
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	770 mg/m
CAS: 6156-78-1	Manganese Acetate Tetrahydrate	740 mg/m
CAS: 19004-19-4	Cupric Nitrate Hydrate	240 mg/m
CAS: 7631-99-4	Sodium Nitrate	270 mg/m
CAS: 7757-79-1	Potassium Nitrate	600 mg/m
CAS: 7439-89-6	Iron Metal	150 mg/m
CAS: 7440-02-0	Nickel Metal	99 mg/m <sup>3</sup>

# 7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

US

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

(Contd. of page 4)

· Components with limit	t values that require monitoring at the workplace:
CAS: 7697-37-2 Nitric Acid	
PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
REL	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
TLV	Short-term value: (4) NIC-0.025 ppm Long-term value: (2) ppm NIC-A4
CAS: 7647-01-0 Hydro	ochloric Acid
NIOSH RECOMENDE	D EXP LIMI Ceiling limit value: 7.0 mg/m3 mg/m <sup>3</sup>
PEL	Ceiling limit value: 7 mg/m <sup>3</sup> , 5 ppm
REL	Ceiling limit value: 7 mg/m <sup>3</sup> , 5 ppm
TLV	Ceiling limit value: 2 ppm A4

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- $\cdot$  General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

US

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

• Eye protection:

(Contd. of page 5)



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
General Information		
Appearance:	x···1	
Form: Color:	Liquid Clear greenish-blue	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability:	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.01959 g/cm <sup>3</sup> (8.50848 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	<b>r):</b> Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	93.8 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.3 %	

(Contd. of page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

• Other information

No further relevant information available.

#### **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 77.3 mg/l

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- $\cdot$  on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Internatio	onal Agency for Research on Cancer)	
CAS: 7440-02-0	Nickel Metal	2B
· NTP (National T	Toxicology Program)	
CAS: 7440-02-0	Nickel Metal	R
· OSHA-Ca (Occu	pational Safety & Health Administration)	
None of the ingre	edients is listed.	

#### **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 8)

US -

Printing date 08/22/2024

Reviewed on 08/22/2024

#### Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

# **13 Disposal considerations**

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Aci Hydrochloric Acid)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nith Acid, Hydrochloric Acid)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
- Class	8 Corrosive substances
Label	8
IMDG, IATA	
and the second s	
Class	8 Corrosive substances
Label	8
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

	(Contd. of page
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler co	
· EMS Number:	F-A, S-B
· Segregation groups	(SGG1) Acids
· Stowage Category	В
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG36 Stow "separated from" SGG18-alkalis.
	SG49 Stow "separated from" SGG6-cyanides
• Transport in bulk according to Annex II	of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L
~ `	On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities ( $\widetilde{EQ}$ )	Code: E2
· · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S
-	(NITRIC ACID, HYDROCHLORIC ACID), 8, II

# **15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

CAS: 7697-37-2 N	litric Acid	
Section 313 (Speci	fic toxic chemical listings):	
CAS: 7697-37-2	Nitric Acid	
CAS: 7789-02-8	Chromium Nitrate Nonahydrate	
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	
CAS: 7757-79-1	Potassium Nitrate	
CAS: 7440-02-0	Nickel Metal	
TSCA (Toxic Subs	tances Control Act):	
Water		ACTIV
Nitric Acid		ACTIV
Hydrochloric Acid		ACTIV
Sodium Nitrate		ACTIV
Potassium Nitrate		ACTIV
Iron Metal		ACTIV
Nickel Metal		ACTIV

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

(Contd. of page 9)

· Hazardous Air PollutantsCAS: 7647-01-0Hydrochloric Acid

· Proposition 65

 $\cdot$  Chemicals known to cause cancer:

CAS: 7440-02-0 Nickel Metal

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 7440-02-0 Nickel Metal

A5

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 7440-02-0 Nickel Metal

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Nitric Acid Hydrochloric Acid · Hazard statements Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Printing date 08/22/2024

Reviewed on 08/22/2024

Trade name: Mixed Metal Standard 100.0 ppm each in 2% HCl

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

#### · Contact:

Date of Preparation / Last Revision: • Date of preparation / last revision

Revision 0.0, 08-22-2024: Creation date for SDS. CMC/STN 08/22/2024 / -• Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

- CAS: Chemical Abstracts Service (division of the American Chemical Socie NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Eye Damage 1: Serious eye damage/eye irritation – Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

-US -