

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

## 1 Identification

- **Product identifier**
- **Trade name:** Ethylene Glycol 1,000 ppm w/w Standard
- **Article number:** THE534
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Aqua Solutions, Inc.  
6913 Highway 225  
DEER PARK, TX 77536  
USA  
800-256-2586
- **Information department:**  
Technical Coordinator  
Sherman Nelson [shermann@aquasolutions.org](mailto:shermann@aquasolutions.org)
- **Emergency telephone number:**  
Chemtrec: 800-424-9300  
Canutec: 613-996-6666



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Oral 3

H301 Toxic if swallowed.

Acute Toxicity - Dermal 3

H311 Toxic in contact with skin.

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and the visual organs.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
*Methanol*

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 1)

· **Hazard statements**

Highly flammable liquid and vapor.  
Toxic if swallowed, in contact with skin or if inhaled.  
Causes damage to the central nervous system and the visual organs.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If swallowed: Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Rinse mouth.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed: Call a POISON CENTER or doctor/physician.  
Call a poison center/doctor if you feel unwell.  
Take off immediately all contaminated clothing and wash it before reuse.  
In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-56-1 Methanol	99.9%
-----------------------	-------

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 2)

**· Table of Nonhazardous Ingredients**

CAS: 107-21-1 Ethylene Glycol	0.1%
-------------------------------	------

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**· PAC-1:**

CAS: 67-56-1 Methanol	530 ppm
-----------------------	---------

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 3)

CAS: 107-21-1	Ethylene Glycol	30 ppm
<b>· PAC-2:</b>		
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 107-21-1	Ethylene Glycol	150 ppm
<b>· PAC-3:</b>		
CAS: 67-56-1	Methanol	7200* ppm
CAS: 107-21-1	Ethylene Glycol	900 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

<b>· Components with limit values that require monitoring at the workplace:</b>	
<b>CAS: 67-56-1 Methanol</b>	
PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
<b>· Ingredients with biological limit values:</b>	
<b>CAS: 67-56-1 Methanol</b>	
BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 4)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Colorless

· **Odor:** Methanol

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: -97.8 °C (-144 °F)

Boiling point/Boiling range: 64.4 °C (147.9 °F)

· **Flash point:** 11 °C (51.8 °F)

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

Trade name: Ethylene Glycol 1,000 ppm w/w Standard

(Contd. of page 5)

· <b>Flammability (solid, gaseous):</b>	Highly flammable.
· <b>Auto igniting:</b>	455 °C (851 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	5.5 Vol %
<b>Upper:</b>	44 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	128 hPa (96 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.79182 g/cm <sup>3</sup> (6.60774 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	99.9 %
<b>VOC content:</b>	99.90 %
	791.0 g/l / 6.60 lb/gal
<b>Solids content:</b>	0.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US  
(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

Trade name: Ethylene Glycol 1,000 ppm w/w Standard

(Contd. of page 6)

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### ATE (Acute Toxicity Estimate)

Oral	LD50	100 mg/kg
Dermal	LD50	300 mg/kg
Inhalative	LC50/4h	3 mg/l

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Toxic

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024



Reviewed on 04/11/2024

Trade name: Ethylene Glycol 1,000 ppm w/w Standard

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	<p style="margin-left: 20px;">UN1993</p>
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	<p style="margin-left: 20px;">Flammable liquids, n.o.s. (Methanol) FLAMMABLE LIQUID, N.O.S. (Methanol)</p>
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p style="margin-left: 20px;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p style="margin-left: 20px;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	<p style="margin-left: 20px;">II</p>
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> </ul>	<p style="margin-left: 20px;">Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> <li>· <b>Stowage Code</b></li> </ul>	<p style="margin-left: 20px;">Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.</p>
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	<p style="margin-left: 20px;">Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> </ul>	<p style="margin-left: 20px;">On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p style="margin-left: 20px;">1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</p>

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

Trade name: Ethylene Glycol 1,000 ppm w/w Standard

(Contd. of page 8)

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANOL), 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

All ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

Methanol

ACTIVE

Ethylene Glycol

ACTIVE

· **Hazardous Air Pollutants**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

All ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

CAS: 107-21-1 Ethylene Glycol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS06

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Methanol

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 9)

- **Hazard statements**

*Highly flammable liquid and vapor.  
Toxic if swallowed, in contact with skin or if inhaled.  
Causes damage to the central nervous system and the visual organs.*

- **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If swallowed: Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Rinse mouth.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed: Call a POISON CENTER or doctor/physician.  
Call a poison center/doctor if you feel unwell.  
Take off immediately all contaminated clothing and wash it before reuse.  
In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.

- **Contact:**

*Date of Preparation / Last Revision:*

- **Date of preparation / last revision**

*Revision 0.0 04-11-2024: Creation date for SDS. CMC/STN  
04/11/2024*

- **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value*

(Contd. on page 11)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 04/11/2024

Reviewed on 04/11/2024

**Trade name: Ethylene Glycol 1,000 ppm w/w Standard**

(Contd. of page 10)

*PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Acute Toxicity - Oral 3: Acute toxicity – Category 3**Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1*

US