

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

1 Identification

- **Product identifier**
- **Trade name:** Sulfur Standard Blank in Diesel
- **Article number:** LY366
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

- Muta. 1A H340 May cause genetic defects.
Carc. 2 H351 Suspected of causing cancer.
Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Fuels, diesel
Biphenyl
Naphthalene
- **Hazard statements**
Combustible liquid.
May cause genetic defects.
Suspected of causing cancer.
- **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 1)

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 68334-30-5	Fuels, diesel	90.0%
CAS: 91-20-3	Naphthalene	3.0%
CAS: 92-52-4	Biphenyl	1.5%

· **Table of Nonhazardous Ingredients**

CAS: 2551-13-7	trimethyl benzene	1.5%
----------------	-------------------	------

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 68334-30-5	Fuels, diesel	300 mg/m ³
CAS: 91-20-3	Naphthalene	15 ppm
CAS: 92-52-4	Biphenyl	0.87 ppm

· **PAC-2:**

CAS: 68334-30-5	Fuels, diesel	3,300 mg/m ³
CAS: 91-20-3	Naphthalene	83 ppm
CAS: 92-52-4	Biphenyl	9.6 ppm

· **PAC-3:**

CAS: 68334-30-5	Fuels, diesel	20,000 mg/m ³
CAS: 91-20-3	Naphthalene	500 ppm
CAS: 92-52-4	Biphenyl	300 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 3)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 68334-30-5 Fuels, diesel

TLV	Long-term value: 100* mg/m ³ as total hydrocarbons; Skin; *inh. fraction + vapor
-----	------------------------------------------------------------------------------------------------

CAS: 91-20-3 Naphthalene

PEL	Long-term value: 50 mg/m ³ , 10 ppm
-----	------------------------------------------------

REL	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
-----	---------------------------------------------------------------------------------------------------

TLV	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
-----	-------------------------------------------------------------

CAS: 92-52-4 Biphenyl

PEL	Long-term value: 1 mg/m ³ , 0.2 ppm
-----	------------------------------------------------

REL	Long-term value: 1 mg/m ³ , 0.2 ppm
-----	------------------------------------------------

TLV	Long-term value: 1.3 mg/m ³ , 0.2 ppm
-----	--------------------------------------------------

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

- **Breathing equipment:** Not required.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Clear, colorless to light amber

Odor:	Characteristic
--------------	----------------

Odor threshold:	Not determined.
------------------------	-----------------

pH-value:	Not determined.
------------------	-----------------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 4)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	>60 °C (>140 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	
	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C (104 °F):	5 mm ² /s
· Solvent content:	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gl
Solids content:	4.5 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)		
Oral	LD50	14,655 mg/kg (rat)
Dermal	LD50	166,667 mg/kg (rat)

CAS: 91-20-3 Naphthalene		
Oral	LD50	500 mg/kg (ATE)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 68334-30-5	Fuels, diesel	2B
CAS: 91-20-3	Naphthalene	2B

- **NTP (National Toxicology Program)**

CAS: 91-20-3	Naphthalene	R
--------------	-------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017





Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> · UN-Number · DOT · IMDG, IATA | <p>NA1993
UN1993</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA | <p>COMBUSTIBLE LIQUID, N.O.S (Fuels, diesel)
FLAMMABLE LIQUID, N.O.S. (Fuels, diesel, NAPHTHALENE, CRUDE, Biphenyl), MARINE POLLUTANT
FLAMMABLE LIQUID, N.O.S. (Fuels, diesel)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <p>
3</p> |
| <ul style="list-style-type: none"> · Class | <p>3 Combustible liquids</p> |
| <ul style="list-style-type: none"> · IMDG | <p> </p> |
| <ul style="list-style-type: none"> · Class · Label | <p>9 Miscellaneous dangerous substances and articles
9</p> |
| <ul style="list-style-type: none"> · IATA | <p></p> |
| <ul style="list-style-type: none"> · Class · Label | <p>9 Miscellaneous dangerous substances and articles
9</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | <p>III</p> |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | <p>Product contains environmentally hazardous substances:
Naphthalene
Symbol (fish and tree)</p> |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): | <p>Warning: Miscellaneous dangerous substances and articles
90</p> |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 7)

· EMS Number:	<i>F-E,S-E</i>
· Stowage Category	<i>A</i>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	

· IMDG	
· Limited quantities (LQ)	<i>5L</i>
· Excepted quantities (EQ)	<i>Code: E1</i>
	<i>Maximum net quantity per inner packaging: 30 ml</i>
	<i>Maximum net quantity per outer packaging: 1000 ml</i>
· UN "Model Regulation":	<i>UN 1993 FLAMMABLE LIQUIDS, N.O.S. (FUELS, DIESEL), 9, III</i>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

CAS: 91-20-3 | *Naphthalene*

CAS: 92-52-4 | *Biphenyl*

- **TSCA (Toxic Substances Control Act):**

Fuels, diesel

Naphthalene

Biphenyl

- **TSCA new (21st Century Act) (Substances not listed)**

- **Proposition 65**

- **Chemicals known to cause cancer:**

CAS: 91-20-3 | *Naphthalene*

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

CAS: 91-20-3 | *Naphthalene*

C, CBD

CAS: 92-52-4 | *Biphenyl*

SC

- **TLV (Threshold Limit Value established by ACGIH)**

CAS: 68334-30-5 | *Fuels, diesel*

A3

CAS: 91-20-3 | *Naphthalene*

A4

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Fuels, diesel

Biphenyl

Naphthalene

· **Hazard statements**

Combustible liquid.

May cause genetic defects.

Suspected of causing cancer.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

11-30-2017: review SDS for accuracy. STN

Creation date for SDS 12-11-2015. STN

11/30/2017 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/30/2017

Reviewed on 11/30/2017

Trade name: Sulfur Standard Blank in Diesel

(Contd. of page 9)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Muta. 1A: Germ cell mutagenicity – Category 1A
Carc. 2: Carcinogenicity – Category 2

US