

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

1 Identification

- **Product identifier**
- **Trade name:** Heptane, Laboratory Grade 0.2 uM Filtered
- **Article number:** ND720
- **CAS Number:**
142-82-5
- **EC number:**
205-563-8
- **Index number:**
601-008-00-2
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 1

H330 Fatal if inhaled.



GHS08 Health hazard

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: **Heptane, Laboratory Grade 0.2 uM Filtered**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS06 GHS07 GHS08

· **Signal word** *Danger*· **Hazard statements***Highly flammable liquid and vapor.**Fatal if inhaled.**Causes skin irritation.**May cause drowsiness or dizziness.**May be fatal if swallowed and enters airways.*· **Precautionary statements***Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**[In case of inadequate ventilation] wear respiratory protection.**If swallowed: Immediately call a poison center/doctor.**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**Call a poison center/doctor if you feel unwell.**Specific treatment is urgent (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**In case of fire: Use CO₂, powder or water spray to extinguish.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)***Health = 2**Fire = 3**Reactivity = 0*· **HMIS-ratings (scale 0 - 4)***Health = 2**Fire = 3**Reactivity = 0*· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** *Not applicable.*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
CAS: 142-82-5 n-Heptane
- **Identification number(s)**
- **EC number:** 205-563-8
- **Index number:** 601-008-00-2

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Remove breathing apparatus only after contaminated clothing have been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 3)

- See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
 - **PAC-1:** 500 ppm
 - **PAC-2:** 830 ppm
 - **PAC-3:** 5000* ppm

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 142-82-5 n-Heptane

PEL	Long-term value: 2000 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV	Short-term value: 500 ppm Long-term value: 400 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 4)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Gasoline-like
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	-57.2 °C (-71 °F)
Boiling point/Boiling range:	98.3 °C (208.9 °F)

· **Flash point:** -7.8 °C (18 °F)

· **Flammability:** Highly flammable.

· **Auto igniting:** 215 °C (419 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Not determined.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 5)

Upper:	6.7 Vol %
· Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
· Vapor pressure at 50 °C (122 °F):	190 hPa (142.5 mm Hg)
· Density at 20 °C (68 °F):	0.68 g/cm ³ (5.6746 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	0.05 g/l
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.4 mPas
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Inhalative	LC50/4h	0.05 mg/l (ATE)
------------	---------	-----------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)** Substance is not listed.
- **NTP (National Toxicology Program)** Substance is not listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered



(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Assessment by list): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1206
- **UN proper shipping name**
- **DOT** Heptanes
- **IMDG** HEPTANES, MARINE POLLUTANT
- **IATA** HEPTANES
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG**
- 
- **Class** 3 Flammable liquids

(Contd. on page 8)

US

Safety Data Sheet


acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 7)

· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Environmentally hazardous substance, liquid; Marine Pollutant
· Marine pollutant:	No Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1206 HEPTANES, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is not listed.
- **Section 313 (Specific toxic chemical listings):** Substance is not listed.
- **TSCA (Toxic Substances Control Act):** ACTIVE
- **Hazardous Air Pollutants** Substance is not listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency) D**
- **TLV (Threshold Limit Value)** Substance is not listed.

(Contd. on page 9)

- US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 8)

- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** *Danger*
- **Hazard statements**
 - Highly flammable liquid and vapor.*
 - Fatal if inhaled.*
 - Causes skin irritation.*
 - May cause drowsiness or dizziness.*
 - May be fatal if swallowed and enters airways.*
- **Precautionary statements**
 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
 - Ground/bond container and receiving equipment.*
 - Use explosion-proof electrical/ventilating/lighting/equipment.*
 - Use only non-sparking tools.*
 - Take precautionary measures against static discharge.*
 - Do not breathe dust/fume/gas/mist/vapors/spray.*
 - Wash thoroughly after handling.*
 - Use only outdoors or in a well-ventilated area.*
 - Wear protective gloves/protective clothing/eye protection/face protection.*
 - [In case of inadequate ventilation] wear respiratory protection.*
 - If swallowed: Immediately call a poison center/doctor.*
 - Do NOT induce vomiting.*
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - Call a poison center/doctor if you feel unwell.*
 - Specific treatment is urgent (see on this label).*
 - Take off contaminated clothing and wash it before reuse.*
 - If skin irritation occurs: Get medical advice/attention.*
 - In case of fire: Use CO₂, powder or water spray to extinguish.*
 - Store in a well-ventilated place. Keep container tightly closed.*
 - Store in a well-ventilated place. Keep cool.*
 - Store locked up.*
 - Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
 - Date of Preparation / Last Revision:*
- **Date of preparation / last revision**
 - Revision 1.2, 10/31/2024: Reviewed SDS for accuracy. CMC/STN*
 - 11/01/2024 / 1.2*
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods*

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/01/2024

Reviewed on 10/31/2024

Trade name: Heptane, Laboratory Grade 0.2 uM Filtered

(Contd. of page 9)

*DOT: US Department of Transportation**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Acute Toxicity - Inhalation 1: Acute toxicity – Category 1**Skin Irritation 2: Skin corrosion/irritation – Category 2**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**Aspiration Hazard 1: Aspiration hazard – Category 1**** Data compared to the previous version altered.**

US