

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

1 Identification

- **Product identifier**
- **Trade name:** Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl
- **Article number:** ND401
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Eye Irritation 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard statements**
Causes serious eye irritation.
- **Precautionary statements**
Wash thoroughly after handling.
Wear eye protection / face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 0
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT: Not applicable.**
- **vPvB: Not applicable.**

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture of the substances listed below with nonhazardous additions.**

· **Dangerous components:**

CAS: 10043-52-4	Calcium Chloride	12.433%
-----------------	------------------	---------

· **Table of Nonhazardous Ingredients**

CAS: 7732-18-5	Water	71.664%
CAS: 7647-14-5	Sodium Chloride	14.714%
CAS: 7447-40-7	Potassium Chloride	1.189%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 10043-52-4	Calcium Chloride	12 mg/m ³
-----------------	------------------	----------------------

· **PAC-2:**

CAS: 10043-52-4	Calcium Chloride	130 mg/m ³
-----------------	------------------	-----------------------

· **PAC-3:**

CAS: 10043-52-4	Calcium Chloride	790 mg/m ³
-----------------	------------------	-----------------------

7 Handling and storage

· **Handling:**

· **Precautions for safe handling** *No special precautions are necessary if used correctly.*

· **Information about protection against explosions and fires:** *No special measures required.*

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** *No special requirements.*

· **Information about storage in one common storage facility:** *Not required.*

· **Further information about storage conditions:** *Keep receptacle tightly sealed.*

· **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** *No further data; see section 7.*

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** *The lists that were valid during the creation were used as basis.*

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** *Not required.*

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 3)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Odorless
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 4)

· Density at 20 °C (68 °F):	1.17828 g/cm ³ (9.83275 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.

· Solubility in / Miscibility with Water:	Fully miscible.
--	-----------------

· Partition coefficient (n-octanol/water):	Not determined.
---	-----------------

· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:	
Water:	71.7 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal

Solids content:	28.3 %
------------------------	--------

· Other information	No further relevant information available.
----------------------------	--

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)		
--------------------------------------	--	--

Oral	LD50	8,043 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl

(Contd. of page 5)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** *No further relevant information available.*

· **Persistence and degradability** *No further relevant information available.*

· **Behavior in environmental systems:**

· **Bioaccumulative potential** *No further relevant information available.*

· **Mobility in soil** *No further relevant information available.*

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

· **Other adverse effects** *No further relevant information available.*

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

· **Recommended cleansing agent:** *Water, if necessary with cleansing agents.*

14 Transport information

· **UN-Number**

· **DOT, ADN, IMDG, IATA** *Not regulated*

· **UN proper shipping name**

· **DOT, ADN, IMDG, IATA** *Not regulated*

· **Transport hazard class(es)**

· **DOT, ADN, IMDG, IATA**

· **Class** *Not regulated*

· **Packing group**

· **DOT, IMDG, IATA** *Not regulated*

· **Environmental hazards:**

· **Marine pollutant:** *No*

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 6)

- | | |
|--|-----------------|
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

Water	ACTIVE
Sodium Chloride	ACTIVE
Calcium Chloride	ACTIVE
Potassium Chloride	ACTIVE

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Drilling Fluid #1 7.35 g/L K; 68.2 g/L Na
52.9 g/L Ca; 205.4 g/l Cl**

(Contd. of page 7)

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard statements**

Causes serious eye irritation.

· **Precautionary statements**

Wash thoroughly after handling.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

Date of Preparation / Last Revision:

· **Date of preparation / last revision**

Revision 1.2, 05/23/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0 10-04-2016: Creation date for SDS. STN

05/23/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

· *** Data compared to the previous version altered.**