

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

1 Identification

- **Product identifier**
- **Trade name:** Nitrogen Standard Blank
(Xylene) ASTM D5762
- **Article number:** LY338
- **CAS Number:**
1330-20-7
- **EC number:**
215-535-7
- **Index number:**
601-022-00-9
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS07

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Skin Irritation 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

**Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762**

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Xylene (Xylol)

· **Hazard statements**

Flammable liquid and vapor.

Harmful in contact with skin or if inhaled.

Causes skin irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

CAS: 1330-20-7 Xylene (Xylol)

· **Identification number(s)**

· **EC number:** 215-535-7

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

**Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762**

· **Index number:** 601-022-00-9

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

130 ppm

· **PAC-2:**

920* ppm

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762

(Contd. of page 3)

· **PAC-3:**
2500* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 1330-20-7 Xylene (Xylol)

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, A4

· **Ingredients with biological limit values:**

CAS: 1330-20-7 Xylene (Xylol)

BEI 1.5 g/g creatinine
LD50 Intraperitoneal: urine
Time: end of shift
LD50: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762

(Contd. of page 4)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Clear

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

- **Flash point:** 30 °C (86 °F)

- **Flammability (solid, gaseous):** Flammable.

- **Auto igniting:** 500 °C (932 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762

(Contd. of page 5)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F): 6.7-8.2 hPa (5-6.2 mm Hg)	
· Density at 20 °C (68 °F): 0.87 g/cm ³ (7.26015 lbs/gal)	
· Relative density Not determined.	
· Vapor density Not determined.	
· Evaporation rate Not determined.	
· Solubility in / Miscibility with Water at 20 °C (68 °F): 0.2 g/l	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.61 mPas
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.00 %
	870.0 g/l / 7.26 lb/gal
· Solids content: 0.0 %	
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	1,100 mg/kg
Inhalative	LC50/4h	11 mg/l

CAS: 1330-20-7 Xylene (Xylol)

Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4h	11 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762

(Contd. of page 6)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

3

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Assessment by list): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|----------------------------------|---------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1307 |
| · UN proper shipping name | |
| · DOT | Xylenes |
| · IMDG, IATA | XYLENES |

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** III

· **Environmental hazards:**
 · **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids
 · **Hazard identification number (Kemler code):** 30
 · **EMS Number:** F-E,S-D
 · **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L
 · **Hazardous substance:** 100 lbs, 45.4 kg

· **IMDG**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1307 XYLENES, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 No further relevant information available.
 · **Sara**

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

**Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762**

(Contd. of page 8)

· **Section 313 (Specific toxic chemical listings):**

Substance is listed.

· **TSCA (Toxic Substances Control Act):**

ACTIVE

· **Hazardous Air Pollutants**

Substance is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

I

· **TLV (Threshold Limit Value)**

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Xylene (Xylol)

· **Hazard statements**

Flammable liquid and vapor.

Harmful in contact with skin or if inhaled.

Causes skin irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/16/2024

Reviewed on 05/16/2024

**Trade name: Nitrogen Standard Blank
(Xylene) ASTM D5762**

(Contd. of page 9)

Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
Date of Preparation / Last Revision:
- **Date of preparation / last revision**
Revision 1.2, 05/16/2024: Reviewed SDS for accuracy. MH/STN
05/16/2024
- **Abbreviations and acronyms:**
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 3: Flammable liquids – Category 3
 Acute Toxicity - Dermal 4: Acute toxicity – Category 4
 Skin Irritation 2: Skin corrosion/irritation – Category 2
- *** Data compared to the previous version altered.**

US