Printing date 08/08/2024 Reviewed on 08/08/2024

1 Identification

- · Product identifier
- · Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade
- · Article number: B8240-4L
- CAS Number: 111-76-2 • EC number: 203-905-0
- Index number: 603-014-00-0
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

AQUA SOLUTIONS

*

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled. Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Flammable Liquids 4 H227 Combustible liquid.

- · Label elements
- GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- GHS07
- · Signal word Warning
- · Hazard statements

Combustible liquid.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 1)

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin: Wash with plenty of water.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 2Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

CAS: 111-76-2 2-butoxyethanol

- · Identification number(s)
- · EC number: 203-905-0
- · Index number: 603-014-00-0

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- · Protective Action Criteria for Chemicals
- · **PAC-1**: 60 ppm
- · PAC-2: 120 ppm
- · PAC-3: 700 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 20 ppm

BEI, A3

· Ingredients with biological limit values:

CAS: 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Butoxyacetic acid (BAA) (with hydrolysis)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	ahamiaal nyanaytias	
Information on basic physical and General Information	cnemicai properties	
Appearance:		
Form:	Oily	
Color:	Colorless	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	-75 °C (-103 °F)	
Boiling point/Boiling range:	169-172 °C (336.2-341.6 °F)	
Flash point:	67 °C (152.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Not determined.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	10.6 Vol %	
Vapor pressure at 20 °C (68 °F):	<1 hPa (<0.8 mm Hg)	
Density at 20 °C (68 °F):	0.9 g/cm³ (7.5105 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with Water at 20 °C (68 °F):	1 g/l	
Partition coefficient (n-octanol/wat		
Viscosity:	,	
Dynamic at 20 °C (68 °F):	6.4 mPas	
Kinematic:	Not determined.	

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

Oral	LD50	1,200 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4h	3 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) 3
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

HS

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 4 0	A Company				
44	rang	nort	Tinit	ormat	ากท
	LI WILD	u	ועועו	JI III UUI	uoiv

$\cdot \boldsymbol{U}$	N-	Nui	mbei	۰
------------------------	----	-----	------	---

 $\cdot DOT$

NA1993 UN1993

· IMDG, IATA

· IMDG, IATA

· UN proper shipping name

COMBUSTIBLE LIQUID, N.O.S (2-butoxyethanol) FLAMMABLE LIQUID, N.O.S. (2-butoxyethanol)

- · Transport hazard class(es)
- $\cdot DOT$



· Class · Label 3 Combustible liquids

· IMDG, IATA



· Class · Label 3 Flammable liquids

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

· Marine pollutant:

No

· Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code): 30

F-E,S-E

· EMS Number:

· Stowage Category

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 8)

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

	(Contd. of page 7
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (2-BUTOXYETHANOL) 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is listed.
- · TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) NL
- · TLV (Threshold Limit Value) A3
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

· Hazard statements

Combustible liquid.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

(Contd. on page 9)

Printing date 08/08/2024 Reviewed on 08/08/2024

Trade name: 2-Butoxyethanol (Butyl Cellosolve®), Practical Grade

(Contd. of page 8)

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin: Wash with plenty of water.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 2.0, 08-08-2024: updated hazards and DOT information to match supplier SDS. STN

Revision 1.3 08/07/2024: Reviewed SDS for accuracy. CMC/STN

Creation date for SDS 07-02-2014. STN

08/08/2024 / 1.3

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 $IATA: International\ Air\ Transport\ Association$

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

* * Data compared to the previous version altered.

US