

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

1 Identification

- **Product identifier**
- **Trade name:** Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade
- **Article number:** E2438
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Single Exposure 2 H371 May cause damage to the central nervous system and the visual organs.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
Methanol
- **Hazard statements**
Highly flammable liquid and vapor.
Suspected of causing cancer.
May cause damage to the central nervous system and the visual organs.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 1)

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF exposed or concerned: Get medical advice/attention.
- In case of fire: Use CO₂, powder or water spray to extinguish.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	92.904%
CAS: 67-56-1	Methanol	4.05%
CAS: 141-78-6	Ethyl Acetate	1.151%
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	1.025%

· **Table of Nonhazardous Ingredients**

CAS: 142-82-5	n-Heptane	0.87%
---------------	-----------	-------

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 141-78-6	Ethyl Acetate	1,200 ppm
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 142-82-5	n-Heptane	500 ppm

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 3)

· PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 141-78-6	Ethyl Acetate	1,700 ppm
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 142-82-5	n-Heptane	830 ppm
· PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 141-78-6	Ethyl Acetate	10000** ppm
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 142-82-5	n-Heptane	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1000 ppm
A3	

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 4)

CAS: 67-56-1 MethanolPEL Long-term value: 260 mg/m³, 200 ppmREL Short-term value: 325 mg/m³, 250 ppm
Long-term value: 260 mg/m³, 200 ppm
SkinTLV Short-term value: 250 ppm
Long-term value: 200 ppm
Skin; BEIc**CAS: 141-78-6 Ethyl Acetate**PEL Long-term value: 1400 mg/m³, 400 ppmREL Long-term value: 1400 mg/m³, 400 ppm

TLV Long-term value: 400 ppm

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)PEL Long-term value: 410 mg/m³, 100 ppmREL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppmTLV Short-term value: 75 ppm
Long-term value: 20 ppm
BEI, A3**· Ingredients with biological limit values:****CAS: 67-56-1 Methanol**BEI 15 mg/L
LD50 Intraperitoneal: urine
Time: end of shift
LD50: Methanol (background, nonspecific)**CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)**BEI 1 mg/L
LD50 Intraperitoneal: urine
Time: end of shift
LD50: MIBK**· Additional information:** The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Acidic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172.4 °F)

· **Flash point:** 13 °C (55.4 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 425 °C (797 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	3.5 Vol %
Upper:	19 Vol %

· **Vapor pressure at 20 °C (68 °F):** 59 hPa (44.3 mm Hg)

· **Density at 20 °C (68 °F):** 0.78166 g/cm³ (6.52295 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 6)

- | | |
|---|--|
| · Solubility in / Miscibility with Water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 100.0 % |
| VOC content: | 100.00 % |
| | 781.7 g/l / 6.52 lb/gal |
| · Solids content: | 0.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	2,469 mg/kg
Dermal	LD50	7,407 mg/kg
Inhalative	LC50/4h	69.3 mg/l

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1170 |
| · UN proper shipping name | |
| · DOT | Ethanol solutions |
| · IMDG | ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |
| · IATA | ETHANOL SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 8)

· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids

· **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:**
 · **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-D

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-56-1 Methanol

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **TSCA (Toxic Substances Control Act):**

Ethyl Alcohol, Absolute 200 Proof ACTIVE

Methanol ACTIVE

Ethyl Acetate ACTIVE

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 9)

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	ACTIVE
n-Heptane	ACTIVE

· **Hazardous Air Pollutants**

CAS: 67-56-1	Methanol
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Proposition 65**

· **Chemicals known to cause cancer:**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
---------------	---

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof
CAS: 67-56-1	Methanol
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	I
CAS: 142-82-5	n-Heptane	D

· **TLV (Threshold Limit Value)**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	A3
--------------	-----------------------------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.	
------------------------------------	--

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
Methanol

· **Hazard statements**

Highly flammable liquid and vapor.
Suspected of causing cancer.
May cause damage to the central nervous system and the visual organs.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethyl Alcohol, Denatured
Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 10)

Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Environment protection department.

• **Contact:**

Date of Preparation / Last Revision:

• **Date of preparation / last revision**

Revision 1.2, 07-25-2024: Reviewed SDS for accuracy. STN/GW
 07/25/2024 / -

• **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) – Category 2

• *** Data compared to the previous version altered.**