Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: isopropanol-Water 99:10 v/v Solution Article numbe: 17614 Details of the supplier of the safety data sheet ManufacturerSupplier: Aqua Solutions, Inc. 6013 Highway 225 DEER PARK, TX 77336 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org Chanter: 601-24-9300 Canutec: 613-996-6666 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Information of the substance or mixture Voltage: GHS02 Flame Flammable Liquids 2 II225 Highly flammable liquid and vapor. Voltage: GHS07 Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard jetograms Signal word Danger Hazard-determining components of labeling: Isopropanol May cause drowsiness or dizziness. Flamathenens Highly flammable liquid and vapor. Causes serious eye irritation. Mazard determining components of labeling: Isopropanol May cause drowsiness or dizenses.		
90:10 v/v Solution Article number: 17614 Details of the supplier of the safety data sheet ManufacturerSupplier: Aqua Solutions, Inc. 6013 Highway 225 DEER PARK, TX 77536 USM 800-256-2586 Information department: Technical Coordinator Schemers: Bool 24-9300 Channes: 000-24-9300 Canutes: 613-990-6666 Hazard(s) identification Hazard(s) identification Classification of the substance or mixture (a) Solution: (b) Solution: Filter Trajet Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. (a) Solution: (b) Solution: (c) Filter Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. (a) Solution: (b) Solution: (c) Solution: (c) Single Exposure 3 H336 May cause drowsiness or dizziness. (a) Solution: (b) Solution: (c) Solution: <	· Product identifier	
Article number: 17614 Details of the supplier of the safety data sheet ManufacturerSupplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77336 USM Wood Social	Trade name: Isopropanol-Water	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Agua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemirez: 800-242-9300 Canue: Chemirez: 613-996-6666 Harad (f) Identification Classification of the substance or mixture Wistors of the substance or mixture Wistor of the substance or mixture Wistor of the substance or mixture Wistor of the substance or mixture Mamouble Liquids 2 H225 Highly flammable liquid and vapor. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or diztness. Label elements Chysic of Glasoff Chysic of Glasoff Signal word Danger Hazard determing components of labeling: Isopropanol Hazard statements Highly flamwable liquid and vapor. Cause drowsiness or dizaliness. Precuational statements Highly flamwable liquid and vapor. Cause serious eye irritation. Signal word Danger Hazard statements Hazard statements Hazard statements Hazard statements Highly flammable liquid and vapor. Cause way from heat/spark/sopen flames/hot surfaces. - No smoking. Ground/boad condinier and receiving equipment.		
Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77336 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemrer: 800-424-3930 Canute:: 613-996-6666 Information of the substance or mixture Web Constitution of the substance or mixture Maxard(s) Identification Classification of the substance or mixture Market State Stat		
Aqua Solutions, fr.c. 6913 Highway 225 DERP PARK, TX 77336 USA USA 800-255-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Technical Coordinator Shermann@aquasolutions.org Shermann Velson shermann@aquasolutions.org Emergency telephone number: Connect: 613-996-6666 USA Gamtes: Official Coordinator Gamtes: Official Condinator Gamtes: Official Condinator Gamtes: Flammable Liquids 2 H225 Highly flammable liquid and vapor. Operations GHS07 Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Laad elements The product is classified and labeled according to the Globally Harmonized System (GHS). Haard Jotograms GHS02 GHS02 GHS07 Signal word Danger Haard statements Haard determining components of labeling: Foropanol Haard statements Habel statemas Highly flammable liqui		
DEER PARK, TX 77536 USA 800-256-2586 Information department: Technical Coordinator Sherman Néslon shermann@aquasolutions.org Emergency telephone number: Chemire: 800-256-2586 Information department: Chemire: 800-256-2586 Information department: Chemire: 800-256-2586 Information department: Chemire: 800-256-2586 Information department: Chemire: 800-256-2586 Information department: Flazard(s) identification Classification of the substance or mixture Information of th	Aqua Solutions, Inc.	
USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemitrec: 800-424-9300 Canutec: 613-996-6666 <i>Hazard(s) identification</i> Classification of the substance or mixture		SOLUTIONS
Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemitree: 800-424-9300 Canuez: 613-996-6666 Ilazard(s) identification Classification of the substance or mixture is a substance or mixture or mixture is a substance or mixture o		
Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency: telephone number: Chemtree: 800-424-9300 Canuee: 613-996-6666 Hazard(s) identification Classification of the substance or mixture	800-256-2586	
Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemre:: 800-424-9300 Canutec: 613-996-6666	Information department:	
Emergency telephone number: Chemtres: $800-424+9300$ Canutes: $613-996-6666$ Hazard(s) identification Classification of the substance or mixture \widehat{OO} GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. \widehat{OO} GHS07 Eye Irritation 2.A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements Hazard pictograms \widehat{OO} $\widehat{OHS07}$ Flama big telements Ho product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms \widehat{OO} $\widehat{OHS07}$ Signal word Danger Hazard-determining components of labeling: Isopropanol Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precutionary statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsines or dizziness. Precuti		
Canutee: 613-996-6666	· Emergency telephone number:	
Hazard(s) identification Classification of the substance or mixture Image: Classification or molecular or the substance or mixture Image: Classification or mixture <td></td> <td></td>		
Classification of the substance or mixture		
Classification of the substance or mixture	Hazard(s) identification	
Finamable Liquids 2 H225 Highly flammable liquid and vapor. Finamable Liquids 2 H225 Highly flammable liquid and vapor. Finamable Liquids 2 H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS07 Signal word Danger Hzard statements Hazard tetermining components of labeling: Sopropanol Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Kerg away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. No smoking.		
Flammable Liquids 2H225 Highly flammable liquid and vapor. \widehat{V} <t< td=""><td>Classification of the substance or mixture</td><td></td></t<>	Classification of the substance or mixture	
$\overrightarrow{v}_{v} constraints} constraints for the formula of the formula$	GHS02 Flame	
Eye Irritation $2A$ H319 Causes serious eye irritation.Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.Label elementsGHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).Hazard pictograms $\overbrace{OHS02}^{*}$ $\overbrace{OHS02}^{*}$ $\overbrace{OHS07}^{*}$ Signal word DangerHazard-determining components of labeling: IsopropanolHazard statementsHayon. Causes serious eye irritation. May cause drowsiness or dizziness.Precutionary statementsKarard surfaces No smoking. Ground/bond container and receiving equipment.	∇	
Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Image: Constraint of the product of the Globally Harmonized System (GHS) Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.		flammable liquid and vapor.
Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms $\overbrace{OGHS02}^{\circ}$ $\overbrace{OHS07}^{\circ}$ Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.		flammable liquid and vapor.
GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms	GHS07	
 Hazard pictograms With the second second	<i>Eye Irritation 2A</i> H319 Causes	serious eye irritation.
 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. 	<i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> <i>H319 Causes</i> <i>H336 May ca</i> <i>Label elements</i>	serious eye irritation. use drowsiness or dizziness.
 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. 	<i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> H336 May ca <i>Label elements</i> <i>GHS label elements</i> The product is classified and labeled accordi	serious eye irritation. use drowsiness or dizziness.
 Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. 	<i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> H336 May ca <i>Label elements</i> <i>GHS label elements</i> The product is classified and labeled accordi	serious eye irritation. use drowsiness or dizziness.
Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	<i>Eye Irritation 2A</i> <i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> <i>H336 May ca</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled accordi</i> <i>Hazard pictograms</i> <i>Given the product of the product is classified and labeled accordi</i> <i>Hazard pictograms</i>	serious eye irritation. use drowsiness or dizziness.
 Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	<i>Eye Irritation 2A</i> <i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3 H336 May ca</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled accordi</i> <i>Hazard pictograms</i> <i>GHS02 GHS07</i>	serious eye irritation. use drowsiness or dizziness.
Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	<i>Eye Irritation 2A</i> <i>Eye Irritation 2A</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> <i>H319 Causes</i> <i>Specific Target Organ Toxicity - Single Exposure 3</i> <i>H336 May ca</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled accordi</i> <i>Hazard pictograms</i> <i>GHS02</i> <i>GHS02</i> <i>GHS07</i> <i>Signal word Danger</i> <i>Hazard-determining components of labeling:</i>	serious eye irritation. use drowsiness or dizziness.
Causes serious eye irritation. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	Eye Irritation 2A Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H336 May ca Label elements GHS label elements The product is classified and labeled accordi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol	serious eye irritation. use drowsiness or dizziness.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	Eye Irritation 2A Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H336 May ca Label elements GHS label elements The product is classified and labeled accordi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements	serious eye irritation. use drowsiness or dizziness.
Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment.	Eye Irritation 2A Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H336 May ca Label elements GHS label elements The product is classified and labeled accordi Hazard pictograms $\overrightarrow{OHS02}$ $\overrightarrow{OHS07}$ Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation.	serious eye irritation. use drowsiness or dizziness.
	Eye Irritation 2A H319 Causes Specific Target Organ Toxicity - Single Exposure 3 H336 May ca Label elements GHS label elements The product is classified and labeled accordi Hazard pictograms i Hazard pictograms i Hazard pictograms i Hazard biologicGHS02 GHS07 Signal word Danger i Hazard-determining components of labeling:IsopropanolHazard statementsHighly flammable liquid and vapor.Causes serious eye irritation.May cause drowsiness or dizziness.	serious eye irritation. use drowsiness or dizziness.
	Eye Irritation $2A$ H319 CausesSpecific Target Organ Toxicity - Single Exposure 3H336 May caLabel elementsGHS label elements The product is classified and labeled accordiHazard pictograms $\overbrace{GHS02}$ $\overbrace{GHS02}$ $\overbrace{GHS07}$ Signal word DangerHazard-determining components of labeling: IsopropanolHazard statementsHighly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoki.	serious eye irritation. use drowsiness or dizziness. ing to the Globally Harmonized System (GHS).

Printing date 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution Reviewed on 05/14/2024

(Contd. of page 1) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) *Health* = 2Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2FIRE 3 Fire = 3**REACTIVITY O** Reactivity = 0• Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components: CAS: 67-63-0 Isopropanol 87.601% • Table of Nonhazardous Ingredients

12.399%

4 First-aid measures

CAS: 7732-18-5 Water

- Description of first aid measures
- *General information: Immediately remove any clothing soiled by the product.*
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3)

US

Printing date 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution Reviewed on 05/14/2024

• After eye contact:

(Contd. of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • *After swallowing:* If symptoms persist consult doctor.

· Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.	
• Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
· PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppm
· PAC-3:	
CAS: 67-63-0 Isopropanol	12000** ppm
	·

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

(Contd. on page 4)

Printing date 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

(Contd. of page 3)

Reviewed on 05/14/2024

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 67-63-0 Isopropanol

- PEL Long-term value: 980 mg/m³, 400 ppm
- REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
- TLV Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

· Ingredients with biological limit values:

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

(Contd. of page 4)

US

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and of the second backward by the second backward by the second backward backward backward backward by the second by the	chemical properties
General Information Appearance: Form: Color: Odor:	Liquid Clear de l'alcool
Odor threshold:	l Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 82 °C (179.6 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower: Upper:	2 Vol % 12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F): Relative density	0.81166 g/cm³ (6.7733 lbs/gal) Not determined.

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

		(Contd. of page
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octan	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	87.6 %	
Water:	12.4 %	
VOC content:	87.60 %	
	711.0 g/l / 5.93 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

3

⁰⁵

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1219	
UN proper shipping name		
DOT, IMDG, IATA	Isopropanol solution	
Transport hazard class(es)		
DOT		
-		
PLAMMABLE LOUD		
FLAMMABLE LIQUD		
V		
Class	3 Flammable liquids	

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
Stowage Category	В
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2 .	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1219 ISOPROPANOL SOLUTION, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available

1
i

· Sara	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
CAS: 67-63-0 Isopropanol	
· TSCA (Toxic Substances Control Act):	
Isopropanol	ACTIVE
Water	ACTIVI
· Hazardous Air Pollutants	
None of the ingredients is listed.	
	(Contd. on page

US

Printing date 05/14/2024

· Proposition 65

Reviewed on 05/14/2024

Trade name: Isopropanol-Water

90:10 v/v Solution

(Contd. of page 8)

A4

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

CAS: 67-63-0 Isopropanol

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Isopropanol · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/sprav Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 10)

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Isopropanol-Water 90:10 v/v Solution

(Contd. of page 9)

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: • Date of preparation / last revision Revision 1.2, 04-15-2024: Reviewed SDS For accuracy. GW/STN Creation date for SDS 08-18-2016. STN 05/14/2024 • Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.