

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

1 Identification

- **Product identifier**
- **Trade name:** Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl
- **Article number:** HOE043
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS03 Flame over circle

Ox. Liq. 2 H272 May intensify fire; oxidizer.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS03



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Nitric Acid
Aluminum Nitrate

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 1)

- **Hazard statements**

May intensify fire; oxidizer.
Harmful if swallowed.
Causes severe skin burns and eye damage.

- **Precautionary statements**

Keep away from heat.
Keep/Store away from clothing/combustible materials.
Take any precaution to avoid mixing with combustibles.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 3
Reactivity = 0

The substance possesses oxidizing properties.

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|----------------|-------------|---------|
| CAS: 7697-37-2 | Nitric Acid | 5.1004% |
|----------------|-------------|---------|

- **Table of Nonhazardous Ingredients**

| | | |
|----------------|------------------|--------|
| CAS: 7784-27-2 | Aluminum Nitrate | 0.409% |
|----------------|------------------|--------|

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 2)

| | | |
|-----------------|--|---------|
| CAS: 7782-61-8 | Ferric Nitrate | 0.0709% |
| CAS: 7647-01-0 | Hydrochloric Acid | 0.0564% |
| CAS: 7789-02-8 | Chromium Nitrate Nonahydrate | 0.0076% |
| CAS: 10196-18-6 | Zinc Nitrate, Reagent Grade | 0.0045% |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 0.0037% |
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | 0.001% |
| CAS: 7446-08-4 | selenium dioxide | 0.0007% |
| CAS: 7732-18-5 | Water | 94.346% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-----------------|--|------------------------|
| CAS: 7697-37-2 | Nitric Acid | 0.16 ppm |
| CAS: 7784-27-2 | Aluminum Nitrate | 83 mg/m ³ |
| CAS: 7782-61-8 | Ferric Nitrate | 22 mg/m ³ |
| CAS: 7647-01-0 | Hydrochloric Acid | 1.8 ppm |
| CAS: 10196-18-6 | Zinc Nitrate, Reagent Grade | 27 mg/m ³ |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 42 mg/m ³ |
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | 1.5 mg/m ³ |
| CAS: 7446-08-4 | selenium dioxide | 0.84 mg/m ³ |

· **PAC-2:**

| | | |
|-----------------|--|-----------------------|
| CAS: 7697-37-2 | Nitric Acid | 24 ppm |
| CAS: 7784-27-2 | Aluminum Nitrate | 920 mg/m ³ |
| CAS: 7782-61-8 | Ferric Nitrate | 110 mg/m ³ |
| CAS: 7647-01-0 | Hydrochloric Acid | 22 ppm |
| CAS: 10196-18-6 | Zinc Nitrate, Reagent Grade | 300 mg/m ³ |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 150 mg/m ³ |
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | 53 mg/m ³ |
| CAS: 7446-08-4 | selenium dioxide | 1.6 mg/m ³ |

· **PAC-3:**

| | | |
|-----------------|--|-------------------------|
| CAS: 7697-37-2 | Nitric Acid | 92 ppm |
| CAS: 7784-27-2 | Aluminum Nitrate | 5,500 mg/m ³ |
| CAS: 7782-61-8 | Ferric Nitrate | 640 mg/m ³ |
| CAS: 7647-01-0 | Hydrochloric Acid | 100 ppm |
| CAS: 10196-18-6 | Zinc Nitrate, Reagent Grade | 1,800 mg/m ³ |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 240 mg/m ³ |
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | 320 mg/m ³ |
| CAS: 7446-08-4 | selenium dioxide | 9.5 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 4)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 7697-37-2 Nitric Acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 5)

9 Physical and chemical properties

| | |
|---|---|
| · Information on basic physical and chemical properties | |
| · General Information | |
| · Appearance: | |
| Form: | Liquid |
| Color: | Clear |
| · Odor: | Odorless |
| · Odor threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 83 °C (181.4 °F) |
| · Flash point: | Not applicable. |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17.3 mm Hg) |
| · Density at 20 °C (68 °F): | 1.01961 g/cm ³ (8.50865 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): Not determined. | |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Water: | 94.3 % |
| VOC content: | 0.00 % |
| | 0.0 g/l / 0.00 lb/gl |
| Solids content: | 0.5 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 6)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|-----------------|--|---|
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | 1 |
| CAS: 7446-08-4 | selenium dioxide | 3 |

- **NTP (National Toxicology Program)**

| | | |
|-----------------|--|---|
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal | K |
|-----------------|--|---|

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**



(Contd. of page 7)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

| | |
|---------------------------------------|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN3264 |
| · UN proper shipping name | |
| · DOT | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) |
| · IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| | |
| · IMDG, IATA | |
| |  |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| · Packing group | |
| · DOT, IMDG, IATA | II |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Corrosive substances |
| · Danger code (Kemler): | 80 |
| · EMS Number: | F-A,S-B |
| · Segregation groups | Acids |
| · Stowage Category | B |
| · Stowage Code | SW2 Clear of living quarters. |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 8)

- | | |
|--|---|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

| | |
|----------------|-------------|
| CAS: 7697-37-2 | Nitric Acid |
|----------------|-------------|

· Section 313 (Specific toxic chemical listings):

| | |
|-----------------|--|
| CAS: 7697-37-2 | Nitric Acid |
| CAS: 7784-27-2 | Aluminum Nitrate |
| CAS: 7782-61-8 | Ferric Nitrate |
| CAS: 7789-02-8 | Chromium Nitrate Nonahydrate |
| CAS: 10196-18-6 | Zinc Nitrate, Reagent Grade |
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal |
| CAS: 7446-08-4 | selenium dioxide |

· TSCA (Toxic Substances Control Act):

| |
|-------------------|
| Nitric Acid |
| Hydrochloric Acid |
| selenium dioxide |
| Water |

- TSCA new (21st Century Act) (Substances not listed)
- Proposition 65

· Chemicals known to cause cancer:

| | |
|-----------------|--|
| CAS: 13478-00-7 | Nickel Nitrate, Reagent Grade, Crystal |
|-----------------|--|

· Chemicals known to cause reproductive toxicity for females:

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

· Chemicals known to cause reproductive toxicity for males:

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 9)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 7446-08-4 | selenium dioxide

D

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS03

GHS05

GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Nitric Acid

Aluminum Nitrate

· **Hazard statements**

May intensify fire; oxidizer.

Harmful if swallowed.

Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep away from heat.

Keep/Store away from clothing/combustible materials.

Take any precaution to avoid mixing with combustibles.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Mixed Metals Spike Soln.
in 2% HNO₃ & 0.05% HCl**

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

11-21-2017: review SDS for accuracy. STN

Revision 0.0, 08-31-2016: Creation date for SDS. STN

11/21/2017 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1