Printing date 05/28/2024

Reviewed on 05/28/2024

Identification	
Product identifier	
Trade name: 20% Sodium Acetate	
Buffer Solution	
Article number: PPG176	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier: Aqua Solutions, Inc.	AUQA
6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536	
USA 800-256-2586	
Information department:	
Technical Coordinator	
Sherman Nelson shermann@aquasolutions.org	
<i>Emergency telephone number:</i> <i>Chemtrec: 800-424-9300</i>	
Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02 Flame	
Flammable Liquids 3 H226 Flammable liquid and vapor.	
тапалана Елупав 5-11220 ганинана идиа ана тарот.	
GHS05 Corrosion	
GHS05 Corrosion	1ge.
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama	ıge.
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama	ıge.
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. GHS07	ıge.
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. GHS07 Sensitization - Skin 1 H317 May cause an allergic skin reaction.	ıge.
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. GHS07 Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according	· · · · · · · · · · · · · · · · · · ·
GHS05 Corrosion Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. GHS07 Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according Hazard pictograms Sensitization - Skin 1	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Image 1 H318 Causes serious eye damage. Image 1 H317 May cause an allergic skin reaction. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Image 1 H317 May cause an allergic skin reaction. Image 2 Image 1 Image 3 Image 2 Image 4 Image 2 Image 5 Image 2 Image 6 Image 2 Image 7 Image 2	· · · · · · · · · · · · · · · · · · ·
Skin CorrosionSkin Corrosion 1AH314 Causes severe skin burns and eye damaEye Damage 1H318 Causes serious eye damage. $$ \overbrace	· · · · · · · · · · · · · · · · · · ·
Skin Corrosion 1A H314 Causes severe skin burns and eye dama Eye Damage 1 H318 Causes serious eye damage. Image 1 H317 May cause an allergic skin reaction. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Image 2 Image 1 Image 3 Image 2 Image 4 Image 2 Image 5 Image 2 Image 6 Image 2 Image 7 Image 2 Image 7 Image 2 Image 7 Image 2 Image 7 Image 2 Image 8 Image 2 Image 7	· · · · · · · · · · · · · · · · · · ·

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

	(Contd. of page 1)
Causes severe skin burns and eye damage.	
May cause an allergic skin reaction.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dusts or mists.	
Wash thoroughly after handling.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Rinse mouth. Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa	iter/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	:C
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,	, if present and easy to ao.
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention.	
Wash contaminated clothing before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international	l regulations
· Classification system:	regulations.
· NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 2	
3 0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
· IIMIS-raings (scale 0 - 4)	
$\frac{\text{HEALTH}}{3} Health = 3$	
FIRE 2 $Fire = 2$	
REACTIVITY Reactivity = 0	
· Other hazards	
• Results of PBT and vPvB assessment	
• PBT: Not applicable.	
· vPvB: Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 64-19-7 Acetic Acid, Glacial	23.035%
	201000 //

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

52.174% (Contd. on page 3)

US -

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

CAS: 6131-90-4 Sodium Acetate Trihydrate

(Contd. of page 2) 24.792%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

	tions, protective equipment and emergency procedures	
	ry protective device.	
Wear protective	equipment. Keep unprotected persons away.	
· Environmental J	precautions:	
Dilute with plent	y of water.	
Do not allow to	enter sewers/ surface or ground water.	
• Methods and mo	terial for containment and cleaning up:	
Absorb with liqu	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing	agent.	
Dispose contami	nated material as waste according to section 13.	
Ensure adequate	ventilation.	
Reference to oth	er sections	
See Section 7 for	information on safe handling.	
See Section 8 for	information on personal protection equipment.	
See Section 13 fo	or disposal information.	
· Protective Action	n Criteria for Chemicals	
• PAC-1:		
CAS: 6131-90-4	Sodium Acetate Trihydrate	11 mg/m ³
CAS: 64-19-7	Acetic Acid, Glacial	5 ppm
		(Contd. on page 4

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

· PAC-2:	(Contd. of page 3)
CAS: 6131-90-4 Sodium Acetate Trihydrate	120 mg/m ³
CAS: 64-19-7 Acetic Acid, Glacial	35 ppm
· PAC-3:	
CAS: 6131-90-4 Sodium Acetate Trihydrate	690 mg/m ³
CAS: 64-19-7 Acetic Acid, Glacial	250 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 64-19-7 Acetic Acid, Glacial

- PEL Long-term value: 25 mg/m³, 10 ppm
- REL Short-term value: 37 mg/m³, 15 ppm

Long-term value: 25 mg/m³, 10 ppm

TLV Short-term value: 15 ppm Long-term value: 10 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

⁻ US

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Vinegar
Odor threshold:	Not determined.
<i>pH-value at 20 °C (68 °F):</i>	<2
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	40 °C (104 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	485 °C (905 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

		(Contd. of page 5
Upper:	17 Vol %	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.09713 g/cm ³ (9.15555 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	23.0 %	
Water:	52.2 %	
VOC content:	23.03 %	
	252.7 g/l / 2.11 lb/gal	
Solids content:	24.8 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 4,602 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

Printing date 05/28/2024

Reviewed on 05/28/2024

(Contd. of page 6)

Trade name: 20% Sodium Acetate Buffer Solution

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number		
· DOT, IMDG, IATA	UN3265	

Printing date 05/28/2024

Reviewed on 05/28/2024

Buffer Solution	
	(Contd. of pag
UN proper shipping name DOT	Corrosive liquid, acidic, organic, n.o.s. (Acetic Acid, Glacial
· IMDG, IATA) CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Acetic Ac Glacial)
• Transport hazard class(es)	
DOT	
CORROSVE	
8	
· Class	8 Corrosive substances
· Label	8
· IMDG, IATA	
- Class - Label	8 Corrosive substances 8
Packing group	
DOT, IMDG, IATA	111
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler c	
• EMS Number: • Segregation groups	F-A,S-B (SGG1) Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II	Lof
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

(Contd. of page 8)

ACTIVE

ACTIVE

· UN "Model Regulation":

UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (ACETIC ACID, GLACIAL), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

Water

Acetic Acid, Glacial

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 10)

⁻ US

(Contd. of maga 0)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/28/2024

Reviewed on 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution

(Con	d. of page 9)
Hazard-determining components of labeling:	
Acetic Acid, Glacial	
Hazard statements	
Flammable liquid and vapor.	
Causes severe skin burns and eye damage.	
May cause an allergic skin reaction.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dusts or mists.	
Wash thoroughly after handling.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Rinse mouth. Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and e	asy to do.
Continue rinsing.	-
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
If skin irritation or rash occurs: Get medical advice/attention.	
Wash contaminated clothing before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision:

• Date of preparation / last revision Revision 1.2, 05/28/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 08-30-2016, Creation date for SDS. STN 05/28/2024

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Printing date 05/28/2024

Trade name: 20% Sodium Acetate Buffer Solution Reviewed on 05/28/2024

(Contd. of page 10)

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Eye Damage 1: Serious eye damage/eye irritation – Category 1 Sensitization - Skin 1: Skin sensitisation – Category 1 • * Data compared to the previous version altered.