Printing date 05/31/2024

Reviewed on 05/31/2024

# **1** Identification · Product identifier · Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol • Article number: SPX450 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 **2** Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labeling: Isopropanol · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. (Contd. on page 2) US

Printing date 05/31/2024

Reviewed on 05/31/2024

#### Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

	(Contd. of page 1)
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/sho	wer.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-	sent and easy to do.
Continue rinsing.	
Call a poison center/doctor if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regula	itions.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
$\begin{array}{c} 4 \\ 2 \\ 2 \\ 0 \end{array}$ $\begin{array}{c} Health = 2 \\ Fire = 3 \\ Reactivity = 0 \end{array}$	
· HMIS-ratings (scale 0 - 4)	
HEALTH2FIRE3Fire = 3REACTIVITY $\overline{0}$ Reactivity = 0	
· Other hazards	
• Results of PBT and vPvB assessment	
• <b>PBT</b> : Not applicable.	
• <b>vPvB:</b> Not applicable.	
3 Composition/information on ingredients	
• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
	00.1569

 CAS: 67-63-0
 Isopropanol
 98.156%

 CAS: 111-31-9
 Hexanethiol 96%
 1.844%

# 4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3)

US

Printing date 05/31/2024

Reviewed on 05/31/2024

#### Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

(Contd. of page 2)

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

· Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### **6** Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
CAS: 111-31-9 Hexanethiol 96%	0.045 ppm
· PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppm
CAS: 111-31-9 Hexanethiol 96%	0.5 ppm
· PAC-3:	
CAS: 67-63-0 Isopropanol	12000** ppm
CAS: 111-31-9 Hexanethiol 96%	48 ppm

## 7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

US

Printing date 05/31/2024

Reviewed on 05/31/2024

#### Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

(Contd. of page 3)

Prevent formation of aerosols. • Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 $\cdot$  Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

#### · Control parameters

· Con	ponents with limit values that require monitoring at the workplace:
CAS	S: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	. Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	<sup>7</sup> Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
CAS	5: 111-31-9 Hexanethiol 96%
REL	. Ceiling limit value: 2.7* mg/m³, 0.5* ppm *15-min
· Ingr	redients with biological limit values:
CAS	5: 67-63-0 Isopropanol
BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)
· Add	itional information: The lists that were valid during the creation were used as basis.
<ul> <li>Pers</li> <li>Gen</li> <li>Keep</li> <li>Imm</li> <li>Was</li> <li>Avoit</li> <li>Avoit</li> <li>Brea</li> <li>In co</li> </ul>	osure controls sonal protective equipment: eral protective and hygienic measures: p away from foodstuffs, beverages and feed. mediately remove all soiled and contaminated clothing. wh hands before breaks and at the end of work. id contact with the eyes. id contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use piratory protective device that is independent of circulating air.
	(Contd. on page 5)

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Like rotten eggs (mercaptans)
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	-89.5 °C (-129.1 °F) 82 °C (179.6 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower:	2 Vol %

Printing date 05/31/2024

Reviewed on 05/31/2024

### Trade name: Mercaptan Standard

5,000 ppm w/w in Isopropanol

		(Contd. of page 5
Upper:	12 Vol %	
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)	
• Density at 20 °C (68 °F):	0.78598 g/cm³ (6.559 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
$\cdot$ Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	<b>r):</b> Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	98.2 %	
VOC content:	98.16 %	
	771.5 g/l / 6.44 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

### **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

 Oral
 LD50
 68,012 mg/kg (rat)

 Inhalative
 LC50/4h
 58,575 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: Mercaptan Standard

5,000 ppm w/w in Isopropanol

(Contd. of page 6)

3

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## <u>12 Ecological information</u>

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

• General notes:

- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- *PBT*: Not applicable.
- **vPvB**: Not applicable.
- Other adverse effects No further relevant information available.

# **13 Disposal considerations**

· Waste treatment methods

- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number		
· DOT, IMDG, IATA	UN1993	
· UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Isopropanol	
	)	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Isopropanol	
·	)	

Printing date 05/31/2024

Reviewed on 05/31/2024

### Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

	(Contd. of pa
Transport hazard class(es)	
DOT	
RAMMABLE LOUD	
3	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	
LMS Number: Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	
Excepted quantities $(EQ)$	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 50 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL
	), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US

Printing date 05/31/2024

Reviewed on 05/31/2024

Trade name: Mercaptan Standard

5,000 ppm w/w in Isopropanol

CAS: 67-63-0 Isopropanol	
TSCA (Toxic Substances Control Act):	
Isopropanol	ACTIV
Hexanethiol 96%	ACTIV
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 67-63-0 Isopropanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: Isopropanol
Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

A4

Printing date 05/31/2024

Reviewed on 05/31/2024

#### Trade name: Mercaptan Standard 5,000 ppm w/w in Isopropanol

(Contd. of page 9)

Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

Date of preparation / last revision Revision 1.2, 05/31/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 04-05-2022: Creation date for SDS. STN 05/31/2024
Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

• \* Data compared to the previous version altered.

US -