*Printing date 06/17/2024* 

Reviewed on 06/17/2024

# **1** Identification · Product identifier · Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664) • Article number: 6545 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. GHS06 Skull and crossbones Acute Toxicity - Inhalation 3 H331 Toxic if inhaled. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child. Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure. GHS07 Acute Toxicity - Oral 4 H302 Harmful if swallowed. Skin Irritation 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

– ÚS

Printing date 06/17/2024

Reviewed on 06/17/2024


Trade name:	Total Acid Number Solvent
	Modified with Chloroform (ASTM D664)




\_\_\_\_US

Printing date 06/17/2024

Reviewed on 06/17/2024



(Contd. of page 2)



#### · Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous con	nponents:	
CAS: 67-66-3	Chloroform	65.279%
CAS: 67-63-0	Isopropanol	34.28%
• Table of Nonh	azardous Ingredients	
CAS: 7732-18-	5 Water	0.441%

### 4 First-aid measures

#### · Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

(Contd. of page 3)

#### **5** Fire-fighting measures

- · Extinguishing media
- $\cdot$  Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
   Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

CAS: 67-66-3 Chloroform	2 ppm
CAS: 67-63-0 Isopropanol	400 ppm
· PAC-2:	
CAS: 67-66-3 Chloroform	64 ppm
CAS: 67-63-0 Isopropanol	2000* ppm
· PAC-3:	
CAS: 67-66-3 Chloroform	3,200 ppm
CAS: 67-63-0 Isopropanol	12000** ppm

### 7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

(Contd. on page 5)

US

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- *Specific end use(s)* No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

C	not parameters
	ponents with limit values that require monitoring at the workplace:
	: 67-66-3 Chloroform
PEL	Ceiling limit value: 240 mg/m <sup>3</sup> , 50 ppm
REL	Short-term value: 9.78* mg/m³, 2* ppm
	*60-min; See Pocket Guide App. A
TLV	Long-term value: 10 ppm
	<i>A3</i>
CAS	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 400 ppm
	Long-term value: 200 ppm
	BEI, A4
· Ingr	edients with biological limit values:
CAS	: 67-63-0 Isopropanol
BEI	40 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift at end of workweek
	LD50: Acetone (background, nonspecific)
· Addi	itional information: The lists that were valid during the creation were used as basis.
·Expe	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	p away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately. Id contact with the eyes and skin.
	thing equipment:
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use
	iratory protective device that is independent of circulating air.
	(Contd. on page 6)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

(Contd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties		
· Information on basic physical and	chemical properties	
· General Information		
· Appearance:		
Form:	Liquid	
Color:	Clear	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
<b>Boiling point/Boiling range:</b>	61 °C (141.8 °F)	
· Flash point:	13 °C (55.4 °F)	
· Flammability (solid, gaseous):	Highly flammable.	
· Auto igniting:	425 °C (797 °F)	
• Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits: Lower:	2 Vol %	
	(Contd. on page 7	

US

Printing date 06/17/2024

Reviewed on 06/17/2024

### Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

		(Contd. of page
Upper:	12 Vol %	
· Vapor pressure at 20 °C (68 °F):	210 hPa (157.5 mm Hg)	
Density at 20 °C (68 °F):	1.23956 g/cm³ (10.34413 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	e <b>r):</b> Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	34.3 %	
Water:	0.4~%	
VOC content:	34.28 %	
	424.9 g/l / 3.55 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

# **10 Stability and reactivity**

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Oral LD50 766 mg/kg

- Inhalative LC50/4h 4.6 mg/l
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot$  Additional toxicological information:

*The product shows the following dangers according to internally approved calculation methods for preparations: Toxic* 

(Contd. on page 8)

US

Printing date 06/17/2024

Reviewed on 06/17/2024

(Contd. of page 7)

2B

3

R

### Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

Harmful

Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-66-3 Chloroform

CAS: 67-63-0 Isopropanol

· NTP (National Toxicology Program)

CAS: 67-66-3 Chloroform

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- $\cdot$  Other adverse effects No further relevant information available.

# **13 Disposal considerations**

- Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN1992	
· UN proper shipping name		
$\cdot DOT$	Flammable liquids, toxic, n.o.s. (Isopropanol	
201	, Chloroform)	

Printing date 06/17/2024

Reviewed on 06/17/2024

## Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

IMDG, IATA	FLAMMABLE LIQUID, TOXIC, N.O.S. (Isopropanol , Chloroform)
· Transport hazard class(es)	
• DOT	
RAMARE LODO	
· Class	3 Flammable liquids
· Label	3, 6.1
· IMDG	
· Class	3 Flammable liquids
· Label	3/6.1
·IATA	
· Class · Label	3 Flammable liquids 3 (6.1)
· Packing group · DOT, IMDG, IATA	Ш
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler co	
EMS Number:	F-E,S-D
· Stowage Category	
· Stowage Code	SW2 Clear of living quarters.
• Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.
Transport/Additional information:	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
	On cargo aneraji oniy. 00 L
·IMDG	
$\cdot$ Limited quantities (LQ)	IL Charles II
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

(Contd. of page 9)

ACTIVE

ACTIVE

ACTIVE

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

· UN "Model Regulation":

UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (ISOPROPANOL , CHLOROFORM), 3 (6.1), II

### **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

CAS: 67-66-3 Chloroform

· Section 313 (Specific toxic chemical listings):

CAS: 67-66-3 Chloroform CAS: 67-63-0 Isopropanol

• TSCA (Toxic Substances Control Act):

Chloroform

Isopropanol

Water
• Hazardous Air Pollutants

CAS: 67-66-3 Chloroform

CAS: 07-00-5 Chiore

· Proposition 65

· Chemicals known to cause cancer:

CAS: 67-66-3 Chloroform

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-66-3 Chloroform

· Carcinogenic categories

· EPA (Environmental Protection Agency) CAS: 67-66-3 Chloroform

· TLV (Threshold Limit Value)

CAS: 67-66-3 Chloroform

CAS: 67-63-0 Isopropanol

 $\cdot$  NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 67-66-3 Chloroform

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 11)

B2, L, NL


A3 A4

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2024

Reviewed on 06/17/2024



(Contd. of page 10) · Hazard pictograms GHS02 GHS06 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: Chloroform Isopropanol · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 12)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Total Acid Number Solvent Modified with Chloroform (ASTM D664)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 11)

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Department issuing SDS: Environment protection department.
 Contact: Date of Preparation / Last Revision:
 Date of preparation / last revision Revision 0.1, 06/17/2024: Reviewed SDS for accuracy. MH/STN 06/17/2024 / 1.0
 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 4: Acute toxicity – Category 4 Acute Toxicity - Inhalation 3: Acute toxicity - Category 3 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1  $\cdot$  \* Data compared to the previous version altered.

US ·