

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

1 Identification

- **Product identifier**
- **Trade name:** Lithium Metal Wire (In Mineral Oil)
- **Article number:** L5100
- **CAS Number:**
7439-93-2
- **EC number:**
231-102-5
- **Index number:**
003-001-00-4
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Substances and mixtures which, in contact with water, emit flammable gases 1

H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS05 Corrosion

Skin Corrosion 1B

H314 Causes severe skin burns and eye damage.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS05

- **Signal word** *Danger*
- **Hazard statements**
In contact with water releases flammable gases, which may ignite spontaneously.
Causes severe skin burns and eye damage.
- **Precautionary statements**
Do not allow contact with water.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 1)

Handle under inert gas. Protect from moisture.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, sand, extinguishing powder to extinguish.

Store in a dry place. Store in a closed container.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 2

The substance demonstrates unusual reactivity with water.

· **HMIS-ratings (scale 0 - 4)**



HEALTH 3 Health = 3

FIRE 0 Fire = 0

REACTIVITY 2 Reactivity = 2

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

CAS: 7439-93-2 lithium

· **Identification number(s)**

· **EC number:** 231-102-5

· **Index number:** 003-001-00-4

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 2)

- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
- **PAC-1:** 3.3 mg/m³
- **PAC-2:** 36 mg/m³
- **PAC-3:** 220 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Thorough dedusting.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:** Not required.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Solid
Color:	White
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not applicable.

- **Change in condition**

Melting point/Melting range:	180.54 °C (357 °F)
-------------------------------------	--------------------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: *Lithium Metal Wire (In Mineral Oil)*

(Contd. of page 4)

Boiling point/Boiling range:	1,347 °C (34.447 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Contact with water liberates extremely flammable gases.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Not determined.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	0 hPa
· Density at 20 °C (68 °F):	0.534 g/cm ³ (4.45623 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)** Substance is not listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 5)

- **NTP (National Toxicology Program)** Substance is not listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
*Water hazard class 1 (Assessment by list): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| UN-Number | |
| DOT, IMDG, IATA | UN1415 |
| UN proper shipping name | |
| DOT | Lithium |
| IMDG, IATA | LITHIUM |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 4.3 Substances which, in contact with water, emit flammable gases |

(Contd. on page 7)

US

Safety Data Sheet


acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: *Lithium Metal Wire (In Mineral Oil)*

(Contd. of page 6)

· Label	4.3
· IMDG, IATA	
	
· Class	4.3 Substances which, in contact with water, emit flammable gases
· Label	4.3
· Packing group	
· DOT, IMDG, IATA	I
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Substances which, in contact with water, emit flammable gases
· Hazard identification number (Kemler code):	X423
· EMS Number:	F-G,S-N
· Stowage Category	E
· Handling Code	H1 Keep as dry as reasonably practicable
· Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: 15 kg
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1415 LITHIUM, 4.3, I

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is not listed.
- **Section 313 (Specific toxic chemical listings):** Substance is not listed.
- **TSCA (Toxic Substances Control Act):** ACTIVE
- **Hazardous Air Pollutants** Substance is not listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 7)

- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency)** Substance is not listed.
- **TLV (Threshold Limit Value)** Substance is not listed.
- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS05

- **Signal word** *Danger*
- **Hazard statements**
 - In contact with water releases flammable gases, which may ignite spontaneously.*
 - Causes severe skin burns and eye damage.*
- **Precautionary statements**
 - Do not allow contact with water.*
 - Handle under inert gas. Protect from moisture.*
 - Do not breathe dusts or mists.*
 - Wash thoroughly after handling.*
 - Wear protective gloves/protective clothing/eye protection/face protection.*
 - If swallowed: Rinse mouth. Do NOT induce vomiting.*
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 - Immediately call a poison center/doctor.*
 - Specific treatment (see on this label).*
 - Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.*
 - Wash contaminated clothing before reuse.*
 - In case of fire: Use CO2, sand, extinguishing powder to extinguish.*
 - Store in a dry place. Store in a closed container.*
 - Store locked up.*
 - Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
 - Date of Preparation / Last Revision:*
- **Date of preparation / last revision**
 - Revision 1.2, 05/15/2024: Reviewed SDS for accuracy. MH/STN*
 - Creation date for SDS 11-07-2014. STN*
 - 05/15/2024*
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods*
 - DOT: US Department of Transportation*
 - IATA: International Air Transport Association*

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 8)

*EINECS: European Inventory of Existing Commercial Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Substances and mixtures which, in contact with water, emit flammable gases 1: Substances and mixtures which in contact with water emit flammable gases – Category 1**Skin Corrosion 1B: Skin corrosion/irritation – Category 1B***· * Data compared to the previous version altered.**

US