Printing date 07/25/2024

Reviewed on 07/25/2024

1 Identification · Product identifier · Trade name: Ethylenediamine, Reagent Grade · Article number: E6890 · CAS Number: 107-15-3 • EC number: 203-468-6 · Index number: 612-006-00-6 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. GHS05 Corrosion H314 Causes severe skin burns and eye damage. Skin Corrosion 1B GHS07 Acute Toxicity - Oral 4 H302 Harmful if swallowed. Acute Toxicity - Dermal 4 H312 Harmful in contact with skin. Sensitization - Skin 1 H317 May cause an allergic skin reaction. · Label elements · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

(Contd. of page 1)

US



(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

CAS: 107-15-3 ethylenediamine

- · Identification number(s)
- EC number: 203-468-6
- Index number: 612-006-00-6

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

(Contd. of page 3)

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

• Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

- **PAC-1:** 0.88 ppm
- **PAC-2:** 9.7 ppm
- **PAC-3:** 20 ppm

7 Handling and storage

· Handling:

• Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

CAS: 107-15-3 ethylenediamine

PEL Long-term value: 25 mg/m³, 10 ppm

REL Long-term value: 25 mg/m³, 10 ppm

TLV Long-term value: 10 ppm Skin, A4

• *Additional information:* The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.


(Contd. on page 5)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

(Contd. of page 4)





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c General Information	hemical properties
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Ammonia-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	8.5 °C (47.3 °F)
Boiling point/Boiling range:	117 °C (242.6 °F)
Flash point:	34 °C (93.2 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	385 °C (725 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2.7 Vol %
Upper:	16.6 Vol %
Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

		(Contd. of page
Density at 20 °C (68 °F):	0.98 g/cm³ (8.1781 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.05 g/l	
Partition coefficient (n-octanol/w	uter): Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	1.54 mPas	
Kinematic:	Not determined.	
Other information	No further relevant information available.	

10 Stability and reactivity

· *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Oral LD50 500 mg/kg (ATE)

Dermal LD50 1,100 mg/kg (ATE)

· Primary irritant effect:

- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

• Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

(Contd. on page 7)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

(Contd. of page 6)

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	UN1604	
DOT, IMDG, IATA	0111004	
UN proper shipping name		
DOT	Ethylenediamine	
IMDG, IATA	ETHYLENEDIAMINE	
DOT		
Class	8 Corrosive substances	
Label	8, 3	

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

	(Contd. of pag
·IMDG	
· Class	8 Corrosive substances
· Label	8/3
·IATA	
• •	
· Class	8 Corrosive substances
·Label	8 (3)
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code):	
· EMS Number:	F-E,S-C
· Segregation groups	(SGG18) Alkalis
· Stowage Category	
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG35 Stow "separated from" SGG1-acids
• Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
· Hazardous substance:	5000 lbs, 2270 kg
·IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1604 ETHYLENEDIAMINE, 8 (3), II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

• Section 355 (extremely hazardous substances): Substance is listed.

• Section 313 (Specific toxic chemical listings): Substance is not listed.

• TSCA (Toxic Substances Control Act): ACTIVE

(Contd. on page 9)

[·]US

(Contd. of page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

· Hazardous Air Pollutants Substance is not listed.

· Proposition 65

· Chemicals known to cause cancer: Substance is not listed.

- Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) D
- TLV (Threshold Limit Value) A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- *GHS label elements* The substance is classified and labeled according to the Globally Harmonized System (GHS). *Hazard pictograms*



· Signal word Danger · Hazard statements Flammable liquid and vapor. Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. [In case of inadequate ventilation] wear respiratory protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

⁻ US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: Ethylenediamine, Reagent Grade

(Contd. of page 9)

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: • Date of preparation / last revision Revision 1.2, 07-25-2024: Reviewed SDS for accuracy. STN/GW Creation date for SDS 07-28-2016. STN 07/25/2024 / 1.1

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Oral 4: Acute toxicity – Category 4 Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Sensitization - Respiratory 1: Respiratory sensitisation - Category 1 Sensitization - Skin 1: Skin sensitisation - Category 1 • * Data compared to the previous version altered.