Printing date 05/16/2024

Reviewed on 05/16/2024

inting date 05/16/2024	Reviewed on 05/16/202
I Identification	
· Product identifier	
• Trade name: <u>Chloride Standard 1.0 ppm</u> w/v in p-Xylene	
• Article number: LY095	
<ul> <li>Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: Aqua Solutions, Inc.</li> <li>6913 Highway 225 DEER PARK, TX 77536 USA</li> </ul>	AQUA SOLUTIONS
800-256-2586	
<ul> <li>Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org</li> <li>Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666</li> </ul>	
P Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
Flammable Liquids 3 H226 Flammable liquid and vapor.	
$\overset{1}{\frown}$	
GHS07	
Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.	
Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.	
Skin Irritation 2 H315 Causes skin irritation.	
<ul> <li>Label elements</li> <li>GHS label elements The product is classified and labeled according to the Glob</li> <li>Hazard pictograms</li> </ul>	oally Harmonized System (GHS).
GHS02 GHS07	
· Signal word Warning	
· Hazard-determining components of labeling:	
p-Xylene • <b>Hazard statements</b> Flammable liquid and vapor. Harmful in contact with skin or if inhaled.	
p-Xylene • <b>Hazard statements</b> Flammable liquid and vapor.	

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

	(Contd. of page 1)
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Dispose of contents/container in accordance with local/regional/national/international regulation.	<i>s</i> .
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 1 Fire = 3 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH2FIRE3Fire = 3REACTIVITY0Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• <b>PBT:</b> Not applicable.	
• <b>vPvB:</b> Not applicable.	
3 Composition/information on ingredients	
• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 106-42-3 p-Xylene	100.0%
Сло. 100 12 5 р Луюнс	100.070

· Table of Nonhazardous Ingredients

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

# 4 First-aid measures

- Description of first aid measures General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

0.0002%

US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** *Fire-fighting measures*

· Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

•	PAC-1:

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	$2.5 mg/m^3$
• PAC-2:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	27 mg/m <sup>3</sup>
• PAC-3:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	160 mg/m <sup>3</sup>

## 7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Printing date 05/16/2024

Reviewed on 05/16/2024

#### Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

(Contd. of page 3)

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

## CAS: 106-42-3 p-Xylene

- PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm
- REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm
  - Long-term value: 435 mg/m<sup>3</sup>, 100 ppm
- *TLV Long-term value: 20 ppm BEI, OTO, A4*

## · Ingredients with biological limit values:

CAS: 106-42-3 p-Xylene

BEI 1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

US

Printing date 05/16/2024

Reviewed on 05/16/2024

#### Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and c</li> <li>General Information</li> </ul>	nemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Xylene
• Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	13.3 °C (55.9 °F)
<b>Boiling point/Boiling range:</b>	138 °C (280.4 °F)
· Flash point:	25 °C (77 °F)
· Flammability (solid, gaseous):	Flammable.
· Auto igniting:	525 °C (977 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.7 Vol %
Upper:	7.6 Vol %
· Vapor pressure at 20 °C (68 °F):	8.2 hPa (6.2 mm Hg)
· Density at 20 °C (68 °F):	0.85667 g/cm <sup>3</sup> (7.14891 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

		(Contd. of page
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.2 g/l	
· Partition coefficient (n-octanol/we	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	856.7 g/l / 7.15 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

# **10 Stability and reactivity**

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

## ATE (Acute Toxicity Estimate)

Dermal LD50 1,100 mg/kg

Inhalative LC50/4h 11 mg/l

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot$  Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

· Carcinogenic categories

· IARC (Interna	tional Agency for Research on Cancer)	
CAS: 106-42-3	p-Xylene	3
CAS: 88-06-2	2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	2B
	(Contd. on	page 7)

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

(Contd. of page 6)

R

· NTP (National Toxicology Program)

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packagings:

• *Recommendation: Disposal must be made according to official regulations.* 

UN-Number		
DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (p-Xylene)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (p-Xylene)	
Transport hazard class(es)		
DOT		
RAMMARE LOOP		
Class	3 Flammable liquids	

-ι

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

	(Contd. of pag
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code	
EMS Number: Stowage Category	F-E, <u>S-E</u> A
0 0 0	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
£	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (P-XYLENE), 3, III

# **15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):
- None of the ingredients is listed.
- · Section 313 (Specific toxic chemical listings):
- All ingredients are listed.
- · TSCA (Toxic Substances Control Act):
- p-Xylene
- 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal
- · Hazardous Air Pollutants
- All ingredients are listed.

(Contd. on page 9)

ACTIVE

ACTIVE

US

I В2

A4

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/16/2024

#### Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

	(Contd. of page 8)
· Proposition 65	
· Chemicals known to cause cancer:	
CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 106-42-3 p-Xylene

CAS: 88-06-2 2,4,6-Trichlorophenol, 98% w/w, Reagent Grade Crystal

· TLV (Threshold Limit Value)

CAS: 106-42-3 p-Xylene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Warning

· Hazard-determining components of labeling: p-Xylene · Hazard statements Flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes skin irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse.

(Contd. on page 10)

Printing date 05/16/2024

\*

Reviewed on 05/16/2024

Trade name: Chloride Standard 1.0 ppm w/v in p-Xylene

(Contd. of page 9)

	ire: Use CO2, powder or water spray to extinguish.	
	vell-ventilated place. Keep cool. contents/container in accordance with local/regional/national/international regulations.	
	afety assessment: A Chemical Safety Assessment has not been carried out.	
Chemical s	<b>ujety assessment:</b> A Chemical Sujety Assessment has not been curried but.	
Other inf	<i>formation</i>	
This inform	nation is based on our present knowledge. However, this shall not constitute a guarantee for	a
specific pro	oduct features and shall not establish a legally valid contractual relationship.	
Departmen	t issuing SDS: Environment protection department.	
Contact:		
Date of Pre	eparation / Last Revision:	
Date of pre	paration / last revision	
Revision 1.	2, 05/16/2024: Reviewed SDS for accuracy. MH/STN	
05/16/2024		
Abbreviatio	ons and acronyms:	
	ational Maritime Code for Dangerous Goods	
	artment of Transportation	
	tional Air Transport Association	
	opean Inventory of Existing Commercial Chemical Substances opean List of Notified Chemical Substances	
	al Abstracts Service (division of the American Chemical Society)	
	nal Fire Protection Association (USA)	
	dous Materials Identification System (USA)	
	e Organic Compounds (USA, EU)	
	concentration, 50 percent	
	dose, 50 percent nt, Bioaccumulative and Toxic	
	ersistent and very Bioaccumulative	
-	and Institute for Occupational Safety	
	pational Safety & Health	
	ld Limit Value	
	ible Exposure Limit	
	nended Exposure Limit	
	al Exposure Limit	
	iquids 3: Flammable liquids – Category 3	
	y - Dermal 4: Acute toxicity – Category 4 2 2: Skin corrosion/irritation – Category 2	
	pared to the previous version altered.	