

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

1 Identification

- **Product identifier**
- **Trade name:** Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007
- **Article number:** UNI002
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Toluene

Solvent naphtha (petroleum), light arom.

1,2,4-Trimethylbenzene

cumene

Ethylbenzene, Anhydrous, 99.8%

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 1 | Health = *1 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|-----------------|--|--------|
| CAS: 108-88-3 | Toluene | >96.0% |
| CAS: 64742-95-6 | Solvent naphtha (petroleum), light arom. | >0.18% |

· **Table of Nonhazardous Ingredients**

| | | |
|----------------|--------------------------------|---------|
| CAS: 7732-18-5 | Water | >0.2% |
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene | >0.18% |
| CAS: 104-76-7 | 2-Ethyl-1-hexanol | >0.06% |
| CAS: 108-67-8 | mesitylene | >0.06% |
| CAS: 526-73-8 | 1,2,3-Trimethylbenzene | >0.03% |
| CAS: 1330-20-7 | Xylene (Xylol) | >0.03% |
| CAS: 98-82-8 | cumene | >0.006% |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | >0.006% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

| | | |
|----------------|--------------------------------|---------|
| CAS: 108-88-3 | Toluene | 67 ppm |
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene | 140 ppm |
| CAS: 104-76-7 | 2-Ethyl-1-hexanol | 0.1 ppm |
| CAS: 108-67-8 | mesitylene | 140 ppm |
| CAS: 526-73-8 | 1,2,3-Trimethylbenzene | 140 ppm |
| CAS: 1330-20-7 | Xylene (Xylol) | 130 ppm |
| CAS: 98-82-8 | cumene | 50 ppm |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | 33 ppm |

· PAC-2:

| | | |
|----------------|--------------------------------|-----------|
| CAS: 108-88-3 | Toluene | 560 ppm |
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene | 360 ppm |
| CAS: 104-76-7 | 2-Ethyl-1-hexanol | 100 ppm |
| CAS: 108-67-8 | mesitylene | 360 ppm |
| CAS: 526-73-8 | 1,2,3-Trimethylbenzene | 360 ppm |
| CAS: 1330-20-7 | Xylene (Xylol) | 920* ppm |
| CAS: 98-82-8 | cumene | 300 ppm |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | 1100* ppm |

· PAC-3:

| | | |
|---------------|---------|-----------|
| CAS: 108-88-3 | Toluene | 3700* ppm |
|---------------|---------|-----------|

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 4)

| | | |
|----------------|--------------------------------|-----------|
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene | 480 ppm |
| CAS: 104-76-7 | 2-Ethyl-1-hexanol | 200 ppm |
| CAS: 108-67-8 | mesitylene | 480 ppm |
| CAS: 526-73-8 | 1,2,3-Trimethylbenzene | 480 ppm |
| CAS: 1330-20-7 | Xylene (Xylol) | 2500* ppm |
| CAS: 98-82-8 | cumene | 730 ppm |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | 1800* ppm |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

CAS: 108-88-3 Toluene

| | |
|-----|---|
| PEL | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 20 ppm BEI, OTO, A4 |

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 108-88-3 Toluene

| | |
|-----|--|
| BEI | 0.02 mg/L <i>LD50 Intraperitoneal: blood</i> <i>Time: prior to last shift of workweek</i> <i>LD50: Toluene</i> |
| | 0.03 mg/L <i>LD50 Intraperitoneal: urine</i> <i>Time: end of shift</i> <i>LD50: Toluene</i> |
| | 0.3 mg/g creatinine <i>LD50 Intraperitoneal: urine</i> <i>Time: end of shift</i> <i>LD50: o-Cresol with hydrolysis (background)</i> |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.*
- Immediately remove all soiled and contaminated clothing.*
- Wash hands before breaks and at the end of work.*
- Store protective clothing separately.*
- Avoid contact with the skin.*
- Avoid contact with the eyes and skin.*

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 6)

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|------------------------|-----------------|
| Form: | Liquid |
| Color: | Brown |
| Odor: | Aromatic |
| Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|-------------------------------------|---------------------------|
| Melting point/Melting range: | -95 °C (-139 °F) |
| Boiling point/Boiling range: | 110-111 °C (230-231.8 °F) |

· **Flash point:** 4 °C (39.2 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 535 °C (995 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 1.2 Vol % |
| Upper: | 7 Vol % |

· **Vapor pressure at 20 °C (68 °F):** 29 hPa (21.8 mm Hg)

· **Vapor pressure at 50 °C (122 °F):** 124 hPa (93 mm Hg)

· **Density at 20 °C (68 °F):** 0.86793 g/cm³ (7.24288 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water at 15 °C (59 °F): 0.5 g/l

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

| | |
|----------------------------------|-----------------|
| Dynamic at 20 °C (68 °F): | 0.6 mPas |
| Kinematic: | Not determined. |

· **Solvent content:**

| | |
|--------------------------|---------------------------|
| Organic solvents: | >96.6 % |
| Water: | >0.2 % |
| VOC content: | >96.55 % |
| | >838.0 g/l / >6.99 lb/gal |

Solids content: >0.0 %

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007

(Contd. of page 7)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|----------------|--------------------------------|----|
| CAS: 108-88-3 | Toluene | 3 |
| CAS: 1330-20-7 | Xylene (Xylol) | 3 |
| CAS: 98-82-8 | cumene | 2B |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | 2B |

- **NTP (National Toxicology Program)**

| | | |
|--------------|--------|---|
| CAS: 98-82-8 | cumene | R |
|--------------|--------|---|

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

Trade name: *Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007*

(Contd. of page 8)

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UNI993

· **UN proper shipping name**

· **DOT**

· **IMDG, IATA**

Flammable liquids, n.o.s. (Toluene)

FLAMMABLE LIQUID, N.O.S. (Toluene)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:**

F-E,S-E

· **Stowage Category**

B

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 9)

- | | |
|--|---|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE), 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

| | |
|----------------|--------------------------------|
| CAS: 108-88-3 | Toluene |
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene |
| CAS: 1330-20-7 | Xylene (Xylol) |
| CAS: 98-82-8 | cumene |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% |

· TSCA (Toxic Substances Control Act):

| | |
|--|--------|
| Toluene | ACTIVE |
| Water | ACTIVE |
| 1,2,4-Trimethylbenzene | ACTIVE |
| Solvent naphtha (petroleum), light arom. | ACTIVE |
| 2-Ethyl-1-hexanol | ACTIVE |
| mesitylene | ACTIVE |
| 1,2,3-Trimethylbenzene | ACTIVE |
| Xylene (Xylol) | ACTIVE |
| cumene | ACTIVE |
| Ethylbenzene, Anhydrous, 99.8% | ACTIVE |

· Hazardous Air Pollutants

| | |
|----------------|--------------------------------|
| CAS: 108-88-3 | Toluene |
| CAS: 1330-20-7 | Xylene (Xylol) |
| CAS: 98-82-8 | cumene |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% |

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 10)

· **Proposition 65**

· **Chemicals known to cause cancer:**

| | |
|---------------|--------------------------------|
| CAS: 98-82-8 | cumene |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

| | |
|---------------|---------|
| CAS: 108-88-3 | Toluene |
|---------------|---------|

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

| | | |
|----------------|--------------------------------|--------|
| CAS: 108-88-3 | Toluene | II |
| CAS: 95-63-6 | 1,2,4-Trimethylbenzene | II |
| CAS: 108-67-8 | mesitylene | II |
| CAS: 526-73-8 | 1,2,3-Trimethylbenzene | II |
| CAS: 1330-20-7 | Xylene (Xylol) | I |
| CAS: 98-82-8 | cumene | D, CBD |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | D |

· **TLV (Threshold Limit Value)**

| | | |
|----------------|--------------------------------|----|
| CAS: 108-88-3 | Toluene | A4 |
| CAS: 1330-20-7 | Xylene (Xylol) | A4 |
| CAS: 100-41-4 | Ethylbenzene, Anhydrous, 99.8% | A3 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Toluene
Solvent naphtha (petroleum), light arom.
1,2,4-Trimethylbenzene
cumene
Ethylbenzene, Anhydrous, 99.8%

· **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 11)

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision

Revision 1.0 05/11/2023, reviewed SDS for accuracy. STN

05/11/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/11/2023

Reviewed on 05/11/2023

**Trade name: Water Saturated Toluene with
25 ml/gal Demulsifier/ASTM D1796, D4007**

(Contd. of page 12)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
Carcinogenicity 1B: Carcinogenicity – Category 1B
Toxic to Reproduction 2: Reproductive toxicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
Aspiration Hazard 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

US