Reviewed on 07/19/2024 Printing date 07/19/2024

1 Identification

· Product identifier

· Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

· Article number: M5005

· CAS Number: 78-93-3 · EC number:

201-159-0 · Index number: 606-002-00-3

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.



H319 Causes serious eye irritation. Eye Irritation 2A

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 1)

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

CAS: 78-93-3 Methyl Ethyl Ketone

- · Identification number(s)
- · EC number: 201-159-0
- · Index number: 606-002-00-3

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 2)

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- · Protective Action Criteria for Chemicals
- · PAC-1: 200 ppm
- · PAC-2: 2700* ppm
- · **PAC-3:** 4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 3)

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 78-93-3 Methyl Ethyl Ketone

PEL Long-term value: 590 mg/m³, 200 ppm REL Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 150 ppm Long-term value: 75 ppm

BEI, Skin

· Ingredients with biological limit values:

CAS: 78-93-3 Methyl Ethyl Ketone

BEI 2 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methyl ethyl ketone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

· Body protection: Protective work clothing

9 Physical and chemical properties

(Contd. of page 4)

· Information on basic physical and chemical properties · General Information	
· Appearance:	
Form:	Liquid
Color:	Colorless
0.1	A . 1•1

Odor: Acetone-like
 Odor threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: -86.3 °C (-123.3 °F)
Boiling point/Boiling range: 79-80.5 °C (174.2-176.9 °F)

• Flash point: $-4 \,^{\circ}C \, (24.8 \,^{\circ}F)$

Flammability (solid, gaseous): Highly flammable.
 Auto igniting: 514 °C (957.2 °F)

• Decomposition temperature: Not determined.

· Ignition temperature: Not determined.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

 Lower:
 1.8 Vol %

 Upper:
 11.5 Vol %

• Vapor pressure at 20 °C (68 °F): 105 hPa (78.8 mm Hg)

• Density at 20 °C (68 °F): 0.806 g/cm³ (6.72607 lbs/gal)
• Polative density

Not determined

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water at 20 °C (68 °F): 290 g/l

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 0.4 mPas **Kinematic:** Not determined.

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 5)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1193

(Contd. on page 7)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 6) · UN proper shipping name $\cdot DOT$ Ethyl methyl ketone · IMDG, IATA Methyl Ethyl Ketone · Transport hazard class(es) $\cdot DOT$ 3 Flammable liquids · Class · Label · IMDG, IATA · Class 3 Flammable liquids · Label · Packing group II· DOT, IMDG, IATA · Environmental hazards: · Marine pollutant: No Warning: Flammable liquids · Special precautions for user · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Hazardous substance: 5000 lbs, 2270 kg · UN "Model Regulation": UN 1193 METHYL ETHYL KETONE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is not listed.
- · TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.

(Contd. on page 8)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 7)

- · Carcinogenic categories
- · EPA (Environmental Protection Agency) I
- · TLV (Threshold Limit Value) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





· Signal word Danger

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2 07/19/2024: Reviewed SDS for accuracy. MH/STN

Creation date for SDS 11-20-2014. STN

07/19/2024 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Printing date 07/19/2024 Reviewed on 07/19/2024

Trade name: Methyl Ethyl Ketone (2-Butanone), Laboratory Grade 99%

(Contd. of page 8)

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

US