Printing date 05/14/2024 Reviewed on 05/14/2024

1 Identification

· Product identifier

· Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

· Article number: HUN008

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department: Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the central nervous system, the kidneys, the liver and the respiratory system

through prolonged or repeated exposure.



GHS05 Corrosion

H314 Causes severe skin burns and eye damage. Skin Corrosion 1B

Eye Damage 1 H318 Causes serious eye damage.



Acute Toxicity - Oral 4 Acute Toxicity - Inhalation 4 Sensitization - Skin 1

H332 Harmful if inhaled. H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

(Contd. on page 2)



Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Chloroform

Acetic Acid, Glacial

Acetone

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 3)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 2)

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 64-19-7 Acetic Acid, Glacial	40.768%			
CAS: 67-64-1 Acetone	30.585%			
CAS: 67-66-3 Chloroform	28.647%			

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
CAS: 64-19-7 Acetic Acid, Glacial	5 ppm
CAS: 67-64-1 Acetone	200 ppn
CAS: 67-66-3 Chloroform	2 ppm
· PAC-2:	
CAS: 64-19-7 Acetic Acid, Glacial	35 ppm
CAS: 67-64-1 Acetone	3200* ppr
CAS: 67-66-3 Chloroform	64 ppm
· PAC-3:	
CAS: 64-19-7 Acetic Acid, Glacial	250 ppm
CAS: 67-64-1 Acetone	5700* ppn
CAS: 67-66-3 Chloroform	3,200 ppm

- US

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 4)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Comi	nonents	with	limit	values	that	require	monitoring	at th	ie work	nlace:
Comp	onems	WUIL	uuuuu	ruiues	mui	require	monuom	; ui iii	ie woin	piuce.

CAS: 64-19-7 Acetic Acid, Glacial

PEL Long-term value: 25 mg/m³, 10 ppm

REL Short-term value: 37 mg/m³, 15 ppm

Long-term value: 25 mg/m³, 10 ppm

TLV Short-term value: 15 ppm Long-term value: 10 ppm

CAS: 67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm Long-term value: 250 ppm

A4, BEI

CAS: 67-66-3 Chloroform

PEL Ceiling limit value: 240 mg/m³, 50 ppm

REL Short-term value: 9.78* mg/m³, 2* ppm *60-min; See Pocket Guide App. A

TLV Long-term value: 10 ppm

A3

(Contd. on page 6)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 67-64-1 Acetone

BEI 25 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

chemical mixture.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear

(Contd. on page 7)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

	(Contd. of page
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)
· Flash point:	-17 °C (1.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	465 °C (869 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	17 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Density at 20 °C (68 °F):	$1.03118 \ g/cm^3 \ (8.6052 \ lbs/gal)$
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	Eully missikle
Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	- 4
Organic solvents:	71.4 %
VOC content:	40.77 %
	420.4 g/l / 3.51 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 7)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
ATE (Acute Toxicity Estimate)					
Oral	LD50	1,745 mg/kg			
Dermal	<i>LD50</i>	2,600 mg/kg (rabbit)			
Inhalative	LC50/4h	10.5 mg/l			

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 67-66-3 Chloroform	2B
· NTP (National Toxicology Program)	
CAS: 67-66-3 Chloroform	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 9)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 8)

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 4 700		C	
14 Trans	nort in	torma	tion
IT II WILL	טונו נונטע	j OI III u	uvuu

•	UN-N	umber

· DOT, IMDG, IATA

UN3286

· UN proper shipping name

 $\cdot DOT$

Flammable liquid, toxic, corrosive, n.o.s. (Acetone, Chloroform,

Acetic Acid, Glacial

· IMDG, IATA

FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (Acetone, Chloroform, Acetic Acid, Glacial

,

- · Transport hazard class(es)
- $\cdot DOT$







· Class · Label

3 Flammable liquids

3, 6.1, 8

· IMDG







· Class · Label 3 Flammable liquids

3/6.1/8

 \cdot IATA









3 Flammable liquids

3 (6.1, 8)

0.1, 8)

(Contd. on page 10)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

	(Contd. of page
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	: 338
EMS Number:	F-E,S-C
Segregation groups	(SGG1) Acids
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
Segregation Code	SG5 Segregation as for class 3
	SG8 Stow "away from" class 4.1
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	11
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
guantity timulations	On cargo aircraft only: 5 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
1 2	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O. (ACETONE, CHLOROFORM, ACETIC ACID, GLACIAL
), 3 (6.1+8), II

15 Regulatory information

CAS: 67-66-3 Chloroform

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Sara

· Sara	
· Section 355 (extremely hazardous substances):	
CAS: 67-66-3 Chloroform	
· Section 313 (Specific toxic chemical listings):	
CAS: 67-66-3 Chloroform	
· TSCA (Toxic Substances Control Act):	
Acetic Acid, Glacial	ACTIVE
Acetone	ACTIVE
Chloroform	ACTIVE
· Hazardous Air Pollutants	

(Contd. on page 11)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 10)

· Proposition 65

· Chemicals known to cause cancer:

CAS: 67-66-3 Chloroform

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-66-3 Chloroform

· Carcinogenic categories

· EPA (Environ	mental Protection Agency)	
CAS: 67-64-1	Acetone	I
CAS: 67-66-3	Chloroform	B2, L, NL
mr ri (mi 1	71 71 1. YY 7 . \	<u> </u>

$\cdot TLV$	(Threshold Limit	Value)
-------------	------------------	-------	---

,	•	
CAS: 67-64-1	Acetone	A4
CAS: 67-66-3	Chloroform	<i>A3</i>

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 67-66-3 Chloroform

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS08

· Signal word Danger

GHS07 GHS02 GHS05

· Hazard-determining components of labeling:

Chloroform

Acetic Acid, Glacial

Acetone

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 12)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 11)

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 05/14/2024: Reviewed SDS for accuracy. MH/STN 05/14/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 13)

Printing date 05/14/2024 Reviewed on 05/14/2024

Trade name: Solvent Mix: 40% Acetone

40% Acetic Acid, 20% Chloroform v/v

(Contd. of page 12)

 $Flammable\ Liquids\ 2:\ Flammable\ liquids\ -\ Category\ 2$

Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

* Data compared to the previous version altered.