

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

1 Identification

- **Product identifier**
- **Trade name:** Isopropanol-
Ammonium Acetate Buffer
- **Article number:** SPE444
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS05 Corrosion

Skin Corrosion 1A

H314 Causes severe skin burns and eye damage.

Eye Damage 1

H318 Causes serious eye damage.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS05



GHS07

- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Isopropanol
Acetic Acid, Glacial

· **Hazard statements**

Highly flammable liquid and vapor.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-63-0	Isopropanol	80.0%
CAS: 64-19-7	Acetic Acid, Glacial	8.0%

- **Table of Nonhazardous Ingredients**

CAS: 7732-18-5	Water	11.0%
CAS: 631-61-8	Ammonium Acetate	1.0%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 67-63-0	Isopropanol	400 ppm
CAS: 64-19-7	Acetic Acid, Glacial	5 ppm
CAS: 631-61-8	Ammonium Acetate	3.8 mg/m ³

· **PAC-2:**

CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm
CAS: 631-61-8	Ammonium Acetate	42 mg/m ³

· **PAC-3:**

CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 64-19-7	Acetic Acid, Glacial	250 ppm
CAS: 631-61-8	Ammonium Acetate	250 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 67-63-0 Isopropanol	
PEL	Long-term value: 980 mg/m ³ , 400 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 4)

REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
CAS: 64-19-7 Acetic Acid, Glacial	
PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 15 ppm Long-term value: 10 ppm
· Ingredients with biological limit values:	
CAS: 67-63-0 Isopropanol	
BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value at 20 °C (68 °F):** <2· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** 13 °C (55.4 °F)· **Flammability (solid, gaseous):** Highly flammable.· **Auto igniting:** 425 °C (797 °F)· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower:	2 Vol %
Upper:	12 Vol %

· **Vapor pressure at 20 °C (68 °F):** 43 hPa (32.3 mm Hg)· **Density at 20 °C (68 °F):** 0.8327 g/cm³ (6.94888 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**· **Organic solvents:** 88.0 %

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 6)

Water:	11.0 %
VOC content:	88.00 % 732.8 g/l / 6.12 lb/gal

Solids content:	1.0 %
------------------------	-------

Other information	No further relevant information available.
--------------------------	--

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)		
Dermal	LD50	13,250 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 67-63-0	Isopropanol	3
--------------	-------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 7)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN2924 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Flammable liquids, corrosive, n.o.s. (Isopropanol, Acetic Acid, Glacial) |
| · DOT | |
| · IMDG, IATA | FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Acetic Acid, Glacial) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 8)

· **Label** 3, 8

· **IMDG**



· **Class** 3 Flammable liquids
· **Label** 3/8

· **IATA**



· **Class** 3 Flammable liquids
· **Label** 3 (8)

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-C

· **Segregation groups** (SGG1) Acids

· **Stowage Category** B

· **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(ISOPROPANOL
, ACETIC ACID, GLACIAL
) , 3 (8), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 9)

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-63-0 | Isopropanol

· **TSCA (Toxic Substances Control Act):**

Isopropanol

ACTIVE

Water

ACTIVE

Acetic Acid, Glacial

ACTIVE

Ammonium Acetate

ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

CAS: 631-61-8 | Ammonium Acetate

D

· **TLV (Threshold Limit Value)**

CAS: 67-63-0 | Isopropanol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02

GHS05

GHS07

· **Signal word** Danger· **Hazard-determining components of labeling:**

Isopropanol

Acetic Acid, Glacial

· **Hazard statements**

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 10)

· **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
 - Ground/bond container and receiving equipment.*
 - Use explosion-proof electrical/ventilating/lighting/equipment.*
 - Use only non-sparking tools.*
 - Take precautionary measures against static discharge.*
 - Do not breathe dusts or mists.*
 - Wash thoroughly after handling.*
 - Use only outdoors or in a well-ventilated area.*
 - Contaminated work clothing must not be allowed out of the workplace.*
 - Wear protective gloves/protective clothing/eye protection/face protection.*
 - If swallowed: Rinse mouth. Do NOT induce vomiting.*
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*
 - Continue rinsing.*
 - Immediately call a poison center/doctor.*
 - Specific treatment (see on this label).*
 - If skin irritation or rash occurs: Get medical advice/attention.*
 - Wash contaminated clothing before reuse.*
 - In case of fire: Use CO₂, powder or water spray to extinguish.*
 - Store in a well-ventilated place. Keep container tightly closed.*
 - Store in a well-ventilated place. Keep cool.*
 - Store locked up.*
 - Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
- **Date of Preparation / Last Revision:**
- **Date of preparation / last revision**
Revision 1.2, 05/29/2024: Reviewed SDS for accuracy. MH/STN
05/29/2024
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/29/2024

Reviewed on 05/29/2024

**Trade name: Isopropanol-
Ammonium Acetate Buffer**

(Contd. of page 11)

*BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Skin Corrosion 1A: Skin corrosion/irritation – Category 1A**Eye Damage 1: Serious eye damage/eye irritation – Category 1**Sensitization - Skin 1: Skin sensitisation – Category 1**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**** Data compared to the previous version altered.**

US