Printing date 05/23/2024

Reviewed on 05/23/2024

<text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text>	1 Identification	
<section-header><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></section-header>	· Product identifier	
<text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text>		
 Manufacturer/Supplier: Aguas Solutions, Inc. 913 Highway 225 DEER PARK, TX 77536 USA 800-250-2586 Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org Imergency telephone number: Chemitre: 800-249-3900 Canutec: 613-996-6666 Imergency telephone number: Chemitre: 801-249-3900 Canutec: 613-996-6666 Imergency telephone number: Chemitre: 800-249-3900 Canutec: 613-996-6666 Imergency telephone Skin Corrosion IB H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. Skin Corrosion IB H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. Skin Corrosion 1B H314 Causes serious eye damage. Skin Corrosion 1B H314 Causes an allergic skin reaction. Inbel elements The product is classified and labeled according to the Globally Harmonized System (GHS). Signal word Danger Signal statements The components of labeling: Acetic Acid, Glacial Bramoble liquid and vapor. 		
Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtree: 803-996-6666 2 Interference: 613-996-6666 2 Interference: 613-996-666 2 Interference: 613-996-66 2 Interference: 613-996-66	• Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA	AQUA
 Classification of the substance or mixture if controls of the substance of the	Technical Coordinator Sherman Nelson shermann@aquasolutions.org • Emergency telephone number: Chemtrec: 800-424-9300	
 Frammable Liquids 3 H226 Flammable liquid and vapor. Frammable Liquids 3 H226 Flammable liquid and vapor. Formable Liquids 3 H226 Flammable liquid and vapor. Formable Corrosion 1B H314 Causes severe skin burns and eye damage. For Damage 1 H318 Causes serious eye damage. For Damage 1 H318 Causes serious eye damage. Formation - Skin 1 H317 May cause an allergic skin reaction. Chabel elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS02 GHS03 GHS05 GHS07 Signal word Danger Hazard-determing components of labeling: Actic Acid, Glacial Hazard statements Flammable liquid and vapor. 	2 Hazard(s) identification	
 Flammable Liquids 3 H226 Flammable liquid and vapor. GHS05 Corrosion Skin Corrosion 1B H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. Output of the series of the series series series eye damage. GHS07 Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements She product is classified and labeled according to the Globally Harmonized System (GHS). Harard pictograms GHS02 GHS07 Signal word Danger Harard-determining components of labeling: Acetic Acid, Glacial Harard statements Flammable liquid and vapor. 	· Classification of the substance or mixture	
 GHS05 Corrosion Skin Corrosion IB H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. Operation - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS02 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flarmable liquid and vapor. 	GHS02 Flame	
 Skin Corrosion 1B H314 Causes severe skin burns and eye damage. Eye Damage 1 H318 Causes serious eye damage. To Damage 1 H318 Causes serious eye damage. To Damage 1 H318 Causes serious eye damage. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. 	Flammable Liquids 3 H226 Flammable liquid and vapor.	
Eye Damage 1H318 Causes serious eye damage. \overbrace{V} $\overbrace{GHS07}$ Sensitization - Skin 1H317 May cause an allergic skin reaction.• Label elements• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).• Hazard pictograms \overbrace{V} \overbrace{V} $\overbrace{GHS02}$ $\overbrace{GHS05}$ $\overbrace{GHS07}$ • Signal word Danger• Hazard-determining components of labeling: Acetic Acid, Glacial• Hazard statements Flammable liquid and vapor.	GHS05 Corrosion	
 GHS07 Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS02 GHS05 GHS07 GHS02 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. 	Skin Corrosion 1B H314 Causes severe skin burns and eye dama	lge.
 Sensitization - Skin 1 H317 May cause an allergic skin reaction. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Korre (GHS) (GHS05 (GHS05 (GHS07 (GHS07 (GHS0))))) Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. 	<i>Eye Damage 1</i> H318 Causes serious eye damage.	
 Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Image of the Globally Harmonized System (GHS). GHS02 GHS05 GHS07 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. 	GHS07	
 GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms 	Sensitization - Skin 1 H317 May cause an allergic skin reaction.	
 Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. (Contd. on page 2) 	· GHS label elements The product is classified and labeled according	g to the Globally Harmonized System (GHS).
 Signal word Danger Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. (Contd. on page 2) 		
 Hazard-determining components of labeling: Acetic Acid, Glacial Hazard statements Flammable liquid and vapor. (Contd. on page 2) 	GHS02 GHS05 GHS07	
Acetic Acid, Glacial • Hazard statements Flammable liquid and vapor. (Contd. on page 2)	· Signal word Danger	
• Hazard statements Flammable liquid and vapor. (Contd. on page 2)	Hazard-determining components of labeling:	
(Contd. on page 2)	· Hazard statements	
110	Flammable liquid and vapor.	(Contd. on page 2)

Printing date 05/23/2024

Trade name: Sodium Acetate Buffer Solution Reviewed on 05/23/2024

(Contd. of page 1) Causes severe skin burns and eye damage. May cause an allergic skin reaction. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 2Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3Fire = 2FIRE 2 **REACTIVITY** O Reactivity = 0 · Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

· Description: Mixture of the substances listed below with honnagaraou	s auanions.
· Dangerous components:	
CAS: 64-19-7 Acetic Acid, Glacial	43.761%
· Table of Nonhazardous Ingredients	
CAS: 7732-18-5 Water	34.136%
	(Contd. on page 3)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Sodium Acetate Buffer Solution

> (Contd. of page 2) 22.103%

CAS: 6131-90-4 Sodium Acetate Trihydrate

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
· Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
Protective Action Criteria for Chemicals
· PAC-1:

CAS: 64-19-7 Acetic Acid, Glacial

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Sodium Acetate Buffer Solution

CAS: 6131-90-4	Sodium Acetate Trihydrate	(Contd. of page 3) <i>11 mg/m³</i>
· PAC-2:		
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm
CAS: 6131-90-4	Sodium Acetate Trihydrate	120 mg/m ³
· PAC-3:		
CAS: 64-19-7	Acetic Acid, Glacial	250 ppm
CAS: 6131-90-4	Sodium Acetate Trihydrate	690 mg/m ³

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 64-19-7 Acetic Acid, Glacial

- PEL Long-term value: 25 mg/m³, 10 ppm
- REL Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
- *TLV* Short-term value: 15 ppm Long-term value: 10 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

US

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2024

Trade name: Sodium Acetate **Buffer Solution**

Reviewed on 05/23/2024

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Vinegar
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	40 °C (104 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	485 °C (905 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Sodium Acetate Buffer Solution

		(Contd. of page
Explosion limits:		
Lower:	4 Vol %	
Upper:	17 Vol %	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.09965 g/cm ³ (9.17658 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	43.8 %	
Water:	34.1 %	
VOC content:	43.76 %	
	481.2 g/l / 4.02 lb/gal	
Solids content:	22.1 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 2,422 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

(Contd. on page 7)

Printing date 05/23/2024

Trade name: Sodium Acetate Buffer Solution

(Contd. of page 6)

Reviewed on 05/23/2024

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- \cdot Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, IMDG, IATA

UN3265

(Contd. on page 8)

US

Printing date 05/23/2024

Reviewed on 05/23/2024

Buffer Solution	
	(Contd. of pa
UN proper shipping name DOT	Corrosive liquid, acidic, organic, n.o.s. (Acetic Acid, Glacial
IMDG, IATA) CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Acetic Ad Glacial)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
Class Label	8 Corrosive substances 8
Class Label	8 Corrosive substances 8
Packing group	0
DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code).	
EMS Number: Segregation groups	F-A,S-B (SGG1) Acids
Stowage Category	Α
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
	57
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
Excepten quantanes (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on pa

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Sodium Acetate Buffer Solution

(Contd. of page 8)

ACTIVE ACTIVE

· UN "Model Regulation":

UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (ACETIC ACID, GLACIAL), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

Acetic Acid, Glacial

Water

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 10)

⁻ US

Printing date 05/23/2024

Trade name: Sodium Acetate Buffer Solution

Reviewed on 05/23/2024

(Contd. of page 9) · Hazard-determining components of labeling: Acetic Acid, Glacial · Hazard statements Flammable liquid and vapor. Causes severe skin burns and eye damage. May cause an allergic skin reaction. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision:

• Date of preparation / last revision Revision 1.2, 05/23/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 04-08-2015: Creation date for SDS. STN 05/23/2024

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

(Contd. on page 11)

US

Printing date 05/23/2024

Trade name: Sodium Acetate Buffer Solution Reviewed on 05/23/2024

(Contd. of page 10)

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Eye Damage 1: Serious eye damage/eye irritation – Category 1 Sensitization - Skin 1: Skin sensitisation – Category 1 • * Data compared to the previous version altered.