

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

1 Identification

- **Product identifier**
- **Trade name:** Potassium Hydroxide 0.45 N
in Ethanol, (NIST)
- **Article number:** HAL005
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371 May cause damage to organs.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS05



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Potassium Hydroxide
Isopropanol
Methanol (Methyl Alcohol)

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 1)

- **Hazard statements**

Highly flammable liquid and vapor.
Causes severe skin burns and eye damage.
May cause damage to organs.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Call a poison center/doctor.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	61.116%
--------------	-----------------------------------	---------

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 2)

CAS: 67-56-1	Methanol (Methyl Alcohol)	3.406%
CAS: 67-63-0	Isopropanol	3.377%
CAS: 1310-58-3	Potassium Hydroxide	2.945%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-5	Water	29.158%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 3)

CAS: 67-63-0	Isopropanol	400 ppm
CAS: 1310-58-3	Potassium Hydroxide	0.18 mg/m ³

· **PAC-2:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 1310-58-3	Potassium Hydroxide	2 mg/m ³

· **PAC-3:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 1310-58-3	Potassium Hydroxide	54 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm
CAS: 67-56-1 Methanol (Methyl Alcohol)	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m ³ , 200 ppm
	Skin

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 4)

TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI
CAS: 67-63-0 Isopropanol	
PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
CAS: 1310-58-3 Potassium Hydroxide	
REL	Ceiling limit value: 2 mg/m ³
TLV	Ceiling limit value: 2 mg/m ³
· Ingredients with biological limit values:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	
BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)
CAS: 67-63-0 Isopropanol	
BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 5)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Alcohol
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172.4 °F)

- **Flash point:** 13 °C (55.4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 425 °C (797 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	3.5 Vol %
Upper:	19 Vol %

- **Vapor pressure at 20 °C (68 °F):** 59 hPa (44.3 mm Hg)

- **Density at 20 °C (68 °F):** 0.8574 g/cm³ (7.155 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	67.9 %
Water:	29.2 %
VOC content:	67.90 % 582.2 g/l / 4.86 lb/gl
· Solids content:	64.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	9,270 mg/kg (rat)
Inhalative	LC50/4 h	80.1 mg/l

CAS: 67-56-1 Methanol (Methyl Alcohol)

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

CAS: 1310-58-3 Potassium Hydroxide

Oral	LD50	273 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 67-63-0	Isopropanol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA** UN1993

· **UN proper shipping name**

· **DOT** Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol)

· **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANOL, Isopropanol)

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):** 338

· **EMS Number:** F-E,S-E

· **Segregation groups** Alkalis

· **Stowage Category** B

· **Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 1 L
 On cargo aircraft only: 5 L

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHANOL,
 METHANOL, ISOPROPANOL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 9)

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-56-1	Methanol (Methyl Alcohol)
--------------	---------------------------

CAS: 67-63-0	Isopropanol
--------------	-------------

· **TSCA (Toxic Substances Control Act):**

Ethyl Alcohol, Absolute 200 Proof

Methanol (Methyl Alcohol)

Isopropanol

Potassium Hydroxide

Water

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof
--------------	-----------------------------------

CAS: 67-56-1	Methanol (Methyl Alcohol)
--------------	---------------------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	A3
--------------	-----------------------------------	----

CAS: 67-63-0	Isopropanol	A4
--------------	-------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS05

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Potassium Hydroxide

Isopropanol

Methanol (Methyl Alcohol)

· **Hazard statements**

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.
--

May cause damage to organs.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 10)

· **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
 - Keep container tightly closed.*
 - Ground/bond container and receiving equipment.*
 - Use explosion-proof electrical/ventilating/lighting/equipment.*
 - Use only non-sparking tools.*
 - Take precautionary measures against static discharge.*
 - Do not breathe dusts or mists.*
 - Wash thoroughly after handling.*
 - Do not eat, drink or smoke when using this product.*
 - Wear protective gloves/protective clothing/eye protection/face protection.*
 - If swallowed: Rinse mouth. Do NOT induce vomiting.*
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 - IF exposed or concerned: Call a poison center/doctor.*
 - Immediately call a poison center/doctor.*
 - Specific treatment (see on this label).*
 - Wash contaminated clothing before reuse.*
 - In case of fire: Use for extinction: CO2, powder or water spray.*
 - Store in a well-ventilated place. Keep cool.*
 - Store locked up.*
 - Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

11-21-2017: review SDS for accuracy. STN

Creation date for SDS 08-03-2015. STN

11/21/2017 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/21/2017

Reviewed on 11/21/2017

**Trade name: Potassium Hydroxide 0.45 N
in Ethanol, (NIST)**

(Contd. of page 11)

*PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flam. Liq. 2: Flammable liquids – Category 2**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**STOT SE 2: Specific target organ toxicity (single exposure) – Category 2*

US