Printing date 06/11/2021 Reviewed on 06/11/2021

### 1 Identification

· Product identifier

• Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

· Article number: CMS027

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

contd. on page 2)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 1)

#### · Hazard pictograms









GHS02

GHS07

GHS05

#### · Signal word Danger

#### · Hazard-determining components of labeling:

Acetic Acid

*Methanol (Methyl Alcohol)* 

Potassium Bromide

#### · Hazard statements

Highly flammable liquid and vapor.

Harmful in contact with skin.

Causes severe skin burns and eye damage.

Causes damage to the central nervous system and the visual organs.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 3Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = 3

Fire = 2

Reactivity = 0

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 64-19-7	Acetic Acid	64.315%		
CAS: 67-56-1	Methanol (Methyl Alcohol)	20.949%		
CAS: 7758-02-3 Potassium Bromide				
· Table of Nonhazardous Ingredients				
CAS: 7732-18-5	Water	13.04%		

## 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 3)

#### · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

*Use neutralizing agent.* 

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 64-19-7	Acetic Acid	5 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm
CAS: 7758-02-3	Potassium Bromide	9.2 mg/m³
· PAC-2:		
CAS: 64-19-7	Acetic Acid	35 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 7758-02-3	Potassium Bromide	$100 \text{ mg/m}^3$
· PAC-3:		
CAS: 64-19-7	Acetic Acid	250 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 7758-02-3	Potassium Bromide	$610 \text{ mg/m}^3$

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

US

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 4)

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

111 111	s time, the remaining constituent has no known exposure timus.
CAS.	64-19-7 Acetic Acid
PEL	Long-term value: 25 mg/m³, 10 ppm
REL	Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
TLV	Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
CAS.	67-56-1 Methanol (Methyl Alcohol)
PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI

### · Ingredients with biological limit values:

#### CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9	I	nysi	icui ur	ia cr	ten	uce	u į	יייוע	per	ue	2

٠,	Inforn	natio	n	on basic	physical	and	chemical	properties
	~		•					

 $\cdot \textit{General Information}$ 

· Appearance: Form:

Form: Liquid
Color: Clear

Odor: Vinegar

Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:64 °C (147.2 °F)

• Flash point: 11 °C (51.8 °F)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

 Lower:
 4 Vol %

 Upper:
 44 Vol %

• Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg)

• Density at 20 °C (68 °F): 0.98235 g/cm³ (8.19771 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not determined.
Not determined.

(Contd. on page 7)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

		(Contd. of page
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	85.3 %	
Water:	13.0 %	
VOC content:	85.26 %	
	837.6 g/l / 6.99 lb/gal	
Solids content:	1.7 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects

· Acute toxicity:						
· <i>LD/LC50</i> 1	· LD/LC50 values that are relevant for classification:					
ATE (Acut	ATE (Acute Toxicity Estimate)					
Oral	LD50	5,666-13,218 mg/kg (rat)				
Dermal	LD50	1,648 mg/kg (rabbit)				
Inhalative	LC50/4h	612 mg/l (rat)				
CAS: 64-1	9-7 Acetic	Acid				
Dermal	LD50	1,100 mg/kg (ATE)				
CAS: 67-5	CAS: 67-56-1 Methanol (Methyl Alcohol)					
Oral	LD50	100 mg/kg (ATE)				
Dermal	LD50	300 mg/kg (ATE)				
Inhalative	LC50/4h	3 mg/l (ATE)				

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

(Contd. on page 8)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 7)

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

US

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 8)

UN-Number	
DOT, IMDG, IATA	UN2920
UN proper shipping name	
DOT	Corrosive liquids, flammable, n.o.s. (Acetic acid, glaci
	Methanol)
IMDG, IATA	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (ACETIC ACE
	GLACIAL, METHANOL)
Transport hazard class(es)	
DOT	
CORROSIVE FLAMMABLE LIQUID	
3	
Class	8 Corrosive substances
Label	8, 3
IMDG	
8	
Class	8 Corrosive substances
Label	8/3
IATA	
Â	
8	
Class	8 Corrosive substances
Label	8 (3)
Packing group	·
DOT, IMDG, IATA	II
Environmental hazards:	
Environmentai nazaras: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Keml	
EMS Number:	F-E,S-C
Segregation groups	Acids E
Stowage Code	E SW1 Protected from sources of heat.
Stowage Code	SW1 Froiectea from sources of neat.  SW2 Clear of living quarters.
Transport in bulk according to Anne	
MARPOL73/78 and the IBC Code	Not applicable.

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

	(Contd. of page 9
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml
· UN ''Model Regulation'':	Maximum net quantity per outer packaging: 500 ml  UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (ACETIC ACID, GLACIAL, METHANOL), 8 (3), II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 67-56-1 Methanol (Methyl Alcohol)

· TSCA (Toxic Substances Control Act):

Acetic Acid	ACTIVE
Methanol (Methyl Alcohol)	ACTIVE
Water	ACTIVE
Potassium Bromide	ACTIVE

· Hazardous Air Pollutants

CAS: 67-56-1 Methanol (Methyl Alcohol)

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol (Methyl Alcohol)

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

(Contd. on page 11)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 10)

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetic Acid

Methanol (Methyl Alcohol)

Potassium Bromide

· Hazard statements

Highly flammable liquid and vapor.

Harmful in contact with skin.

Causes severe skin burns and eye damage.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

Printing date 06/11/2021 Reviewed on 06/11/2021

Trade name: Electrolyte For Bromine Index (W/O Mercury) ASTM D1492

(Contd. of page 11)

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision

Revision 0.0, 09-01-2016: creation date for SDS. STN Revision 1.0 05-07-2021: updated hazard information. STN 06/11/2021 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

US