Printing date 05/22/2024

Reviewed on 05/22/2024

	Reviewed on 05/22/20
Identification	
Product identifier	
Trade name: <u>Nitrogen Stock Std.</u> 1000 ppm w/v in Iso-Octa	<u>ne</u>
Article number: MOT014	
Details of the supplier of the safety data Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	a sheet
Information department:	
Technical Coordinator Sherman Nelson shermann@aquasolutio <b>Emergency telephone number:</b> Chemtrec: 800-424-9300 Canutec: 613-996-6666	ons.org
Hazard(s) identification	
Classification of the substance or mixtu	ıre
GHS02 Flame	
Flammable Liquids 2 GHS08 Health hazard	H225 Highly flammable liquid and vapor.
Carcinogenicity 2	H351 Suspected of causing cancer.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
GHS07	
Skin Irritation 2	H315 Causes skin irritation.
	H315 Causes skin irritation. Exposure 3 H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Single Label elements	
Specific Target Organ Toxicity - Single Label elements GHS label elements The product is class	Exposure 3 H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Single Label elements GHS label elements The product is class	Exposure 3 H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Single A Label elements GHS label elements The product is class Hazard pictograms	Exposure 3 H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Single A Label elements GHS label elements The product is class Hazard pictograms GHS02 GHS07 GHS08	Exposure 3 H336 May cause drowsiness or dizziness. sified and labeled according to the Globally Harmonized System (GHS,

Printing date 05/22/2024

Reviewed on 05/22/2024

## Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

	(Contd. of page 1)
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools. Take presentioners measures against static discharge	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray Wash therewebby after handling	
Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with v	water/shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	valensnower.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/internation	al regulations.
· Classification system:	0
· NFPÅ ratings (scale 0 - 4)	
Health = 1	
Fire = $3$	
$\mathbf{V}$ Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{2} Health = 2$	
FIRE 3 Fire = 3	
<b>REACTIVITY</b> $\bigcirc$ Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
· <b>PBT:</b> Not applicable.	
· vPvB: Not applicable.	
	US –

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Nitrogen Stock Std.

1000 ppm w/v in Iso-Octane

(Contd. of page 2)

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	99.184%
CAS: 110-86-1	Pyridine	0.817%

## 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions:
  Do not allow product to reach sewage system or any water course.
  Inform respective authorities in case of seepage into water course or sewage system.
  Do not allow to enter sewers/ surface or ground water.
  Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

### · Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

## Trade name: Nitrogen Stock Std.

1000 ppm w/v in Iso-Octane

· Protective Acti	on Criteria for Chemicals	(Contd. of page 3
· PAC-1:	•	
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	230 ppm
CAS: 110-86-1	Pyridine	3 ppm
· PAC-2:	·	
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	830 ppm
CAS: 110-86-1	Pyridine	19 ppm
· PAC-3:	·	
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	5000* ppm
CAS: 110-86-1	Pyridine	3600* ppm

### 7 Handling and storage

#### · Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities • Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

TLV Long-term value: 300 ppm

CAS: 110-86-1 Pyridine

PEL Long-term value: 15 mg/m<sup>3</sup>, 5 ppm

REL Long-term value: 15 mg/m<sup>3</sup>, 5 ppm

*TLV Long-term value: 1 ppm* A3

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

### Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

(Contd. of page 4)

Exposure controls
Personal protective equipment:
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.
Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Sweetish	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	-107.4 °C (-161.3 °F)	
Boiling point/Boiling range:	98 °C (208.4 °F)	

Printing date 05/22/2024

Reviewed on 05/22/2024

#### Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

	(Contd. of page 5
· Flash point:	-12 °C (10.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	410 °C (770 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	6 Vol %
· Vapor pressure at 20 °C (68 °F):	15 hPa (11.3 mm Hg)
· Density at 20 °C (68 °F):	0.69168 g/cm³ (5.77207 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
$\cdot$ Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	<b>r):</b> Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.2 %
VOC content:	99.18 %
	686.0 g/l / 5.73 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

# 10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Nitrogen Stock Std.

1000 ppm w/v in Iso-Octane

(Contd. of page 6)

2B

### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 110-86-1 Pyridine

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · *Bioaccumulative potential* No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

(Contd. of page 7)

Transport information	
UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG IATA	Flammable liquids, n.o.s. (Octanes) FLAMMABLE LIQUID, N.O.S. (Octanes), MARINE POLLUTAN FLAMMABLE LIQUID, N.O.S. (Octanes)
Transport hazard class(es)	~ ` ` ` `
Class Label	3 Flammable liquids 3
Class Label	3 Flammable liquids 3
· IATA	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: Octany Yes Symbol (fish and tree)
Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids : 33 F-E,S-E
Stowage Category	B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

US

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2024

Reviewed on 05/22/2024

## Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

	(Contd. of page 8)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (OCTANES), 3, II

# **15 Regulatory information**

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
CAS: 110-86-1 Pyridine	
TSCA (Toxic Substances Control Act):	
2,2,4-Trimethylpentane (Iso-Octane)	ACTIVE
Pyridine	ACTIVE
Hazardous Air Pollutants	· · · ·
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	
Proposition 65	
Chemicals known to cause cancer:	
CAS: 110-86-1 Pyridine	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	I
TLV (Threshold Limit Value)	Аз
CAS: 110-86-1 Pyridine	
	I

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane



## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

(Contd. on page 11)

Printing date 05/22/2024

# Reviewed on 05/22/2024

## Trade name: Nitrogen Stock Std. 1000 ppm w/v in Iso-Octane

	(Contd. of page 10)
Date of preparation / last revision	
Revision 1.2, 05/21/2024: Reviewed SDS for accuracy. MH/STN	
05/22/2024	
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent. Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Carcinogenicity 2: Carcinogenicity – Category 2	
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3	
Aspiration Hazard 1: Aspiration hazard – Category 1	
* Data compared to the previous version altered.	
······································	US -