Printing date 05/10/2024

Reviewed on 05/10/2024

Product identifier		
Trade name: Water Standard 5% w/w		
in n-Butanol		
Article number: GEN139		
Details of the supplier of the safety data sheet		
Manufacturer/Supplier:		
Aqua Solutions, Inc. 6913 Highway 225		SOLUTIONS
DEER PARK, TX 77536		ODEO HONO
USA		
800-256-2586		
Information department:		
Technical Coordinator Sherman Nelson shermann@aquasolutions.org		
Technical Coordinator		
Sherman Nelson shermann@aquasolutions.org		
<i>Emergency telephone number:</i> <i>Chemtrec: 800-424-9300</i>		
Canutec: 613-996-6666		
Hazard(s) identification		
GHS02 Flame Flammable Liquids 3 GHS05 Corrosion	H226	Flammable liquid and vapor.
Flammable Liquids 3		Flammable liquid and vapor. Causes serious eye damage.
Flammable Liquids 3		
Flammable Liquids 3		
Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07	<i>H318</i>	Causes serious eye damage.
Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4	H318 H302	Causes serious eye damage. Harmful if swallowed.
Flammable Liquids 3 Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4 Skin Irritation 2	H318 H302 H315	Causes serious eye damage. Harmful if swallowed. Causes skin irritation.
Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4	H318 H302 H315 H335-H336	Causes serious eye damage. Harmful if swallowed. Causes skin irritation. May cause respiratory irritation. May cau
Flammable Liquids 3 Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4 Skin Irritation 2	H318 H302 H315 H335-H336	Causes serious eye damage. Harmful if swallowed. Causes skin irritation. May cause respiratory irritation. May cau drowsiness or dizziness.
Flammable Liquids 3 Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4 Skin Irritation 2 Specific Target Organ Toxicity - Single Exposure 3 Label elements GHS label elements The product is classified and la Hazard pictograms Contemportation (Contemportation)	H318 H302 H315 H335-H336	Causes serious eye damage. Harmful if swallowed. Causes skin irritation. May cause respiratory irritation. May cau drowsiness or dizziness.
Flammable Liquids 3 Flammable Liquids 3 GHS05 Corrosion Eye Damage 1 GHS07 Acute Toxicity - Oral 4 Skin Irritation 2 Specific Target Organ Toxicity - Single Exposure 3 Label elements GHS label elements The product is classified and label	H318 H302 H315 H335-H336	Causes serious eye damage. Harmful if swallowed. Causes skin irritation. May cause respiratory irritation. May cau drowsiness or dizziness.

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

	(Contd. of page
Hazard-dete	rmining components of labeling:
n-Butyl Alcol	hol
Hazard state	ments
	iquid and vapor.
Harmful if sv	vallowed.
Causes skin i	rritation.
Causes serio	us eye damage.
May cause re	espiratory irritation. May cause drowsiness or dizziness.
	ry statements
	rom heat/sparks/open flames/hot surfaces No smoking.
	l container and receiving equipment.
	n-proof electrical/ventilating/lighting/equipment.
	sparking tools.
	tionary measures against static discharge.
	ing dust/fume/gas/mist/vapors/spray
	ghly after handling.
	rink or smoke when using this product.
	doors or in a well-ventilated area.
	ive gloves/protective clothing/eye protection/face protection.
	: Call a poison center/doctor if you feel unwell.
	hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	D: Remove person to fresh air and keep comfortable for breathing.
	inse cautiously with water for several minutes. Remove contact lenses, if present and easy to d
Continue rin	
	call a poison center/doctor.
	tment (see on this label).
Rinse mouth.	
	aminated clothing and wash it before reuse.
	ion occurs: Get medical advice/attention.
	e: Use CO2, powder or water spray to extinguish.
	ll-ventilated place. Keep container tightly closed.
	ll-ventilated place. Keep cool.
Store locked	
	ontents/container in accordance with local/regional/national/international regulations.
Classification	n system: gs (scale 0 - 4)
INFFA raing	<i>s (scale 0 - 4)</i>
2	Health = 3
	Fire = 3
3 0	$e^{2}Reactivity = 0$
▼ ✓ HMIS-rating	gs (scale 0 - 4)
~	
HEALTH *	
FIRE 3	
	Reactivity = 0
	ds

• *PBT:* Not applicable. • *vPvB:* Not applicable.

(Contd. on page 3)

US

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 2)

95.0%

5.0%

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 71-36-3 n-Butyl Alcohol

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 3)

60 ppm

800 ppm

8000** ppm

See Section 13 for disposal information. • Protective Action Criteria for Chemicals

· PAC-1:

CAS: 71-36-3 n-Butyl Alcohol

· PAC-2:

CAS: 71-36-3 n-Butyl Alcohol

· PAC-3:

CAS: 71-36-3 n-Butyl Alcohol

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 71-36-3 n-Butyl Alcohol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm Skin

TLV Long-term value: 20 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

⁻US

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Distinct
Odor threshold:	Not determined.
<i>pH-value at 20 °C (68 °F):</i>	7
Change in condition	
Melting point/Melting range:	-89 °C (-128.2 °F)
Boiling point/Boiling range:	117 °C (242.6 °F)
Flash point:	35 °C (95 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	340 °C (644 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower:	1.5 Vol %

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

		(Contd. of page 5)
Upper:	9.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)	
· Density at 20 °C (68 °F):	0.8195 g/cm ³ (6.83873 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	77 g/l	
· Partition coefficient (n-octanol/wat	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	95.0 %	
Water:	5.0 %	
VOC content:	95.00 %	
	778.5 g/l / 6.50 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 526 mg/kg

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 7)

US

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 6)

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

<u>12 Ecological information</u>

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number		
· DOT, IMDG, IATA	UN1120	
· UN proper shipping name		
$\cdot DOT$	Butanols solution	
· IMDG, IATA	BUTANOLS solution	

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

	(Contd. of page
· Transport hazard class(es)	
·DOT	
3	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
3	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	111
· Environmental hazards:	
· Marine pollutant:	No
• Special precautions for user	Warning: Flammable liquids
 Hazard identification number (Kemler code). EMS Number: 	: 30 F-E,S-D
• Stowage Category	A
• Transport in bulk according to Annex II of	
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
• DOT • Quantity limitations	On passenger aircraft/rail: 60 L
· Quantity timulations	On passenger aircraft only: 220 L
· IMDG	
· ImDG · Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
• • • • • • • • • • • • • • • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1120 BUTANOLS SOLUTION, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US

Printing date 05/10/2024

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

	(Contd. of page
Section 313 (Specific toxic chemical listings):	
CAS: 71-36-3 n-Butyl Alcohol	
TSCA (Toxic Substances Control Act):	
n-Butyl Alcohol	ACTIVE
Water	ACTIVE
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 71-36-3 n-Butyl Alcohol	
TLV (Threshold Limit Value)	

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: n-Butyl Alcohol
Hazard statements Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Printing date 05/10/2024

*

Reviewed on 05/10/2024

Trade name: Water Standard 5% w/w in n-Butanol

	(Contd. of page 9)
Avoid breathing dust/fume/gas/mist/vapors/spray	(contai of page))
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse sk	in with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathin	
If in eyes: Rinse cautiously with water for several minutes. Remove conto	
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Rinse mouth.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/int	ternational regulations
• Chemical safety assessment: A Chemical Safety Assessment has not been car	
.	
16 Other information	
This information is based on our present knowledge. However, this shal	ll not constitute a guarantee for any
specific product features and shall not establish a legally valid contractual re	
Department issuing SDS: Environment protection department.	-
• Contact:	
Date of Preparation / Last Revision:	
• Date of preparation / last revision Revision 1.2, 05/08/2024: Rewiewed SDS for accuracy. MH/STN	
05/10/2024	
• Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	

- REL: Recommended Exposure Linui REL: Recommended Exposure Linui Flammable Liquids 3: Flammable liquids Category 3 Acute Toxicity Oral 4: Acute toxicity Category 4 Skin Irritation 2: Skin corrosion/irritation Category 2

 - Eye Damage 1: Serious eye damage/eye irritation Category 1 Specific Target Organ Toxicity Single Exposure 3: Specific target organ toxicity (single exposure) Category 3
 - \cdot * Data compared to the previous version altered.