Printing date 05/13/2024 Reviewed on 05/13/2024

1 Identification

· Product identifier

· Trade name: Phenol and Benzyl Alcohol

500 ppm w/v in Methanol

· Article number: GP013

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Oral 3 H301 Toxic if swallowed.

Acute Toxicity - Dermal 3 H311 Toxic in contact with skin.

Acute Toxicity - Inhalation 3 H331 Toxic if inhaled.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and the visual organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 1)

· Hazard-determining components of labeling:

Methanol

· Hazard statements

Highly flammable liquid and vapor.

Toxic if swallowed, in contact with skin or if inhaled.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed: Call a POISON CENTER or doctor/physician.

Call a poison center/doctor if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

	(Contd. of page 2)
· Dangerous components:	
CAS: 67-56-1 Methanol	99.874%
· Table of Nonhazardous Ingredients	
CAS: 100-51-6 Benzyl alcohol	0.063%
CAS: 108-95-2 Phenol	0.063%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- $\cdot \textit{After skin contact:} \ \textit{Immediately wash with water and soap and rinse thoroughly}.$
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

740 ppm

200 ppm

Safety Data Sheet acc. to OSHA HCS

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

Protective Action	n Criteria for Chemicals	(Contd. of page
<i>PAC-1</i> :	•	
CAS: 67-56-1	Methanol	530 ppn
CAS: 100-51-6	Benzyl alcohol	30 ppm
CAS: 108-95-2	Phenol	15 ppm
PAC-2:		
CAS: 67-56-1	Methanol	2,100 ppn
CAS: 100-51-6	Benzyl alcohol	52 ppm
CAS: 108-95-2	Phenol	23 ppm
PAC-3:		
CAS: 67-56-1	Methanol	7200* ppr

7 Handling and storage

CAS: 108-95-2 Phenol

- · Handling:
- · Precautions for safe handling

CAS: 100-51-6 Benzyl alcohol

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions:} \\$

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:			
CAS	: 67-56-1 Methanol		
PEL Long-term value: 260 mg/m³, 200 ppm			
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin		
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI		

(Contd. on page 5)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 4)

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear
Odor: Alcohol

(Contd. on page 6)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

	(Contd. of page
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	-97.8 °C (-144 °F) 64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower: Upper:	5.5 Vol % 44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	0.79162 g/cm³ (6.60607 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: VOC content:	100.0 % 100.00 % 791.6 g/l / 6.61 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values	that	are	relevant	for c	lassificati	on:

ATE (Acute Toxicity Estimate)

OralLD50100 mg/kgDermalLD50300 mg/kgInhalativeLC50/4h3 mg/l

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

· Carcinogenic categories

· IARC	(International	Agency for	Research on	Cancer)

CAS: 108-95-2 Phenol

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Methanol)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Methanol)
Transport hazard class(es)	
DOT	
F.M.M.ABLE LIQUID	
3	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
•	
Class Label	3 Flammable liquids
	<u> </u>
Packing group DOT, IMDG, IATA	II
	П
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code)	Warning: Flammable liquids
EMS Number:	F-E,S-E
Stowage Category	B B
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L

On cargo aircraft only: 60 L

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 8)

IMDG	
Limited quantities (LQ)	1L
· Excepted quantities $(\widetilde{E}Q)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANOL), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

	~ ***	
ĺ	· Section 355 (ex	tremely hazardous substances):
I	CAS: 108-95-2	Phenol

· Section 313 (Specific toxic chemical listings):

CAS: 67-56-1 Methanol CAS: 108-95-2 Phenol

· TSCA (Toxic Substances Control Act):

,	
Methanol	ACTIVE
Benzyl alcohol	ACTIVE
Phenol	ACTIVE

· Hazardous Air Pollutants

CAS: 67-56-1 Methanol CAS: 108-95-2 Phenol

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

CAS: 108-95-2 Phenol

D, I

· TLV (Threshold Limit Value)

CAS: 108-95-2 Phenol

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 9)

· Hazard pictograms







GHS02

GHS06

· Signal word Danger

· Hazard-determining components of labeling:

Methanol

· Hazard statements

Highly flammable liquid and vapor.

Toxic if swallowed, in contact with skin or if inhaled.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed: Call a POISON CENTER or doctor/physician.

Call a poison center/doctor if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 05/13/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0. 08-04-2016: creation date for SDS. STN

05/13/2024

(Contd. on page 11)

Printing date 05/13/2024 Reviewed on 05/13/2024

Trade name: Phenol and Benzyl Alcohol 500 ppm w/v in Methanol

(Contd. of page 10)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1

* Data compared to the previous version altered.

- US