

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

1 Identification

- **Product identifier**
- **Trade name:** Etchant Solution
- **Article number:** ND379
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS05

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric Acid

Acetic Acid

- **Hazard statements**

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 1)

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 2

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 107-21-1	Ethylene Glycol	56.818%
CAS: 7697-37-2	Nitric Acid	24.363%
CAS: 64-19-7	Acetic Acid	17.9667%

· **Table of Nonhazardous Ingredients**

CAS: 7732-18-5	Water	0.853%
----------------	-------	--------

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 2)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 107-21-1	Ethylene Glycol	30 ppm
CAS: 7697-37-2	Nitric Acid	0.16 ppm
CAS: 64-19-7	Acetic Acid	5 ppm

· **PAC-2:**

CAS: 107-21-1	Ethylene Glycol	150 ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 64-19-7	Acetic Acid	35 ppm

· **PAC-3:**

CAS: 107-21-1	Ethylene Glycol	900 ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 64-19-7	Acetic Acid	250 ppm

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 107-21-1 Ethylene Glycol

TLV	Short-term value: 10** mg/m ³ , 50* ppm Long-term value: 25* ppm *vapor fraction: **inh. fraction, aerosol only
-----	--

CAS: 7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

CAS: 64-19-7 Acetic Acid

PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

- **Breathing equipment:** Not required.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Colorless to yellow
Odor:	Light
Odor threshold:	Not determined.

· **pH-value at 20 °C (68 °F):** <2

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	83 °C (181.4 °F)

· **Flash point:** 40 °C (104 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 410 °C (770 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	3.2 Vol %
Upper:	53 Vol %

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 5)

· Vapor pressure at 20 °C (68 °F):	16 hPa (12 mm Hg)
· Density at 20 °C (68 °F):	1.17217 g/cm ³ (9.78176 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	18.0 %
Water:	0.9 %
VOC content:	17.97 %
	210.6 g/l / 1.76 lb/gl
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	18,423 mg/kg (rat)
Dermal	LD50	5,900 mg/kg (rabbit)

CAS: 107-21-1 Ethylene Glycol

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

CAS: 64-19-7 Acetic Acid

Dermal	LD50	1,100 mg/kg (ATE)
--------	------	-------------------

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 6)

Strong irritant with the danger of severe eye injury.

· **Sensitization:** *No sensitizing effects known.*

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** *No further relevant information available.*

· **Persistence and degradability** *No further relevant information available.*

· **Behavior in environmental systems:**

· **Bioaccumulative potential** *No further relevant information available.*

· **Mobility in soil** *No further relevant information available.*

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

· **Other adverse effects** *No further relevant information available.*

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

· **Recommended cleansing agent:** *Water, if necessary with cleansing agents.*

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 7)

14 Transport information

· UN-Number	UN2920
· DOT, IMDG, IATA	
· UN proper shipping name	Corrosive liquids, flammable, n.o.s. (Nitric acid, Acetic acid, glacial)
· DOT	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (NITRIC ACID, ACETIC ACID, GLACIAL)
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
· Class	8 Corrosive substances
· Label	8, 3
· IMDG	
· Class	8 Corrosive substances
· Label	8/3
· IATA	
· Class	8 Corrosive substances
· Label	8 (3)
· Packing group	II
· DOT, IMDG, IATA	
· Environmental hazards:	No
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	83
· EMS Number:	F-E,S-C
· Segregation groups	Acids
· Stowage Category	E
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 8)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 1 L

On cargo aircraft only: 30 L

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 2920 CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. (NITRIC ACID, ACETIC ACID, GLACIAL), 8 (3), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

CAS: 7697-37-2	Nitric Acid
----------------	-------------

· **Section 313 (Specific toxic chemical listings):**

CAS: 107-21-1	Ethylene Glycol
---------------	-----------------

CAS: 7697-37-2	Nitric Acid
----------------	-------------

· **TSCA (Toxic Substances Control Act):**

Ethylene Glycol

Nitric Acid

Acetic Acid

Water

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 107-21-1	Ethylene Glycol
---------------	-----------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 107-21-1	Ethylene Glycol	A4
---------------	-----------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 9)

· **Hazard pictograms**

GHS02 GHS05

· **Signal word** Danger· **Hazard-determining components of labeling:**

Nitric Acid

Acetic Acid

· **Hazard statements**

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.· **Contact:**· **Date of preparation / last revision**

12-13-2017: review SDS for accuracy. STN

Creation date for SDS 10-23-2014. STN

12/13/2017 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/13/2017

Reviewed on 12/13/2017

Trade name: Etchant Solution

(Contd. of page 10)

ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US