Printing date 08/19/2024 Reviewed on 08/19/2024

1 Identification

· Product identifier

Trade name: <u>Potassium Hydroxide 0.1 N in</u> <u>IPA NIST Traceable, ASTM D</u> 974

· Article number: ERL114

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

502 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 1)

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 67-63-0	Isopropanol	98.987%	
CAS: 1310-58-3	Potassium Hydroxide	0.76%	

(Contd. on page 3)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

 CAS: 12230-71-6
 Barium Hydroxide
 (Contd. of page 2)

 0.253%
 0.253%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1 10100111011	er de la ger en	
· PAC-1:		
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 1310-58-3	Potassium Hydroxide	0.18 mg/m^{3}
CAS: 12230-71-6	Barium Hydroxide	3.4 mg/m^3
· PAC-2:		
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 1310-58-3	Potassium Hydroxide	$2 mg/m^3$
		(Contd. on page 4

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

CAS: 12230-71-6	Barium Hydroxide	(Contd. of page 3) 420 mg/m^3
· PAC-3:		
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 1310-58-3	Potassium Hydroxide	54 mg/m³
CAS: 12230-71-6	Barium Hydroxide	$2,500 \text{ mg/m}^3$

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.

· Cont	rol parameters			
· Com	· Components with limit values that require monitoring at the workplace:			
CAS	: 67-63-0 Isopropanol			
PEL	Long-term value: 980 mg/m³, 400 ppm			
REL	Short-term value: 1225 mg/m^3 , 500 ppm Long-term value: 980 mg/m^3 , 400 ppm			
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4			
CAS	: 1310-58-3 Potassium Hydroxide			
REL	Ceiling limit value: 2 mg/m³			
TLV	Ceiling limit value: 2 mg/m³			
CAS	: 12230-71-6 Barium Hydroxide			
PEL	Long-term value: 0.5 mg/m³ as Ba			
REL	Long-term value: 0.5 mg/m³ as Ba			
	(Contd. on page 5)			

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 4)

TLV Long-term value: 0.5 mg/m³

as Ba, A4

· Ingredients with biological limit values:

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 6)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

	(Contd. of page		
Color: · Odor:	Clear to slightly turbid de l'alcool		
· Odor threshold:	l Not determined.		
· pH-value:	Not determined.		
Change in condition Melting point/Melting range: Boiling point/Boiling range:	-89.5 °C (-129.1 °F) 82 °C (179.6 °F)		
· Flash point:	12 °C (53.6 °F)		
· Flammability (solid, gaseous):	Highly flammable.		
· Auto igniting:	425 °C (797 °F)		
Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.		
· Explosion limits: Lower: Upper:	2 Vol % 12 Vol %		
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)		
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	0.79 g/cm³ (6.59255 lbs/gal) Not determined. Not determined. Not determined.		
Solubility in / Miscibility with Water:	Fully miscible.		
· Partition coefficient (n-octanol/wate	er): Not determined.		
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.		
· Solvent content: Organic solvents: VOC content:	99.0 % 98.99 % 782.0 g/l / 6.53 lb/gal		
Solids content:	0.0 %		
· Other information	No further relevant information available.		

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 6)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 39,494 mg/kg

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

US

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT	Flammable liquids, n.o.s. (Isopropanol
IMDG, IATA) FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Transport hazard class(es)	
DOT	
RAMMANE LOUIS 3 Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code) EMS Number: Stowage Category	Warning: Flammable liquids : 30 F-E,S-E B

(Contd. on page 9)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 8)

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL) 3 II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	[,] hazardous	substances):
---------------	------------	------------------------	--------------

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 67-63-0 Isopropanol

CAS: 12230-71-6 Barium Hydroxide

· TSCA (Toxic Substances Control Act):

IsopropanolACTIVEPotassium HydroxideACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 12230-71-6 Barium Hydroxide

D, CBD(inh), NL(oral)

· TLV (Threshold Limit Value)

 CAS: 67-63-0
 Isopropanol
 A4

 CAS: 12230-71-6
 Barium Hydroxide
 A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 9)

· Signal word Danger

· Hazard-determining components of labeling:

Isopropanol

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 08-19-2024: Reviewed SDS for accuracy. STN/GW

Creation date for SDS 08-06-2014. STN

08/19/2024 / 1.1

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 11)

Printing date 08/19/2024 Reviewed on 08/19/2024

Trade name: Potassium Hydroxide 0.1 N in IPA NIST Traceable, ASTM D 974

(Contd. of page 10)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* * Data compared to the previous version altered.

HS.