Printing date 06/17/2024

Reviewed on 06/17/2024


1 Identification

- · Product identifier
- Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200
- Article number: 4460
- · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification



Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200



US -

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 2)

29.204%

70.797%

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 5470-11-1 Hydroxylamine Hydrochloride

• Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

4 First-aid measures

• Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

 $\cdot \textit{After skin contact: Immediately wash with water and so ap and rinse thoroughly.}$

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- \cdot Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

Printing date 06/17/2024

*

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 3)

6 Accidental release measures
· Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
· Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· Protective Action Criteria for Chemicals
· PAC-1:
CAS: 5470-11-1 Hydroxylamine Hydrochloride 0.42 mg/m ³
· PAC-2:
CAS: 5470-11-1 Hydroxylamine Hydrochloride 4.7 mg/m ³
· PAC-3:
CAS: 5470-11-1 Hydroxylamine Hydrochloride 28 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- *Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.*
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

ÚS —

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physic General Information	cal and chemical properties	
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Odorless	
Odor threshold:	Not determined.	

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

Kevieweu	on	00/1	112

	(Contd. of page
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.02727 g/cm ³ (8.57257 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Water:	70.8 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	29.2 %
Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 6)

	tion on toxicological effects
· Acute to	•
	0 values that are relevant for classification:
,	sute Toxicity Estimate)
	LD50 342 mg/kg
Dermal	LD50 3,767 mg/kg
-	irritant effect:
	kin: Irritant to skin and mucous membranes.
	ve: Irritating effect.
	ation: Sensitization possible through skin contact.
	luct shows the following dangers according to internally approved calculation methods for preparations:
Harmful	
Irritant	
· Carcino	genic categories
· IARC (I	nternational Agency for Research on Cancer)
None of	the ingredients is listed.
· NTP (Na	ational Toxicology Program)
None of	the ingredients is listed.
· OSHA-C	Ca (Occupational Safety & Health Administration)
None of	the ingredients is listed.
12 Ecolog	ical information

- Aquatic toxicity: No further relevant information available.
- $\cdot \textit{Persistence and degradability} \textit{ No further relevant information available}.$
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN1760
· UN proper shipping name	
DOT	Corrosive liquids, n.o.s. (Hydroxylamine Hydrochloride)
IMDG	CORROSIVE LIQUID, N.O.S. (Hydroxylamine Hydrochloria MARINE POLLUTANT
·IATA	CORROSIVE LIQUID, N.O.S. (Hydroxylamine Hydrochloride)
• Transport hazard class(es)	
DOT	
UP THE	
CORROSIVE	
V	
· Class	8 Corrosive substances
· Label	8
Class	8 Corrosive substances
Label	8
IATA	·········
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substance Hydroxylamine Hydrochloride

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

	(Contd. of page 8
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code)	: 80
· EMS Number:	F-A,S-B
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
·IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (\widetilde{EQ})	Code: El
1 1 2	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1760 CORROSIVE LIQUID, N.O.S. (HYDROXYLAMIN
č	HYDROCHLORIDE), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

• Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
Water	ACTIVE
Hydroxylamine Hydrochloride	ACTIVE
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
	(Contd. on page 1)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 9)

US

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

· Hazard-determining components of labeling: Hydroxylamine Hydrochloride · Hazard statements May be corrosive to metals. Harmful if swallowed. Causes skin irritation. Causes serious eve irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. *Keep only in original container.* Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. (Contd. on page 11)

Printing date 06/17/2024

Trade name: 30% w/v Hydroxylamine Hydrochloride Solution ASTM E-200

(Contd. of page 10)

Reviewed on 06/17/2024

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department. · Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 0.1, 06/17/2024: Reviewed SDS for accuracy. MH/STN 06/17/2024 / 1.0 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Corrosive to Metals 1: Corrosive to metals – Category 1 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 • * Data compared to the previous version altered.