Printing date 05/16/2024

Reviewed on 05/16/2024

1 Identification

- · Product identifier
- Trade name: <u>Sulfur Stock Standard</u> <u>1000 ppm w/w in Diesel</u>
- · Article number: LY364
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc.
- 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification



GHS08 Health hazard

Germ Cell Mutagenicity 1A H340 May cause genetic defects.

Carcinogenicity 2	H351 Suspected of causing cancer.
Flammable Liquids 4	H227 Combustible liquid.

· Label elements

- *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*
- GHS08

· Signal word Danger

- Hazard-determining components of labeling: Fuels, diesel
 Biphenyl
 Naphthalene
 Hazard statements
 Combustible liquid.
 May cause genetic defects.
 Suspected of causing cancer.
 Precautionary statements
 Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.

(Contd. on page 2)



⁻ US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

	(Contd. of page 1)
Keep away from flames and hot surfaces. – No smoking.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF exposed or concerned: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	5.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
$\begin{array}{c} 2 \\ 0 \\ $	
· HMIS-ratings (scale 0 - 4)	
HEALTH 1 $Health = 1$	
FIRE 2 $Fire = 2$	
$\begin{array}{c} \text{REACTIVITY} \hline 0 \\ \end{array} Reactivity = 0 \\ \end{array}$	
· Other hazards	
· Results of PBT and vPvB assessment	
· PBT: Not applicable.	
• vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 68334-30-5	Fuels, diesel	90.0%
CAS: 91-20-3	Naphthalene	3.0%
CAS: 92-52-4	Biphenyl	1.5%
· Table of Nonhazardous Ingredients		
CAS: 2551-13-7	trimethyl benzene	1.5%
CAS: 544-40-1	Butyl sulfide	0.456%

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

(Contd. of page 2)

5 *Fire-fighting measures*

- · Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- \cdot Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:			
CAS: 68334-30-5	Fuels, diesel	300 mg/m ³	
CAS: 91-20-3	Naphthalene	15 ppm	
CAS: 92-52-4	Biphenyl	0.87 ppm	
· PAC-2:	· PAC-2:		
CAS: 68334-30-5	Fuels, diesel	3,300 mg/m ³	
CAS: 91-20-3	Naphthalene	83 ppm	
CAS: 92-52-4	Biphenyl	9.6 ppm	
• PAC-3:			
CAS: 68334-30-5	Fuels, diesel	20,000 mg/m ³	
CAS: 91-20-3	Naphthalene	500 ppm	
CAS: 92-52-4	Biphenyl	300 ppm	

7 Handling and storage

· Handling:

- · Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 68334-30-5 Fuels, diesel

TLV Long-term value: 100* mg/m³

as total hydrocarbons;Skin;*inh. fraction+vapor,A3

CAS: 91-20-3 Naphthalene

PELLong-term value: 50 mg/m³, 10 ppmRELShort-term value: 75 mg/m³, 15 ppm

Long-term value: 50 mg/m³, 10 ppm TLV Long-term value: 10 ppm

Skin; BEI, A3

CAS: 92-52-4 Biphenyl

PEL Long-term value: 1 mg/m³, 0.2 ppm

REL Long-term value: 1 mg/m³, 0.2 ppm

TLV Long-term value: 0.2 ppm

· Ingredients with biological limit values:

CAS: 91-20-3 Naphthalene

BEI -

LD50 Intraperitoneal: -Time: end of shift

LD50: 1-Naphthol with hydrolysis + 2-Naphthol with hydrolysis (Nq,Ns)

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately.
- **Breathing equipment:** Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

(Contd. of page 3)

US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

(Contd. of page 4)

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling.

· Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and General Information	r · · · · · · · · · · · · · · · · · · ·	
Appearance:		
Form:	Liquid	
Color:	Clear, colorless to light amber	
· Odor:	Diesel	
· Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	>60 °C (>140 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
Density:	Not determined.	
Relative density	Not determined.	
· Vapor density	Not determined.	
• Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 40 °C (104 °F):	5 mm ² /s	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	4.5 %	
	(Contd. on J	1 206

US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard

1000 ppm w/w in Diesel

(Contd. of page 5)

• Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 16,333 mg/kg (*rat*)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

CAS: 68334-30-5 Fuels, diesel

CAS: 91-20-3 Naphthalene

· NTP (National Toxicology Program)

CAS: 91-20-3 Naphthalene

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 7)

2B

2B

R

US

Printing date 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel Reviewed on 05/16/2024

(Contd. of page 6)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

 $\cdot \textit{Other adverse effects}$ No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT	NA1993
IMDG, IATA	UN1993
UN proper shipping name	
DOT	COMBUSTIBLE LIQUID, N.O.S (Fuels, diesel)
IMDG	FLAMMABLE LIQUID, N.O.S. (Fuels, diesel, Naphthalene
	Biphenyl), MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (Fuels, diesel)
Transport hazard class(es)	
DOT	
COMBUSTIBLE 3	
Class	3 Combustible liquids
Label	3
IMDG	
Class	9 Miscellaneous dangerous substances and articles
Label	9
IATA	
\sim	

US

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

	(Contd. of page
Label	9
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances Naphthalene
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code)	: 90
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
· ~	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (FUELS, DIESEL), 9, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
CAS: 91-20-3 Naphthalene	
CAS: 92-52-4 Biphenyl	
TSCA (Toxic Substances Control Act):	
Fuels, diesel	ACTIVI
Naphthalene	ACTIVI
Biphenyl	ACTIVI
Butyl sulfide	ACTIVI
Hazardous Air Pollutants	
CAS: 91-20-3 Naphthalene	
CAS: 92-52-4 Biphenyl	
Proposition 65	
Chemicals known to cause cancer:	
CAS: 91-20-3 Naphthalene	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

Printing date 05/16/2024

Reviewed on 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

• Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

\cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
CAS: 91-20-3 Na	<i>phthalene</i>	C, CBD
CAS: 92-52-4 Bij	phenyl	SC
• TLV (Threshold)	Limit Value)	
CAS: 68334-30-5	Fuels, diesel	A3
CAS: 91-20-3	Naphthalene	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Fuels, diesel **Biphenyl** Naphthalene · Hazard statements Combustible liquid. May cause genetic defects. Suspected of causing cancer. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. *Keep away from flames and hot surfaces. – No smoking.* Wear protective gloves/protective clothing/eye protection/face protection. IF exposed or concerned: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

(Contd. on page 10)

- US

Printing date 05/16/2024

Trade name: Sulfur Stock Standard 1000 ppm w/w in Diesel

Reviewed on 05/16/2024

	(Contd. of page 9)
Date of Preparation / Last Revision:	
Date of preparation / last revision	
Revision 1.2, 05/16/2024: Reviewed SDS for accuracy. MH/STN	
Revision 0.0. 10-31-2016: Creation date for SDS. STN	
05/16/2024	
• Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 4: Flammable liquids – Category 4	
Germ Cell Mutagenicity 1A: Germ cell mutagenicity – Category 1A	
Carcinogenicity 2: Carcinogenicity – Category 2	
• * Data compared to the previous version altered.	