Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Dimethylbutane 2.2-dimethylbutane Article number: 73-83-2         Cash Number: 73-83-2         200-906-8         Index number: 601-007-00-7         Details of the supplier of the safety data sheet Manufacture/Supplier: Agua Solutions, Inc. 6013 Highway 225 DEER PARK, TX 77536 USA 800-256-2586         Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org Emergency telephone number: Chemtree: 800-84-9300 Canutee: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture Contract: 800-84-9300 Canutee: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture Contract: 800-256-2586         Information Liquids 2         Hazard(s) identification         Classification of the substance or mixture Contract: 800-24-9300 Canutee: 613-996-6666         Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Contract:       Contract State Contract	Identification	
Article number: $27.83-2$ Crownber: $52.83-2$ EC number: $601-007-00-7$ Dotails of the supplier of the safety data sheet <b>Manufacturer/Supplier:</b> Aqua Solutions, Inc. $601-007-00-7$ Details of the supplier of the safety data sheet <b>Manufacturer/Supplier:</b> Aqua Solutions, Inc. $601-007-00-7$ Details of the supplier of the safety data sheet <b>Manufacturer/Supplier:</b> Again Solutions, Inc. $601-007-00-7$ DEER PARK, TX 77336       USA         800-256-2586 <b>Information department:</b> Technical Coordinator       Sherman Nelson shermann@ aquasolutions.org <b>Emergency telephone number:</b> Chemitrec: $800-424-9300$ Canutec: $613-996-6666$ <b>Hazard(s) identification Cassification of the substance or mixture</b> $$ $$ GHS02 Flame         Flammable Liquids 2       H225 Highly flammable liquid and vapor. $$ $$ $$ GHS07         Shir Irritation 1       H304 May be fatal if swallowed and enters airways. $$ $$ $$ GHS07         Shin Irritation 2       H315 Causes skin irr	Product identifier	
Article number: D4781         CAS Number: $75.83-2$ EC number: $00-906-8$ Index number: $00-100-700-7$ Details of the supplier of the safety data sheet         Mamufacturer/Supplier:         Aqua Solutions, Inc. $001-807-80-7$ DEER PARK, TX 7736         USA         800-256-2586 <b>Information department:</b> Technical Coordinator         Sherman Nelson shermann@aquasolutions.org <b>Emergency telephone number:</b> Chemtree: 800-424-9300         Canuele: 613-996-6666 <b>Hazard(s) identification Classification of the substance or mixture</b> $$ $$ <b>GHS02 Flame</b> Flammable Liquids 2       H225 Highly flammable liquid and vapor. $$ $$ <b>GHS07</b> Shin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. <b>Label elements GHS04 GHS05 Sin</b> Fristubstance is classified and labeled according to the Globally Har		
CAS Number:       75-83-2         TS-83-2       EC number:         200-906-8       Index number:         folds number:       601-007-00-7         Details of the supplier of the safety data sheet       Manufacturer/Supplier:         Aqua Solutions, Inc.       601-007-00-7         Details of the supplier of the safety data sheet       Manufacturer/Supplier:         Aqua Solutions, Inc.       601-007-00-7         DER PARK, TX 77536       USA         USA       800-256-2586         Information department:       Technical Coordinator         Sherman Nelson shermann@aquasolutions.org       Emergency telephone number:         Chanter: 810-424-9300       Canutee: 613-990-6666         Itacard(s) identification       Itacard(s) identification         Canute:: 613-990-6666       Itacard (s) identification         Classification of the substance or mixture       Itacard (s) identification         Classification of the substance or mixture       Itacard (s) GHS02 Flame         Flarmable Liquids 2       H225 Highly flammable liquid and vapor.         Itacard 1       H304 May be fatal if swallowed and enters airways.         Itacard 2       GHS07         Shin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3	2,2-dimethylbutane	
$\begin{array}{c} 75:83:2\\ CC mumber:\\ 200:906:8\\ Index number:\\ 601-007-00-7\\ \hline \\ \hline \\ Details of the supplier of the safety data sheet Manufacturer/Supplier:Aqua Solutions, Inc.6913 Highway 225DEER PARK, TX 77536USA800:256-2586\hline \\ Information department:Technical CoordinatorSherman Nelson shermann@aquasolutions.orgEmergency telephone number:Chemtre: 800-242-9300Castification of the substance or mixture\overbrace{OO} GHS02 FlameFlammable Liquids 2I 225 Highly flammable liquid and vapor.\overbrace{OO} GHS08 Health hazardAspiration Hazard 1Sherman Table Liquids 2I 300  ext{MS08} Health hazardAspiration Hazard 1I 304  ext{May} be fatal if swallowed and enters airways.\overbrace{OO} GHS07Skin Irritation 2Skin Irritation 2Shermat The substance is classified and labeled according to the Globally Harmonized System (GHBazard pictograms\overbrace{OO} GHS07\sub{OO} GHS07Skin Irritation 2Sher The substance is classified and labeled according to the Globally Harmonized System (GHBazard pictograms\overbrace{OO} GHS07Skin Irritation 2Shermat The substance is classified and labeled according to the Globally Harmonized System (GHBazard pictograms)$		
EC number:       200-906-8         Index number:       601-007-00-7         Details of the supplier of the safety data sheet       Manufacturer/Supplier:         Aqua Solutions, Inc.       6913 Highway 225         DEER PARK, TX 77536       USA         Sub0-236-2386       Information department:         Technical Coordinator       Sherman Nelson shermann@ aquasolutions.org         Emergency telephone number:       Chemre: 800-242-9300         Chemre:       Out 242-9300         Coordinator       Sherman Nelson shermann@ aquasolutions.org         Emergency telephone number:       Chemre: 800-242-9300         Chemre:       Out 242-9300         Coordinator       Sherman Nelson shermann@ aquasolutions.org         Emergency telephone number:       Chemre:         Cohemre:       Out 242-9300         Cohemre:       Out 242-9300         GHS02 Flame       H225 Highly flammable liquid and vapor.         Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Specification flacat 1       H304 May be fatal if swallowed and enters airways.         Specific Target Organ Toxicity - Single Exposure 3       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label element		
200906-8 Index number: 601-007-00-7 Details of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DER PARK, TX 77536 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtree: 800-424-9300 Canutee: 613-996-6666 Information of the substance or mixture $\widehat{Voo}$ GHS02 Flame Flammable Liquids 2 Flammable Liquids 2 Flammable Liquids 2 GHS02 Flame Flammable Liquids 2 Shi Irritation 3 Sherific Target Organ Toxicity - Single Exposure 3 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 Sherific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Sherific Target Organ Toxicity - Single Exposure 3 H346 May be fatal if swallowed and enters airways. Sherific Target Organ Toxicity - Single Exposure 3 H346 May be fatal if swallowed and enters airways. Sherific Target Organ Toxicity - Single Exposure 3 H346 May be fatal if swallowed and enters airways. Sherific Target Or		
Index number: $601-007-007$ Social TrowsDetails of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, hc. $6913$ Highway 225 DEER PARK, TX 77536 USA $800-356-3586$ Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemitre: 800-424-9300 Canute: 613-996-6666Itazard(s) identificationClassification of the substance or mixture $\widetilde{\psi}$ GHS02 FlameFlammable Liquids 2H225 Highly flammable liquid and vapor. $\widetilde{\psi}$ GHS08 Health hazard Aspiration Hazard 1H304 May be fatal if swallowed and enters airways. $\widetilde{\psi}$ GHS07Skin Irritation 2H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.Label elements CHS tabel elements CHS tabel elements CHS tabel elements CHS07 GHS07 $\widetilde{\psi}$ </td <td></td> <td></td>		
Details of the supplier of the safety data sheet Manufacturer/Supplier: Agua Solutions. Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtree: 800-424-9300 Canutec: 613-996-6666Chemtree: 800-424-9300 Canutec: 613-996-6666Hazard(s) identificationClassification of the substance or mixture Of HS02 FlameFlammable Liquids 2H225 Highly flammable liquid and vapor.Flammable Liquids 2H225 Highly flammable liquid and vapor.Of Of Skin Irritation 1H304 May be fatal if swallowed and enters airways.Skin Irritation 2H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3Skin Irritation 2H315 Cause and consistence or discussified and labeled according to the Globally Harmonized System (Ghazard pictogramsOf GHS02Of HS03Skin Irritation 2GHS03Skin Irritation 3Specific Target Organ Toxicity - Single Exposure 3H315 Cause drowsiness or dizziness.Label elements GHS04GHS07GHS07GHS07Skin Irritation 2H315 Cause drowsiness or dizziness.Label elements GHS04GHS07GHS05GHS07GHS06GHS07Shabel elements GHS04GHS07GHS07GHS08GHS07GHS09GHS08GHS09GHS07Sin Irritation 2GHS07GHS07GHS07GHS08		30L0 110M3
Manufacturer/Supplier:         Aqua Solutions, Inc.         6913 Highway 225         DEER PARK, TX 77536         USA         800-256-2586         Information department:         Technical Coordinator         Sherman Nelson shermann@aquasolutions.org         Emergency telephone number:         Chemtre:         Chemtre:         Obsolve:         GHS00 - 256-2586    Haracological and the substance or mixture          Obsolve:         GHS02 Flame    Flammable Liquids 2 H225 Highly flammable liquid and vapor.          Flammable Liquids 2         H236 Health hazard    Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.          Skin Irritation 2         Flamets         GHS07         Skin Irritation 2         Skin Irritation 2         H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3         H326 Health babel elements         GHS07         Skin Irritation 2         GHS04 Target Organ Toxicity - Single Exposure 3         H336 May cause drowsiness or dizziness.         Label elements         GHS07	601-007-00-7	
Aqua Solutions, Inc.         6913 Highway 225         6913 Highway 225         DEER PARK, TX 77336         USA         800-256-2586         Information department:         Technical Coordinator         Sherman Nelson shermann@aquasolutions.org         Emergency telephone number:         Chemtre:: 800-424-9300         Canutec: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture         Image: GHS02 Flame         Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Image: GHS08 Health hazard       H304 May be fatal if swallowed and enters airways.         Image: GHS07       GHS07         Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or diziness.         Label elements       GHS08         GHS07       Single Exposure 3         Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       GHS08         GHS03       GHS07         GHS04 </td <td></td> <td>data sheet</td>		data sheet
6 <sup>9</sup> J3 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtre: 800-424-9300 Canuete: 613-996-6666 Hazard(s) identification Classification of the substance or mixture		
DEER PARK, TX 77536 USA 800-256-2586 Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtree: 800-424-9300 Canutee: 613-996-6666		
USA 800-256-2586         Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtree: 800-424-9300 Canutec: 613-996-6666         Ilazard(s) identification         Classification of the substance or mixture $\widetilde{v}$ $\widetilde{v}$ GHS02 Flame         Flammable Liquids 2       H225 Highly flammable liquid and vapor. $\widetilde{v}$ GHS08 Health hazard         Aspiration Hazard 1       H304 May be fatal if swallowed and enters airways. $\widetilde{v}$ GHS07         Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements GHS label elements GHS label elements GHS label elements GHS label elements GHS label elements GHS GHS07       GHS07 $\widetilde{v}$		
Information department:         Technical Coordinator         Sherman Nelson shermann@aquasolutions.org         Emergency telephone number:         Chemtree: 800-424-9300         Canutee: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture $\widehat{O}$ $\widehat{O}$ GHS02 Flame         Flammable Liquids 2 $\widehat{O}$		
Technical Coordinator         Sherman Nelson shermann@aquasolutions.org         Emergency telephone number:         Chemtrec: 800-424-9300         Canute:: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture $\widetilde{V}$ GHS02 Flame         Flammable Liquids 2       H225 Highly flammable liquid and vapor. $\widetilde{V}$ GHS08 Health hazard         Aspiration Hazard 1       H304 May be fatal if swallowed and enters airways. $\widetilde{V}$ GHS07         Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       The substance is classified and labeled according to the Globally Harmonized System (Ghazard pictograms $\widetilde{V}$ $\widetilde{V}$ $\widetilde{V}$ $\widetilde{V}$ $\widetilde{V}$ $\widetilde{V}$	800-256-2586	
Sherman Nelson shermann@aquasolutions.org         Emergency telephone number:         Chemtrec: 800-424-9300         Canutec: 613-996-6666         Hazard(s) identification         Classification of the substance or mixture $\widehat{O}$ $\widehat{O}$ GHS02 Flame         Flammable Liquids 2         H225 Highly flammable liquid and vapor. $\widehat{O}$ </td <td></td> <td></td>		
Emergency telephone number: Chemtree: $800-424-9300$ Canutee: $613-996-6666$ Hazard(s) identification         Classification of the substance or mixture image: GHS02 Flame         Flammable Liquids 2       H225 Highly flammable liquid and vapor.         image: GHS08 Health hazard         Aspiration Hazard 1       H304 May be fatal if swallowed and enters airways.         image: GHS07         Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms         image: GHS02       GHS07         GHS03       GHS08		lutions or a
Chemtrec: 800-424-9300 Canutec: 613-996-6666 Hazard(s) identification Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. GHS08 Health hazard Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irritation 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS07 GHS07 Skin Irritation 2 GHS07 (GHS08) GHS07 (GHS07) Skin Irritation 2 GHS07 (GHS08) GHS07 (GHS07) GHS07 (GHS07) GHS07 (GHS07) GHS07 (GHS08) GHS07 (GHS08) GHS07 (GHS08) GHS07 (GHS08) GHS07 (GHS08)		uuunis.or g
Hazard(s) identification         Classification of the substance or mixture         GHS02 Flame         Flammable Liquids 2         H225 Highly flammable liquid and vapor.         OF Colspan= Colspan= Colspan="2">Colspan= Colspan= Colspan="2">Colspan= Colspan= Colspan="2">Colspan= Colspan= Colspan="2">Colspan= Colspan= Colspan= Colspan= Colspan= Colspan="2">Colspan= Colspan= Colspan= Colspan= Colspan= Colspan="2">Colspan= Colspan= C		
Classification of the substance or mixture $\widetilde{Vortholdow}$ GHS02 FlameFlammable Liquids 2H225 Highly flammable liquid and vapor. $\widetilde{Vortholdow}$ GHS08 Health hazardAspiration Hazard 1H304 May be fatal if swallowed and enters airways. $\widetilde{Vortholdow}$ GHS07Skin Irritation 2H315 Causes skin irritation.Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.Label elementsGHS07GHS02 $\widetilde{GHS07}$ GHS03 $\widetilde{GHS07}$ Skin Irritation 2Gause skin irritation.Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.Label elementsGHS07GHS02 $\widetilde{GHS07}$ GHS03 $\widetilde{GHS07}$ GHS04 $\widetilde{GHS07}$ GHS05 $\widetilde{GHS07}$ GHS06 $\widetilde{GHS07}$ GHS07 $\widetilde{GHS08}$	Canutec: 613-996-6666	
Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Image: Flammable Liquids 2       H225 Highly flammable liquid and vapor.         Image: Flammable Liquids 2       GHS08 Health hazard         Aspiration Hazard 1       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H304 May be fatal if swallowed and enters airways.         Image: Flammable Liquids 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Image: Flammable Liquids 2       Harmonized System (GH Hazard pictograms         Image: Flammable Liquids 2       HS02         Image: Flammable Liquids 2       HS03         Image: Flammable Liquids 2       HS04         Image: Flammable Liquids 2       HS04	Classification of the substance or m	ixture
Aspiration Hazard 1       H304 May be fatal if swallowed and enters airways.         Image: Constraint of the system o	GHS02 Flame	
Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.		
Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.		H225 Highly flammable liquid and vapor.
Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms         Image: Comparison of the temperature of tempera	Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms         Image: Comparison of the temperature of tempera	Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms         Image: Comparison of the state	Flammable Liquids 2 GHS08 Health hazard	
Skin Irritation 2       H315 Causes skin irritation.         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsiness or dizziness.         Label elements       GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms         Image: Comparison of the substance of the s	Flammable Liquids 2 GHS08 Health hazard	
Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms GHS02 GHS07 GHS08	Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1	
Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms GHS02 GHS07 GHS08	Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1	
Label elements GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms GHS02 GHS07 GHS08	Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07	H304 May be fatal if swallowed and enters airways.
GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GH Hazard pictograms GHS02 GHS07 GHS08	Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07 Skin Irritation 2	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.
	Flammable Liquids 2 Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Sing	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.
	Flammable Liquids 2 Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Sing Label elements GHS label elements The substance is	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. gle Exposure 3 H336 May cause drowsiness or dizziness.
	Flammable Liquids 2 Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Sing Label elements GHS label elements The substance is	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. gle Exposure 3 H336 May cause drowsiness or dizziness.
	Flammable Liquids 2 Flammable Liquids 2 GHS08 Health hazard Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Sing Label elements GHS label elements The substance in Hazard pictograms	H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. gle Exposure 3 H336 May cause drowsiness or dizziness.

Printing date 07/19/2024

Reviewed on 07/19/2024

## Trade name: Dimethylbutane 2,2-dimethylbutane

· Signal word Danger	(Contd. of page 1)
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
May cause drowsiness or dizziness.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Avoid release to the environment.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	5.
· Classification system:	
·NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = $3$	
$\mathbf{U}  Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE $3$ Fire = 3	
$\begin{array}{c} \text{REACTIVITY} \\ \hline 0 \end{array}  Reactivity = 0 \end{array}$	
· Other hazards	
· Results of PBT and vPvB assessment	
• <b>PBT:</b> Not applicable.	
• <b>vPvB</b> : Not applicable.	
3 Composition linformation on ingradiants	
3 Composition/information on ingredients	

#### · Chemical characterization: Substances

- CAS No. Description CAS: 75-83-2 Dimethylbutane

(Contd. on page 3)

US

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Dimethylbutane

2,2-dimethylbutane

(Contd. of page 2)

- · Identification number(s)
- EC number: 200-906-8
- Index number: 601-007-00-7

#### 4 First-aid measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
- **PAC-1:** 1,000 ppm
- **PAC-2:** 11000\*\* ppm
- PAC-3: 66000\*\*\* ppm

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- $\cdot$  Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

(Contd. on page 4)

Printing date 07/19/2024

## Trade name: Dimethylbutane 2,2-dimethylbutane

(Contd. of page 3)

Reviewed on 07/19/2024

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 75-83-2 Dimethylbutane

- REL Long-term value: 350 mg/m<sup>3</sup>, 100 ppm Ceiling limit value: 1800\* mg/m<sup>3</sup>, 510\* ppm \*15-min
- *TLV Long-term value: 200 ppm A3*

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

- Avoid contact with the eyes and skin.
- · Breathing equipment: Not required.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US –

Printing date 07/19/2024

Reviewed on 07/19/2024

#### Trade name: Dimethylbutane 2,2-dimethylbutane

(Contd. of page 4)

• Eye protection:



\*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Characteristic Not determined
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-100 °C (-148 °F)
Boiling point/Boiling range:	50 °C (122 °F)
Flash point:	-29 °C (-20.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	435 °C (815 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 55 °C (131 °F):	1,235.9 hPa (927.9 mm Hg)
Density at 20 °C (68 °F):	0.649 g/cm <sup>3</sup> (5.41591 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not determined.
Partition coefficient (n-octanol/wate	<b>r</b> ): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

Printing date 07/19/2024

Reviewed on 07/19/2024

(Contd. of page 5)

Trade name: Dimethylbutane

2,2-dimethylbutane

• Other information

No further relevant information available.

#### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

#### **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Dimethylbutane 2,2-dimethylbutane

(Contd. of page 6)

### **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

DOT HADC LATA	
DOT, IMDG, IATA	UN1208
UN proper shipping name	
DOT	Hexanes
IMDG	HEXANES, MARINE POLLUTANT
ΙΑΤΑ	HEXANES
Transport hazard class(es)	
DOT	
3	
Class	3 Flammable liquids
Label	3
IMDG	
Class	3 Flammable liquids
Label	3
ΙΑΤΑ	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Environmentally hazardous substance, liquid; Marine Pollutant
Marine pollutant:	Νο
<b>F</b>	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids

US -

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Dimethylbutane

2,2-dimethylbutane

	(Contd. of page
· EMS Number:	F-E,S-D
· Stowage Category	Ε
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not amplicable
MARFOL/5//8 and the IBC Code	Not applicable.
• Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
$\cdot$ Limited quantities (LQ)	1L
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1208 HEXANES, 3, II

#### **15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances): Substance is not listed.
- Section 313 (Specific toxic chemical listings): Substance is not listed.
- · TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.

· Carcinogenic categories

- · EPA (Environmental Protection Agency) Substance is not listed.
- TLV (Threshold Limit Value) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- *GHS label elements* The substance is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Signal word Danger
Hazard statements
Highly flammable liquid and vapor.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

(Contd. on page 9)

US

Printing date 07/19/2024

Reviewed on 07/19/2024

#### Trade name: Dimethylbutane 2,2-dimethylbutane

	(Contd. of page 8)
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Avoid release to the environment.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>s</i> .
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

#### · Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2 07/18/2024: Reviewed SDS for accuracy. MH/STN 07/19/2024 / 1.1 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Aspiration Hazard 1: Aspiration hazard – Category 1  $\cdot$  \* Data compared to the previous version altered.

US -