Printing date 06/03/2024

Reviewed on 06/03/2024

Identification	
Product identifier	
Trade name: <u>Thiophene in Benzene</u> 100 ppm w/w Stock Std.	
Article number: TEN050S	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA SOLUTIONS
Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Hazard(s) identification Classification of the substance or mixture	
	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor. H310 Fatal in contact with skin.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1 GHS08 Health hazard	H310 Fatal in contact with skin.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1 GHS08 Health hazard Germ Cell Mutagenicity 1B Carcinogenicity 1A	 H310 Fatal in contact with skin. H340 May cause genetic defects. H350 May cause cancer. H372 Causes damage to the central nervous system an the hematopoietic system through prolonged or system through prolonged prolonged prolonged prolonged prolonged prolonged prolonged pro
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1 GHS08 Health hazard Germ Cell Mutagenicity 1B Carcinogenicity 1A	H310 Fatal in contact with skin. H340 May cause genetic defects. H350 May cause cancer. H372 Causes damage to the central nervous system an
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1 GHS08 Health hazard Germ Cell Mutagenicity 1B Carcinogenicity 1A Specific Target Organ Toxicity - Repeated Exposure 1	 H310 Fatal in contact with skin. H340 May cause genetic defects. H350 May cause cancer. H372 Causes damage to the central nervous system an the hematopoietic system through prolonged o repeated exposure.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 1 GHS08 Health hazard Germ Cell Mutagenicity 1B Carcinogenicity 1A Specific Target Organ Toxicity - Repeated Exposure 1 Aspiration Hazard 1	 H310 Fatal in contact with skin. H340 May cause genetic defects. H350 May cause cancer. H372 Causes damage to the central nervous system an the hematopoietic system through prolonged o repeated exposure.

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.


(Contd. of page 1) · Hazard pictograms GHS02 GHS06 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: Benzene · Hazard statements Highly flammable liquid and vapor. Fatal in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. Causes damage to the central nervous system and the hematopoietic system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. *Ground/bond container and receiving equipment.* Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

(Contd. of page 2)



• Results of PBT and vPvB assessment

• *PBT*: Not applicable.

• **vPvB**: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

 • Dangerous components: CAS: 71-43-2 Benzene

99.999%

0.001%

· Table of Nonhazardous Ingredients

CAS: 110-02-1 Thiopene (Thiofuran), Reagent A.C.S.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

US -

Printing date 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std. Reviewed on 06/03/2024

(Contd. of page 3)

· Special hazards	s arising	from the	e substance	or mixture
-------------------	-----------	----------	-------------	------------

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 71-43-2 Benzene 5	52 ppm
· PAC-2:	
CAS: 71-43-2 Benzene 80	00 ppm
· PAC-3:	
CAS: 71-43-2 Benzene 4000)* ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

⁻ US

Printing date 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 71-43-2 Benzene

- PEL Short-term value: 15* mg/m³, 5* ppm Long-term value: 3* mg/m³, 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
- REL Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
- TLV Short-term value: (2.5) NIC-0.1 ppm Long-term value: (0.5) NIC-0.02 ppm Skin; BEI, A1

· Ingredients with biological limit values:

CAS: 71-43-2 Benzene

BEI 25 μg/g creatinine LD50 Intraperitoneal: urine Time: end of shift Parameter LD50: S-Phenylmercapturic acid (background

500 μg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: t,t-Muconic acid (background)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

(Contd. of page 4)

Reviewed on 06/03/2024

US

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

 Information on basic physical and clip General Information 	hemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Benzene
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	6 °C (42.8 °F)
Boiling point/Boiling range:	80 °C (176 °F)
· Flash point:	-11 °C (12.2 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	555 °C (1,031 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8 Vol %
· Vapor pressure at 20 °C (68 °F):	100 hPa (75 mm Hg)
· Vapor pressure at 50 °C (122 °F):	350 hPa (262.5 mm Hg)
· Density at 20 °C (68 °F):	0.88 g/cm ³ (7.3436 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
\cdot Evaporation rate	Not determined.

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

		(Contd. of page
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.7 g/l	
· Partition coefficient (n-octanol/w	v ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	880.0 g/l / 7.34 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 48 mg/kg (mouse)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Very toxic

Danger through skin absorption.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 71-43-2 Benzene

(Contd. on page 8)

¹⁸

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

(Contd. of page 7)

K

· NTP (National Toxicology Program)

CAS: 71-43-2 Benzene

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 71-43-2 Benzene

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1992	
UN proper shipping name		
DOT	Flammable liquids, toxic, n.o.s. (Benzene)	
IMDG, IATA	FLAMMABLE LIQUID, TOXIC, N.O.S. (Benzene)	
Transport hazard class(es) DOT		
Class	3 Flammable liquids	

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

	(Contd. of page
Label	3, 6.1
IMDG	
- Class	3 Flammable liquids
Label	3/6.1
IATA	
- Class	3 Flammable liquids
Label	3 (6.1)
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	
EMS Number:	F-E,S-D
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: Forbidden
~ ·	On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0
······································	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE),
or mouth requiring i	(6.1), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 71-43-2 Benzene

(Contd. on page 10)

US -

A, K/L

A1

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

(Contd. of page 9) • TSCA (Toxic Substances Control Act): ACTIVE Thiopene (Thiofuran), Reagent A.C.S. ACTIVE · Hazardous Air Pollutants CAS: 71-43-2 Benzene

· Proposition 65

Benzene

· Chemicals known to cause cancer:

CAS: 71-43-2 Benzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

CAS: 71-43-2 Benzene

· Chemicals known to cause developmental toxicity:

CAS: 71-43-2 Benzene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-43-2 Benzene

• TLV (Threshold Limit Value)

CAS: 71-43-2 Benzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 71-43-2 Benzene

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Benzene

· Hazard statements

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes skin irritation.

Causes serious eye irritation. May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system and the hematopoietic system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

(Contd. on page 11)

Printing date 06/03/2024

Reviewed on 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std.

	(Contd. of page 10)
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Do not get in eyes, on skin, or on clothing.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with	n water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact len	
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international/	onal regulations.
	0
National regulations:	
Additional classification according to Decree on Hazardous Materials:	
Carcinogenic hazardous material group III (dangerous).	
Information about limitation of use:	
Workers are not allowed to be exposed to the hazardous carcinogenic materials	contained in this preparation.
Exceptions can be made by the authorities in certain cases.	
Chemical safety assessment: A Chemical Safety Assessment has not been carried o	put.
Other information	
This information is based on our present knowledge. However, this shall not o	constitute a guarantee for any

specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- Date of preparation / last revision Revision 1.2, 06/03/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 11-05-2015: creation date for SDS. STN 06/03/2024
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

US

Printing date 06/03/2024

Trade name: Thiophene in Benzene 100 ppm w/w Stock Std. Reviewed on 06/03/2024

(Contd. of page 11)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Dermal 1: Acute toxicity - Category 1 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B Carcinogenicity 1A: Carcinogenicity – Category 1A Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1 Aspiration Hazard 1: Aspiration hazard - Category 1 \cdot * Data compared to the previous version altered. 11S